

gconfmm

2.28.3

Generated by Doxygen 1.9.5

1 gconfmm Reference Manual	1
1.1 Description	1
1.2 Basic Usage	1
2 Module Index	3
2.1 Modules	3
3 Namespace Index	5
3.1 Namespace List	5
4 Hierarchical Index	7
4.1 Class Hierarchy	7
5 Class Index	9
5.1 Class List	9
6 Module Documentation	11
6.1 gconfmm Enums and Flags	11
6.1.1 Detailed Description	11
6.1.2 Enumeration Type Documentation	11
6.1.2.1 ClientErrorHandlingMode	11
6.1.2.2 ClientPreloadType	12
6.1.2.3 UnsetFlags	12
6.1.2.4 ValueType	12
7 Namespace Documentation	13
7.1 Glib Namespace Reference	13
7.2 Gnome Namespace Reference	13
7.3 Gnome::Conf Namespace Reference	13
7.3.1 Typedef Documentation	14
7.3.1.1 Callback	14
7.3.1.2 ValuePair	14
7.3.1.3 ValueTypePair	14
7.3.2 Function Documentation	14
7.3.2.1 init()	14
8 Class Documentation	15
8.1 Gnome::Conf::ChangeSet Class Reference	15
8.2 Gnome::Conf::Client Class Reference	15
8.2.1 Detailed Description	18
8.2.2 Member Typedef Documentation	18
8.2.2.1 SListHandleBools	18
8.2.2.2 SListHandleFloats	18
8.2.2.3 SListHandleInts	19
8.2.3 Constructor & Destructor Documentation	19

8.2.3.1 ~Client()	19
8.2.4 Member Function Documentation	19
8.2.4.1 add_dir()	19
8.2.4.2 all_dirs()	19
8.2.4.3 all_entries()	20
8.2.4.4 change_set_commit()	20
8.2.4.5 change_set_from_current()	21
8.2.4.6 change_set_reverse()	21
8.2.4.7 clear_cache()	22
8.2.4.8 dir_exists()	22
8.2.4.9 error()	23
8.2.4.10 get()	23
8.2.4.11 get_bool()	23
8.2.4.12 get_bool_list()	23
8.2.4.13 get_client_for_engine()	23
8.2.4.14 get_default_client()	24
8.2.4.15 get_default_from_schema()	24
8.2.4.16 get_entry() [1/2]	24
8.2.4.17 get_entry() [2/2]	25
8.2.4.18 get_float()	25
8.2.4.19 get_float_list()	26
8.2.4.20 get_int()	26
8.2.4.21 get_int_list()	26
8.2.4.22 get_pair()	27
8.2.4.23 get_schema()	27
8.2.4.24 get_schema_list()	27
8.2.4.25 get_string()	28
8.2.4.26 get_string_list()	28
8.2.4.27 get_without_default()	28
8.2.4.28 gobj() [1/2]	28
8.2.4.29 gobj() [2/2]	29
8.2.4.30 gobj_copy()	29
8.2.4.31 key_is_writable()	29
8.2.4.32 notify()	29
8.2.4.33 notify_add()	30
8.2.4.34 notify_remove()	30
8.2.4.35 on_error()	30
8.2.4.36 on_unreturned_error()	31
8.2.4.37 on_value_changed()	31
8.2.4.38 preload()	31
8.2.4.39 recursive_unset()	31
8.2.4.40 remove_dir()	32

8.2.4.41 set() [1/6]	32
8.2.4.42 set() [2/6]	32
8.2.4.43 set() [3/6]	33
8.2.4.44 set() [4/6]	33
8.2.4.45 set() [5/6]	34
8.2.4.46 set() [6/6]	34
8.2.4.47 set_bool_list()	35
8.2.4.48 set_error_handling()	35
8.2.4.49 set_float_list()	35
8.2.4.50 set_int_list()	35
8.2.4.51 set_schema_list()	36
8.2.4.52 set_string_list()	36
8.2.4.53 signal_error()	36
8.2.4.54 signal_value_changed()	36
8.2.4.55 suggest_sync()	36
8.2.4.56 unset()	37
8.2.4.57 value_changed()	37
8.2.5 Friends And Related Function Documentation	37
8.2.5.1 wrap()	37
8.3 Gnome::Conf::Entry Class Reference	38
8.3.1 Detailed Description	39
8.3.2 Constructor & Destructor Documentation	39
8.3.2.1 Entry() [1/4]	39
8.3.2.2 Entry() [2/4]	39
8.3.2.3 Entry() [3/4]	39
8.3.2.4 ~Entry()	39
8.3.2.5 Entry() [4/4]	40
8.3.3 Member Function Documentation	40
8.3.3.1 get_is_default()	40
8.3.3.2 get_is_writable()	40
8.3.3.3 get_key()	40
8.3.3.4 get_schema_name()	40
8.3.3.5 get_value()	40
8.3.3.6 gobj() [1/2]	41
8.3.3.7 gobj() [2/2]	41
8.3.3.8 gobj_copy()	41
8.3.3.9 operator=()	41
8.3.3.10 set_is_default()	41
8.3.3.11 set_is_writable()	41
8.3.3.12 set_schema_name()	42
8.3.3.13 set_value()	42
8.3.4 Friends And Related Function Documentation	42

8.3.4.1 wrap()	42
8.3.5 Member Data Documentation	42
8.3.5.1 gobject_	42
8.4 Gnome::Conf::Error Class Reference	43
8.4.1 Detailed Description	43
8.4.2 Member Enumeration Documentation	43
8.4.2.1 Code	43
8.4.3 Constructor & Destructor Documentation	44
8.4.3.1 Error() [1/2]	44
8.4.3.2 Error() [2/2]	44
8.4.4 Member Function Documentation	44
8.4.4.1 code()	44
8.5 Gnome::Conf::Schema Class Reference	45
8.5.1 Constructor & Destructor Documentation	46
8.5.1.1 Schema() [1/3]	46
8.5.1.2 Schema() [2/3]	46
8.5.1.3 Schema() [3/3]	46
8.5.1.4 ~Schema()	46
8.5.2 Member Function Documentation	46
8.5.2.1 get_car_type()	46
8.5.2.2 get_cdr_type()	46
8.5.2.3 get_default_value()	47
8.5.2.4 get_list_type()	47
8.5.2.5 get_locale()	47
8.5.2.6 get_long_desc()	47
8.5.2.7 get_owner()	47
8.5.2.8 get_short_desc()	47
8.5.2.9 get_type()	47
8.5.2.10 gobj() [1/2]	47
8.5.2.11 gobj() [2/2]	48
8.5.2.12 gobj_copy()	48
8.5.2.13 operator=()	48
8.5.2.14 set_car_type()	48
8.5.2.15 set_cdr_type()	48
8.5.2.16 set_default_value()	48
8.5.2.17 set_list_type()	48
8.5.2.18 set_locale()	49
8.5.2.19 set_long_desc()	49
8.5.2.20 set_owner()	49
8.5.2.21 set_short_desc()	49
8.5.2.22 set_type()	49
8.5.3 Friends And Related Function Documentation	49

8.5.3.1 wrap()	49
8.5.4 Member Data Documentation	50
8.5.4.1 gobject_	50
8.6 Gnome::Conf::SetInterface Class Reference	50
8.6.1 Detailed Description	51
8.6.2 Member Function Documentation	51
8.6.2.1 set() [1/7]	51
8.6.2.2 set() [2/7]	51
8.6.2.3 set() [3/7]	51
8.6.2.4 set() [4/7]	52
8.6.2.5 set() [5/7]	52
8.6.2.6 set() [6/7]	52
8.6.2.7 set() [7/7]	52
8.6.2.8 set_bool_list()	52
8.6.2.9 set_float_list()	53
8.6.2.10 set_int_list()	53
8.6.2.11 set_schema_list()	53
8.6.2.12 set_string_list()	53
8.7 Gnome::Conf::Value Class Reference	53
8.7.1 Detailed Description	55
8.7.2 Constructor & Destructor Documentation	55
8.7.2.1 Value() [1/3]	56
8.7.2.2 Value() [2/3]	56
8.7.2.3 ~Value()	56
8.7.2.4 Value() [3/3]	56
8.7.3 Member Function Documentation	56
8.7.3.1 get_bool()	56
8.7.3.2 get_bool_list()	57
8.7.3.3 get_car()	57
8.7.3.4 get_cdr()	57
8.7.3.5 get_float()	57
8.7.3.6 get_float_list()	57
8.7.3.7 get_int()	58
8.7.3.8 get_int_list()	58
8.7.3.9 get_list_type()	58
8.7.3.10 get_schema()	58
8.7.3.11 get_schema_list()	58
8.7.3.12 get_string()	59
8.7.3.13 get_string_list()	59
8.7.3.14 get_type()	59
8.7.3.15 gobj() [1/2]	59
8.7.3.16 gobj() [2/2]	59

8.7.3.17 gobj_copy()	60
8.7.3.18 operator=()	60
8.7.3.19 set() [1/5]	60
8.7.3.20 set() [2/5]	60
8.7.3.21 set() [3/5]	60
8.7.3.22 set() [4/5]	60
8.7.3.23 set() [5/5]	61
8.7.3.24 set_bool_list()	61
8.7.3.25 set_car()	61
8.7.3.26 set_cdr()	61
8.7.3.27 set_float_list()	62
8.7.3.28 set_int_list()	62
8.7.3.29 set_list_type()	62
8.7.3.30 set_schema_list()	62
8.7.3.31 set_string_list()	63
8.7.3.32 to_string()	63
8.7.4 Friends And Related Function Documentation	63
8.7.4.1 wrap()	63
8.7.5 Member Data Documentation	63
8.7.5.1 gobject_	64
Index	65

Chapter 1

gconfmm Reference Manual

1.1 Description

gconfmm is the official C++ interface for the GConf client API for storing and retrieving configuration data. See [Gnome::Conf::Client](#).

1.2 Basic Usage

Include the gconfmm header:

```
#include <gconfmm.h>
```

(You may include individual headers, such as `gconfmm/client.h` instead.)

If your source file is `program.cc`, you can compile it with:

```
g++ program.cc -o program `pkg-config --cflags --libs gconfmm-2.6`
```

Alternatively, if using autoconf, use the following in `configure.ac`:

```
PKG_CHECK_MODULES([GCONFMM], [gconfmm-2.4])
```

Then use the generated `GCONFMM_CFLAGS` and `GCONFMM_LIBS` variables in the project `Makefile.am` files. For example:

```
program_CPPFLAGS = $(GCONFMM_CFLAGS)
program_LDADD = $(GCONFMM_LIBS)
```


Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

gconfmm Enums and Flags	11
-----------------------------------	----

Chapter 3

Namespace Index

3.1 Namespace List

Here is a list of all namespaces with brief descriptions:

Glib	13
Gnome	13
Gnome::Conf	13

Chapter 4

Hierarchical Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

Glib::Error	
Gnome::Conf::Error	43
Glib::Object	
Gnome::Conf::Client	15
Gnome::Conf::Entry	38
Gnome::Conf::Schema	45
Gnome::Conf::SetInterface	50
Gnome::Conf::ChangeSet	15
Gnome::Conf::Client	15
Gnome::Conf::Value	53

Chapter 5

Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Gnome::Conf::ChangeSet	
A ChangeSet is a set of changes to the GConf database that can be committed and reversed easily	15
Gnome::Conf::Client	
The main Gnome::Conf object	15
Gnome::Conf::Entry	
An Entry stores an entry from a GConf "directory", including a key-value pair, the name of the Schema applicable to this entry, whether the value is a default value, and whether GConf can write a new value at this key	38
Gnome::Conf::Error	
Exception class for Gnome::Conf::Client errors	43
Gnome::Conf::Schema	45
Gnome::Conf::SetInterface	
Common Interface for key-value settable objects	50
Gnome::Conf::Value	
Wrapper for primitive types	53

Chapter 6

Module Documentation

6.1 gconfmm Enums and Flags

Enumerations

- enum `Gnome::Conf::ClientErrorHandlingMode` {
 `Gnome::Conf::CLIENT_HANDLE_NONE` ,
 `Gnome::Conf::CLIENT_HANDLE_UNRETURNED` ,
 `Gnome::Conf::CLIENT_HANDLE_ALL` }
- enum `Gnome::Conf::ClientPreloadType` {
 `Gnome::Conf::CLIENT_PRELOAD_NONE` ,
 `Gnome::Conf::CLIENT_PRELOAD_ONELEVEL` ,
 `Gnome::Conf::CLIENT_PRELOAD_RECURSIVE` }
- enum `Gnome::Conf::ValueType` {
 `Gnome::Conf::VALUE_INVALID` ,
 `Gnome::Conf::VALUE_STRING` ,
 `Gnome::Conf::VALUE_INT` ,
 `Gnome::Conf::VALUE_FLOAT` ,
 `Gnome::Conf::VALUE_BOOL` ,
 `Gnome::Conf::VALUE_SCHEMA` ,
 `Gnome::Conf::VALUE_LIST` ,
 `Gnome::Conf::VALUE_PAIR` }
- enum `Gnome::Conf::UnsetFlags` { `Gnome::Conf::UNSET_INCLUDING_SCHEMA_NAMES` }

6.1.1 Detailed Description

6.1.2 Enumeration Type Documentation

6.1.2.1 ClientErrorHandlingMode

```
enum Gnome::Conf::ClientErrorHandlingMode
```

Enumerator

CLIENT_HANDLE_NONE	
CLIENT_HANDLE_UNRETURNED	
CLIENT_HANDLE_ALL	

6.1.2.2 ClientPreloadType

enum `Gnome::Conf::ClientPreloadType`

Enumerator

CLIENT_PRELOAD_NONE	
CLIENT_PRELOAD_ONELEVEL	
CLIENT_PRELOAD_RECURSIVE	

6.1.2.3 UnsetFlags

enum `Gnome::Conf::UnsetFlags`

Enumerator

UNSET_INCLUDING_SCHEMA_NAMES	
------------------------------	--

6.1.2.4 ValueType

enum `Gnome::Conf::ValueType`

Enumerator

VALUE_INVALID	
VALUE_STRING	
VALUE_INT	
VALUE_FLOAT	
VALUE_BOOL	
VALUE_SCHEMA	
VALUE_LIST	
VALUE_PAIR	

Chapter 7

Namespace Documentation

7.1 Glib Namespace Reference

7.2 Gnome Namespace Reference

Namespaces

- namespace [Conf](#)

7.3 Gnome::Conf Namespace Reference

Classes

- class [ChangeSet](#)
A [ChangeSet](#) is a set of changes to the GConf database that can be committed and reversed easily.
- class [Client](#)
The main [Gnome::Conf](#) object.
- class [Entry](#)
An [Entry](#) stores an entry from a GConf "directory", including a key-value pair, the name of the [Schema](#) applicable to this entry, whether the value is a default value, and whether GConf can write a new value at this key.
- class [Error](#)
Exception class for [Gnome::Conf::Client](#) errors.
- class [Schema](#)
- class [SetInterface](#)
Common Interface for key-value settable objects.
- class [Value](#)
Wrapper for primitive types.

Typedefs

- typedef **std::pair**< [Value](#), [Value](#) > [ValuePair](#)
- typedef **std::pair**< [ValueType](#), [ValueType](#) > [ValueTypePair](#)
- typedef sigc::slot< void, guint, [Entry](#) > [Callback](#)

Enumerations

- enum [ClientErrorHandlingMode](#) {
 [CLIENT_HANDLE_NONE](#) ,
 [CLIENT_HANDLE_UNRETURNED](#) ,
 [CLIENT_HANDLE_ALL](#) }
- enum [ClientPreloadType](#) {
 [CLIENT_PRELOAD_NONE](#) ,
 [CLIENT_PRELOAD_ONELEVEL](#) ,
 [CLIENT_PRELOAD_RECURSIVE](#) }
- enum [ValueType](#) {
 [VALUE_INVALID](#) ,
 [VALUE_STRING](#) ,
 [VALUE_INT](#) ,
 [VALUE_FLOAT](#) ,
 [VALUE_BOOL](#) ,
 [VALUE_SCHEMA](#) ,
 [VALUE_LIST](#) ,
 [VALUE_PAIR](#) }
- enum [UnsetFlags](#) { [UNSET_INCLUDING_SCHEMA_NAMES](#) }

Functions

- void [init](#) ()

7.3.1 Typedef Documentation

7.3.1.1 Callback

```
typedef sigc::slot<void, guint, Entry> Gnome::Conf::Callback
```

7.3.1.2 ValuePair

```
typedef std::pair<Value, Value> Gnome::Conf::ValuePair
```

7.3.1.3 ValueTypePair

```
typedef std::pair<ValueType, ValueType> Gnome::Conf::ValueTypePair
```

7.3.2 Function Documentation

7.3.2.1 init()

```
void Gnome::Conf::init ( )
```

Chapter 8

Class Documentation

8.1 Gnome::Conf::ChangeSet Class Reference

A [ChangeSet](#) is a set of changes to the GConf database that can be committed and reversed easily.

```
#include <gconfmm/changeset.h>
```

Inheritance diagram for Gnome::Conf::ChangeSet:

8.2 Gnome::Conf::Client Class Reference

The main [Gnome::Conf](#) object.

```
#include <gconfmm/client.h>
```

Inheritance diagram for Gnome::Conf::Client:

Collaboration diagram for Gnome::Conf::Client:

Public Types

- typedef Glib::SListHandle< int, BasicTypeTraits< int > > [SListHandleInts](#)
- typedef Glib::SListHandle< bool, BasicTypeTraits< bool > > [SListHandleBools](#)
- typedef Glib::SListHandle< double, BasicTypeTraits< double > > [SListHandleFloats](#)

Public Member Functions

- virtual [~Client](#) ()
- GConfClient * [gobj](#) ()

Provides access to the underlying C GObject.
- const GConfClient * [gobj](#) () const

Provides access to the underlying C GObject.
- GConfClient * [gobj_copy](#) ()

Provides access to the underlying C instance. The caller is responsible for unrefing it. Use when directly setting fields in structs.
- void [add_dir](#) (const Glib::ustring &dir, [ClientPreloadType](#) preload=CLIENT_PRELOAD_NONE)

Add a directory to the list of directories the [Client](#) will watch.
- void [remove_dir](#) (const Glib::ustring &dir)

Remove a directory from the list of directories the [Client](#) will watch.
- guint [notify_add](#) (const Glib::ustring &namespace_section, [Callback](#) callback)

Request notification of changes to namespace_section.
- void [notify_remove](#) (guint cnxn)

Cancel a notification request.
- void [notify](#) (const Glib::ustring &key)

Emits the value_changed signal and notifies listeners as if key had been changed.
- void [set_error_handling](#) ([ClientErrorHandlingMode](#) mode)
- void [clear_cache](#) ()

Clear the client-side cache.
- void [preload](#) (const Glib::ustring &dirname, [ClientPreloadType](#) type)

Preloads a directory.
- [Value](#) [get](#) (const Glib::ustring &key) const

Get the value of a configuration key.
- [Value](#) [get_without_default](#) (const Glib::ustring &key) const

Get the value of a configuration key, without falling back to the default if the key has not been set.
- [Value](#) [get_default_from_schema](#) (const Glib::ustring &key) const

Get the default value of this key by looking it up in the appropriate schema.
- [Entry](#) [get_entry](#) (const Glib::ustring &key, bool use_schema_default=true) const

Get the complete [Entry](#) of the specified key.
- [Entry](#) [get_entry](#) (const Glib::ustring &key, const char *locale, bool use_schema_default=true) const

Get the complete [Entry](#) of the specified key.
- void [unset](#) (const Glib::ustring &key)

Unset a configuration key.
- void [recursive_unset](#) (const Glib::ustring &key, [UnsetFlags](#) flags=UNSET_INCLUDING_SCHEMA_NAMES)

Unsets all keys below key, including key itself.
- Glib::SListHandle< [Entry](#) > [all_entries](#) (const Glib::ustring &dir) const

Retrieve all keys in the given configuration directory.
- Glib::SListHandle< Glib::ustring > [all_dirs](#) (const Glib::ustring &dir) const

Retrieve all subdirectories of a given configuration directory.
- void [suggest_sync](#) ()

Suggest to the GConf server that a sync of cached data to stable storage would be appropriate now.
- bool [dir_exists](#) (const Glib::ustring &p1) const

Determine whether a given configuration directory exists.
- bool [key_is_writable](#) (const Glib::ustring &p1) const

Determine whether a given configuration key is writeable by the application.
- double [get_float](#) (const Glib::ustring &key) const

Get the float value at the given configuration key.

- gint [get_int](#) (const Glib::ustring &key) const
Get the integer at the given configuration key.
- bool [get_bool](#) (const Glib::ustring &key) const
Get the boolean at the given configuration key.
- Glib::ustring [get_string](#) (const Glib::ustring &key) const
Get the string at the given configuration key.
- [Schema](#) [get_schema](#) (const Glib::ustring &key) const
Get the [Schema](#) at the given configuration key.
- SListHandle_ValueInt [get_int_list](#) (const Glib::ustring &key) const
Get the list of integers at the given configuration key.
- SListHandle_ValueBool [get_bool_list](#) (const Glib::ustring &key) const
Get the list of booleans at the given configuration key.
- SListHandle_ValueFloat [get_float_list](#) (const Glib::ustring &key) const
Get the list of doubles at the given configuration key.
- SListHandle_ValueSchema [get_schema_list](#) (const Glib::ustring &key) const
Get the list of Schemas at the given configuration key.
- SListHandle_ValueString [get_string_list](#) (const Glib::ustring &key) const
Get the list of strings at the given configuration key.
- ValuePair [get_pair](#) (const Glib::ustring &key, [ValueTypePair](#) types) const
Get the pair at the given configuration key.
- void [set](#) (const Glib::ustring &key, int **what**)
Set the given configuration key to the specified integer value.
- void [set](#) (const Glib::ustring &key, bool **what**)
Set the given configuration key to the specified boolean value.
- void [set](#) (const Glib::ustring &key, double **what**)
Set the given configuration key to the specified double value.
- void [set](#) (const Glib::ustring &key, const Glib::ustring & **what**)
Set the given configuration key to the specified string.
- void [set](#) (const Glib::ustring &key, const [Schema](#) & **what**)
Set the given configuration key to the specified [Schema](#).
- void [set](#) (const Glib::ustring &key, const [Value](#) & **what**)
Set the given configuration key to the specified [Value](#).
- void [set_int_list](#) (const Glib::ustring &key, const SListHandleInts & **what**)
- void [set_bool_list](#) (const Glib::ustring &key, const SListHandleBools & **what**)
- void [set_float_list](#) (const Glib::ustring &key, const SListHandleFloats & **what**)
- void [set_schema_list](#) (const Glib::ustring &key, const Glib::SListHandle< [Schema](#) > & **what**)
- void [set_string_list](#) (const Glib::ustring &key, const Glib::SListHandle< Glib::ustring > & **what**)
- [ChangeSet](#) [change_set_from_current](#) (const Glib::SArray &[set](#))
Create a [ChangeSet](#) from the current values of the configuration database.
- void [change_set_commit](#) ([ChangeSet](#) &[set](#), bool remove_committed)
Commit the [ChangeSet](#) to the configuration database.
- [ChangeSet](#) [change_set_reverse](#) (const [ChangeSet](#) &[set](#))
Creates a [ChangeSet](#) to reverse the effects of the given [ChangeSet](#).
- Glib::SignalProxy2< void, const Glib::ustring &, const [Value](#) & > [signal_value_changed](#) ()
A signal emitted when a value changes.
- void [value_changed](#) (const Glib::ustring &key, const [Value](#) &value)
- Glib::SignalProxy1< void, const Glib::Error & > [signal_error](#) ()
A signal emitted when an error occurs.
- void [error](#) (const Glib::Error &error)

Static Public Member Functions

- static Glib::RefPtr< [Client](#) > [get_default_client](#) ()
Get the default client object for this application.
- static Glib::RefPtr< [Client](#) > [get_client_for_engine](#) (GConfEngine *engine)

Protected Member Functions

- virtual void [on_value_changed](#) (const Glib::ustring &key, const [Value](#) &value)
- virtual void [on_unreturned_error](#) (const Glib::Error &error)
- virtual void [on_error](#) (const Glib::Error &error)

Related Functions

(Note that these are not member functions.)

- Glib::RefPtr< [Gnome::Conf::Client](#) > [wrap](#) (GConfClient *object, bool take_copy=false)
A Glib::wrap() method for this object.

8.2.1 Detailed Description

The main [Gnome::Conf](#) object.

This class allows you to interface with the [Gnome](#) configuration system. Generally, it stores key-value pairs. The keys have an hierarchical namespace, with elements separated by slashes. The values are either typed primitives (int, bool, string, float or a [Schema](#)), or lists of primitives or pairs of primitives (for limits on the compound values, see [Value](#)). For conventions on the names of keys, see the GConf documentation.

8.2.2 Member Typedef Documentation

8.2.2.1 SListHandleBools

```
typedef Glib::SListHandle< bool, BasicTypeTraits<bool> > Gnome::Conf::Client::SListHandleBools
```

8.2.2.2 SListHandleFloats

```
typedef Glib::SListHandle< double, BasicTypeTraits<double> > Gnome::Conf::Client::SListHandleFloats
```

8.2.2.3 SListHandleInts

```
typedef Glib::SListHandle< int, BasicTypeTraits<int> > Gnome::Conf::Client::SListHandleInts
```

8.2.3 Constructor & Destructor Documentation

8.2.3.1 ~Client()

```
virtual Gnome::Conf::Client::~~Client ( ) [virtual]
```

8.2.4 Member Function Documentation

8.2.4.1 add_dir()

```
void Gnome::Conf::Client::add_dir (
    const Glib::ustring & dir,
    ClientPreloadType preload = CLIENT_PRELOAD_NONE )
```

Add a directory to the list of directories the [Client](#) will watch.

Any changes to keys below this directory will cause the "value_changed" signal to be emitted. When you add the directory, you can request that the [Client](#) preloads its contents - see ClientPreloadType for details.

Added directories may not overlap. That is, if you add "/foo", you may not add "/foo/bar". However you can add "/foo" and "/bar". You can also add "/foo" multiple times; if you add a directory multiple times, it will not be removed until you call [remove_dir\(\)](#) an equal number of times.

Parameters

<i>dir</i>	the directory to watch.
<i>preload</i>	the preload type (if any) to be performed.

8.2.4.2 all_dirs()

```
Glib::SListHandle< Glib::ustring > Gnome::Conf::Client::all_dirs (
    const Glib::ustring & dir ) const
```

Retrieve all subdirectories of a given configuration directory.

Parameters

<i>dir</i>	the configuration directory to scan.
------------	--------------------------------------

Returns

a container with the names of the subdirectories.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.3 all_entries()

```
Glib::SListHandle< Entry > Gnome::Conf::Client::all_entries (
    const Glib::ustring & dir ) const
```

Retrieve all keys in the given configuration directory.

Get all the configuration keys in the given directory, without recursion.

Parameters

<i>dir</i>	the configuration directory to scan.
------------	--------------------------------------

Returns

a container with the names of the configuration keys.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.4 change_set_commit()

```
void Gnome::Conf::Client::change_set_commit (
    ChangeSet & set,
    bool remove_committed )
```

Commit the [ChangeSet](#) to the configuration database.

Commits the configuration changes in the [ChangeSet](#) to the database. If `remove_committed` is `true`, all successfully committed keys will be removed from the [ChangeSet](#). If an error occurs, a [Gnome::Conf::Error](#) will be thrown. This operation is not atomic - an error will be thrown on the first error.

Parameters

<i>set</i>	the ChangeSet to commit.
<i>remove_committed</i>	whether to remove successfully-commited keys from the ChangeSet .

Exceptions

Gnome::Conf::Error	
------------------------------------	--

See also

[ChangeSet](#)**8.2.4.5 change_set_from_current()**

```
ChangeSet Gnome::Conf::Client::change_set_from_current (
    const Glib::SArray & set )
```

Create a [ChangeSet](#) from the current values of the configuration database.

Creates a [ChangeSet](#) containing the current values of all the keys listed in the *set*. For instance, this could be used in a preferences dialog as an undo operation.

Parameters

<i>set</i>	A container of the configuration keys to backup.
------------	--

Returns

the [ChangeSet](#) with the current values.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

See also

[ChangeSet](#)**8.2.4.6 change_set_reverse()**

```
ChangeSet Gnome::Conf::Client::change_set_reverse (
    const ChangeSet & set )
```

Creates a [ChangeSet](#) to reverse the effects of the given [ChangeSet](#).

Creates a [ChangeSet](#) that contains the current values of the keys in `set`, effectively creating a back-up of the values in the database that will be modified when the `set` will be committed. For instance, this allows you to create a back-up changeset to use in case of errors, or an undo facility for preferences.

Parameters

<code>set</code>	the ChangeSet to reverse.
------------------	---

Returns

the reverse [ChangeSet](#).

Exceptions

Gnome::Conf::Error	
------------------------------------	--

See also

[ChangeSet](#)

8.2.4.7 clear_cache()

```
void Gnome::Conf::Client::clear_cache ( )
```

Clear the client-side cache.

8.2.4.8 dir_exists()

```
bool Gnome::Conf::Client::dir_exists (
    const Glib::ustring & p1 ) const
```

Determine whether a given configuration directory exists.

Returns

true if the directory exists.

Exceptions

Gnome::Conf::Error .	
--------------------------------------	--

8.2.4.9 error()

```
void Gnome::Conf::Client::error (
    const Glib::Error & error )
```

8.2.4.10 get()

```
Value Gnome::Conf::Client::get (
    const Glib::ustring & key ) const
```

Get the value of a configuration key.

@parameter key: the configuration key to retrieve.

Returns

the [Value](#) of the key.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.11 get_bool()

```
bool Gnome::Conf::Client::get_bool (
    const Glib::ustring & key ) const
```

Get the boolean at the given configuration key.

8.2.4.12 get_bool_list()

```
SListHandle_ValueBool Gnome::Conf::Client::get_bool_list (
    const Glib::ustring & key ) const
```

Get the list of booleans at the given configuration key.

8.2.4.13 get_client_for_engine()

```
static Glib::RefPtr< Client > Gnome::Conf::Client::get_client_for_engine (
    GConfEngine * engine ) [static]
```

8.2.4.14 `get_default_client()`

```
static Glib::RefPtr< Client > Gnome::Conf::Client::get_default_client ( ) [static]
```

Get the default client object for this application.

The object is a Singleton, so you will always get the same instance. Most applications should use this.

8.2.4.15 `get_default_from_schema()`

```
Value Gnome::Conf::Client::get_default_from_schema (
    const Glib::ustring & key ) const
```

Get the default value of this key by looking it up in the appropriate schema.

@parameter key: the configuration key to retrieve.

Returns

the default [Value](#) of the key.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.16 `get_entry()` [1/2]

```
Entry Gnome::Conf::Client::get_entry (
    const Glib::ustring & key,
    bool use_schema_default = true ) const
```

Get the complete [Entry](#) of the specified key.

Uses the default locale

Parameters

<i>key</i>	the configuration key to retrieve.
<i>use_schema_default</i>	whether to fall back to the Schema default value if the specified configuration key has not been set.

Returns

an [Entry](#) for the corresponding configuration key.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.17 `get_entry()` [2/2]

```
Entry Gnome::Conf::Client::get_entry (
    const Glib::ustring & key,
    const char * locale,
    bool use_schema_default = true ) const
```

Get the complete [Entry](#) of the specified key.

Parameters

<i>key</i>	the configuration key to retrieve.
<i>locale</i>	the locale for the user-visible strings in the Entry 's Schema . Use 0 to use the default.
<i>use_schema_default</i>	whether to fall back to the Schema default value if the specified configuration key has not been set.

Returns

an [Entry](#) for the corresponding configuration key.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.18 `get_float()`

```
double Gnome::Conf::Client::get_float (
    const Glib::ustring & key ) const
```

Get the float value at the given configuration key.

Throws an error if the key does not contain the appropriate type.

Parameters

<i>key</i>	the configuration key to fetch.
------------	---------------------------------

Returns

the value at the specified configuration key.

Exceptions

<i>Gnome::Conf::Error</i>	
---	--

8.2.4.19 get_float_list()

```
SListHandle_ValueFloat Gnome::Conf::Client::get_float_list (
    const Glib::ustring & key ) const
```

Get the list of doubles at the given configuration key.

8.2.4.20 get_int()

```
gint Gnome::Conf::Client::get_int (
    const Glib::ustring & key ) const
```

Get the integer at the given configuration key.

8.2.4.21 get_int_list()

```
SListHandle_ValueInt Gnome::Conf::Client::get_int_list (
    const Glib::ustring & key ) const
```

Get the list of integers at the given configuration key.

If the given key is not a list, or the list elements are not of the appropriate type, an error will be thrown.

Parameters

<i>key</i>	the configuration key that contains the list.
------------	---

Returns

a Glib::SListHandle of the appropriate type.

Exceptions

<i>Gnome::Conf::Error</i>	
---	--

8.2.4.22 get_pair()

```
ValuePair Gnome::Conf::Client::get_pair (
    const Glib::ustring & key,
    ValueTypePair types ) const
```

Get the pair at the given configuration key.

The pair's elements must have the types given in `types` respectively. If the value is not a pair or the types do not match, an error will be thrown.

Parameters

<i>key</i>	the configuration key that contains the pair.
<i>types</i>	a pair of the expected types of the values.

Returns

a ValuePair.

Exceptions

<i>Gnome::Conf::Error</i>	
---	--

8.2.4.23 get_schema()

```
Schema Gnome::Conf::Client::get_schema (
    const Glib::ustring & key ) const
```

Get the [Schema](#) at the given configuration key.

8.2.4.24 get_schema_list()

```
SListHandle_ValueSchema Gnome::Conf::Client::get_schema_list (
    const Glib::ustring & key ) const
```

Get the list of Schemas at the given configuration key.

8.2.4.25 get_string()

```
Glib::ustring Gnome::Conf::Client::get_string (
    const Glib::ustring & key ) const
```

Get the string at the given configuration key.

8.2.4.26 get_string_list()

```
SListHandle_ValueString Gnome::Conf::Client::get_string_list (
    const Glib::ustring & key ) const
```

Get the list of strings at the given configuration key.

8.2.4.27 get_without_default()

```
Value Gnome::Conf::Client::get_without_default (
    const Glib::ustring & key ) const
```

Get the value of a configuration key, without falling back to the default if the key has not been set.

In that case, the type of the value will be `VALUE_INVALID`.

Parameters

<i>key</i>	the configuration key to retrieve.
------------	------------------------------------

Returns

the [Value](#) of the key.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.28 gobj() [1/2]

```
GConfClient * Gnome::Conf::Client::gobj ( ) [inline]
```

Provides access to the underlying C GObject.

8.2.4.29 gobj() [2/2]

```
const GConfClient * Gnome::Conf::Client::gobj ( ) const [inline]
```

Provides access to the underlying C GObject.

8.2.4.30 gobj_copy()

```
GConfClient * Gnome::Conf::Client::gobj_copy ( )
```

Provides access to the underlying C instance. The caller is responsible for unrefing it. Use when directly setting fields in structs.

8.2.4.31 key_is_writable()

```
bool Gnome::Conf::Client::key_is_writable (
    const Glib::ustring & p1 ) const
```

Determine whether a given configuration key is writeable by the application.

Returns

true if the key is writeable.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.32 notify()

```
void Gnome::Conf::Client::notify (
    const Glib::ustring & key )
```

Emits the value_changed signal and notifies listeners as if key had been changed.

Parameters

key	The key that has changed.
-----	---------------------------

@newin2p24

8.2.4.33 `notify_add()`

```
guint Gnome::Conf::Client::notify_add (
    const Glib::ustring & namespace_section,
    Callback callback )
```

Request notification of changes to `namespace_section`.

This includes the key `namespace_section` itself, and any keys below it. For the notification to happen, `namespace_section` must be equal to or below one of the directories added with `add_dir()`. You can still call `notify_add()` for other directories, but no notification will be received until you add a directory above or equal to `namespace_section`. One implication of this is that `remove_dir()` temporarily disables notifications that were below the removed directory.

The callback will be called with the key that changed and the [Entry](#) that holds the new [Value](#). If the [Value](#) has a type of `VALUE_INVALID`, then the key has been unset.

The function returns a connection ID you can use when calling `notify_remove()`.

Parameters

<code>namespace_section</code>	the namespace section for which notification is required.
<code>callback</code>	the sigc::slot to call when the a key under <code>namespace_section</code> changes.

Returns

a connection id that can be passed to `notify_remove()` to cancel the notification request.

8.2.4.34 `notify_remove()`

```
void Gnome::Conf::Client::notify_remove (
    guint cnxn )
```

Cancel a notification request.

Parameters

<code>cnxn</code>	a connection id, previously returned by <code>notify_add()</code>
-------------------	---

See also

[notify_add\(\)](#)

8.2.4.35 `on_error()`

```
virtual void Gnome::Conf::Client::on_error (
    const Glib::Error & error ) [protected], [virtual]
```

8.2.4.36 on_unreturned_error()

```
virtual void Gnome::Conf::Client::on_unreturned_error (
    const Glib::Error & error ) [protected], [virtual]
```

8.2.4.37 on_value_changed()

```
virtual void Gnome::Conf::Client::on_value_changed (
    const Glib::ustring & key,
    const Value & value ) [protected], [virtual]
```

8.2.4.38 preload()

```
void Gnome::Conf::Client::preload (
    const Glib::ustring & dirname,
    ClientPreloadType type )
```

Preloads a directory.

Normally this happens automatically with [add_dir\(\)](#), but if you've called [clear_cache\(\)](#) you may need to do it again.

See also

[add_dir\(\)](#)

8.2.4.39 recursive_unset()

```
void Gnome::Conf::Client::recursive_unset (
    const Glib::ustring & key,
    UnsetFlags flags = UNSET_INCLUDING_SCHEMA_NAMES )
```

Unsets all keys below *key*, including *key* itself.

If any unset fails, it continues on to unset as much as it can. The first failure is then thrown as an exception.

Parameters

<i>key</i>	The configuration key to unset.
<i>flags</i>	Change how the unset is done.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

@newin2p24

8.2.4.40 remove_dir()

```
void Gnome::Conf::Client::remove_dir (
    const Glib::ustring & dir )
```

Remove a directory from the list of directories the [Client](#) will watch.

See also

[add_dir\(\)](#)

8.2.4.41 set() [1/6]

```
void Gnome::Conf::Client::set (
    const Glib::ustring & key,
    bool what ) [virtual]
```

Set the given configuration key to the specified boolean value.

Set the given configuration key to the specified integer value.

Parameters

<i>key</i>	the configuration key to set.
<i>what</i>	the value to set it to.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

ifile "/builddir/build/BUILD/gconfmm-2.28.3/gconf/gconfmm/client.h"

Implements [Gnome::Conf::SetInterface](#).

8.2.4.42 set() [2/6]

```
void Gnome::Conf::Client::set (
    const Glib::ustring & key,
    const Glib::ustring & what ) [virtual]
```

Set the given configuration key to the specified string.

Set the given configuration key to the specified integer value.

Parameters

<i>key</i>	the configuration key to set.
<i>what</i>	the value to set it to.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

ifile "/builddir/build/BUILD/gconfmm-2.28.3/gconf/gconfmm/client.h"

Implements [Gnome::Conf::SetInterface](#).

8.2.4.43 set() [3/6]

```
void Gnome::Conf::Client::set (  
    const Glib::ustring & key,  
    const Schema & what ) [virtual]
```

Set the given configuration key to the specified [Schema](#).

Set the given configuration key to the specified integer value.

Parameters

<i>key</i>	the configuration key to set.
<i>what</i>	the value to set it to.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

ifile "/builddir/build/BUILD/gconfmm-2.28.3/gconf/gconfmm/client.h"

Implements [Gnome::Conf::SetInterface](#).

8.2.4.44 set() [4/6]

```
void Gnome::Conf::Client::set (  
    const Glib::ustring & key,  
    const Value & what ) [virtual]
```

Set the given configuration key to the specified [Value](#).

Set the given configuration key to the specified integer value.

Parameters

<i>key</i>	the configuration key to set.
<i>what</i>	the value to set it to.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

ifile "/builddir/build/BUILD/gconfmm-2.28.3/gconf/gconfmm/client.h"

Implements [Gnome::Conf::SetInterface](#).

8.2.4.45 set() [5/6]

```
void Gnome::Conf::Client::set (  
    const Glib::ustring & key,  
    double what ) [virtual]
```

Set the given configuration key to the specified double value.

Set the given configuration key to the specified integer value.

Parameters

<i>key</i>	the configuration key to set.
<i>what</i>	the value to set it to.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

ifile "/builddir/build/BUILD/gconfmm-2.28.3/gconf/gconfmm/client.h"

Implements [Gnome::Conf::SetInterface](#).

8.2.4.46 set() [6/6]

```
void Gnome::Conf::Client::set (  
    const Glib::ustring & key,  
    int what ) [virtual]
```

Set the given configuration key to the specified integer value.

Parameters

<i>key</i>	the configuration key to set.
<i>what</i>	the value to set it to.

Exceptions

Gnome::Conf::Error	
------------------------------------	--

Implements [Gnome::Conf::SetInterface](#).

8.2.4.47 set_bool_list()

```
void Gnome::Conf::Client::set_bool_list (
    const Glib::ustring & key,
    const SListHandleBools & what )
```

8.2.4.48 set_error_handling()

```
void Gnome::Conf::Client::set_error_handling (
    ClientErrorHandlingMode mode )
```

8.2.4.49 set_float_list()

```
void Gnome::Conf::Client::set_float_list (
    const Glib::ustring & key,
    const SListHandleFloats & what )
```

8.2.4.50 set_int_list()

```
void Gnome::Conf::Client::set_int_list (
    const Glib::ustring & key,
    const SListHandleInts & what )
```

8.2.4.51 set_schema_list()

```
void Gnome::Conf::Client::set_schema_list (
    const Glib::ustring & key,
    const Glib::SListHandle< Schema > & what )
```

8.2.4.52 set_string_list()

```
void Gnome::Conf::Client::set_string_list (
    const Glib::ustring & key,
    const Glib::SListHandle< Glib::ustring > & what )
```

8.2.4.53 signal_error()

```
Glib::SignalProxy1< void, const Glib::Error & > Gnome::Conf::Client::signal_error ( )
```

A signal emitted when an error occurs.

This signal will be emitted when an error occurs, right before the throw() of the error.

Prototype:

```
void on_my_error(const Glib::Error& error)
```

8.2.4.54 signal_value_changed()

```
Glib::SignalProxy2< void, const Glib::ustring &, const Value & > Gnome::Conf::Client::signal←
_value_changed ( )
```

A signal emitted when a value changes.

This signal will only be called for directories added with [add_dir\(\)](#).

Prototype:

```
void on_my_value_changed(const Glib::ustring& key, const Value& value)
```

8.2.4.55 suggest_sync()

```
void Gnome::Conf::Client::suggest_sync ( )
```

Suggest to the GConf server that a sync of cached data to stable storage would be appropriate now.

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.56 unset()

```
void Gnome::Conf::Client::unset (
    const Glib::ustring & key )
```

Unset a configuration key.

Parameters

<i>key</i>	the configuration key to unset.
------------	---------------------------------

Exceptions

<i>Gnome::Conf::Error.</i>	
----------------------------	--

8.2.4.57 value_changed()

```
void Gnome::Conf::Client::value_changed (
    const Glib::ustring & key,
    const Value & value )
```

8.2.5 Friends And Related Function Documentation**8.2.5.1 wrap()**

```
Glib::RefPtr< Gnome::Conf::Client > wrap (
    GConfClient * object,
    bool take_copy = false ) [related]
```

A Glib::wrap() method for this object.

Parameters

<i>object</i>	The C instance.
<i>take_copy</i>	False if the result should take ownership of the C instance. True if it should take a new copy or ref.

Returns

A C++ instance that wraps this C instance.

The documentation for this class was generated from the following file:

- gconfmm/client.h

8.3 Gnome::Conf::Entry Class Reference

An [Entry](#) stores an entry from a GConf "directory", including a key-value pair, the name of the [Schema](#) applicable to this entry, whether the value is a default value, and whether GConf can write a new value at this key.

```
#include <gconfmm/entry.h>
```

Collaboration diagram for Gnome::Conf::Entry:

Public Member Functions

- [Entry](#) ()
- [Entry](#) (GConfEntry *castitem, bool make_a_copy=false)
- [Entry](#) (const [Entry](#) &src)
- [Entry](#) & [operator=](#) (const [Entry](#) &src)
- [~Entry](#) ()
- GConfEntry * [gobj](#) ()
- const GConfEntry * [gobj](#) () const
- GConfEntry * [gobj_copy](#) () const
- *Provides access to the underlying C instance. The caller is responsible for freeing it. Use when directly setting fields in structs.*
- [Entry](#) (const Glib::ustring &key, const [Value](#) &value)
- *Construct an [Entry](#) with the given key and value.*
- void [set_value](#) (const [Value](#) &val)
- *Set the [Value](#) of the entry.*
- void [set_schema_name](#) (const Glib::ustring &val)
- *Set the [Schema](#) name of the entry.*
- void [set_is_default](#) (bool is_default=true)
- *Set whether the value has originated from the default given in the [Schema](#).*
- void [set_is_writable](#) (bool is_writable=true)
- *Set whether the given configuration key is writeable.*
- [Value](#) [get_value](#) () const
- *Retrieve the value of the entry.*
- Glib::ustring [get_schema_name](#) () const
- *Retrieve the [Schema](#) name associated with the given entry.*
- Glib::ustring [get_key](#) () const
- bool [get_is_default](#) () const
- bool [get_is_writable](#) () const

Protected Attributes

- GConfEntry * [gobject_](#)

Related Functions

(Note that these are not member functions.)

- [Gnome::Conf::Entry wrap](#) (GConfEntry *object, bool take_copy=false)
A Glib::wrap() method for this object.

8.3.1 Detailed Description

An [Entry](#) stores an entry from a GConf "directory", including a key-value pair, the name of the [Schema](#) applicable to this entry, whether the value is a default value, and whether GConf can write a new value at this key.

The key should be an absolute key, not a relative key.

8.3.2 Constructor & Destructor Documentation

8.3.2.1 Entry() [1/4]

```
Gnome::Conf::Entry::Entry ( )
```

8.3.2.2 Entry() [2/4]

```
Gnome::Conf::Entry::Entry (
    GConfEntry * castitem,
    bool make_a_copy = false ) [explicit]
```

8.3.2.3 Entry() [3/4]

```
Gnome::Conf::Entry::Entry (
    const Entry & src )
```

8.3.2.4 ~Entry()

```
Gnome::Conf::Entry::~Entry ( )
```

8.3.2.5 Entry() [4/4]

```
Gnome::Conf::Entry::Entry (
    const Glib::ustring & key,
    const Value & value )
```

Construct an [Entry](#) with the given key and value.

8.3.3 Member Function Documentation

8.3.3.1 get_is_default()

```
bool Gnome::Conf::Entry::get_is_default ( ) const
```

8.3.3.2 get_is_writable()

```
bool Gnome::Conf::Entry::get_is_writable ( ) const
```

8.3.3.3 get_key()

```
Glib::ustring Gnome::Conf::Entry::get_key ( ) const
```

8.3.3.4 get_schema_name()

```
Glib::ustring Gnome::Conf::Entry::get_schema_name ( ) const
```

Retrieve the [Schema](#) name associated with the given entry.

8.3.3.5 get_value()

```
Value Gnome::Conf::Entry::get_value ( ) const
```

Retrieve the value of the entry.

Returns

a copy the entry's value.

8.3.3.6 gobj() [1/2]

```
GConfEntry * Gnome::Conf::Entry::gobj ( ) [inline]
```

8.3.3.7 gobj() [2/2]

```
const GConfEntry * Gnome::Conf::Entry::gobj ( ) const [inline]
```

8.3.3.8 gobj_copy()

```
GConfEntry * Gnome::Conf::Entry::gobj_copy ( ) const
```

Provides access to the underlying C instance. The caller is responsible for freeing it. Use when directly setting fields in structs.

8.3.3.9 operator=()

```
Entry & Gnome::Conf::Entry::operator= (
    const Entry & src )
```

8.3.3.10 set_is_default()

```
void Gnome::Conf::Entry::set_is_default (
    bool is_default = true )
```

Set whether the value has originated from the default given in the [Schema](#).

8.3.3.11 set_is_writable()

```
void Gnome::Conf::Entry::set_is_writable (
    bool is_writable = true )
```

Set whether the given configuration key is writeable.

8.3.3.12 set_schema_name()

```
void Gnome::Conf::Entry::set_schema_name (
    const Glib::ustring & val )
```

Set the [Schema](#) name of the entry.

8.3.3.13 set_value()

```
void Gnome::Conf::Entry::set_value (
    const Value & val )
```

Set the [Value](#) of the entry.

8.3.4 Friends And Related Function Documentation

8.3.4.1 wrap()

```
Gnome::Conf::Entry wrap (
    GConfEntry * object,
    bool take_copy = false ) [related]
```

A Glib::wrap() method for this object.

Parameters

<i>object</i>	The C instance.
<i>take_copy</i>	False if the result should take ownership of the C instance. True if it should take a new copy or ref.

Returns

A C++ instance that wraps this C instance.

8.3.5 Member Data Documentation

8.3.5.1 gobject_

```
GConfEntry* Gnome::Conf::Entry::gobject_ [protected]
```

The documentation for this class was generated from the following file:

- gconfmm/entry.h

8.4 Gnome::Conf::Error Class Reference

Exception class for [Gnome::Conf::Client](#) errors.

```
#include <gconfmm/client.h>
```

Inheritance diagram for Gnome::Conf::Error:

Collaboration diagram for Gnome::Conf::Error:

Public Types

- enum [Code](#) {
 [SUCCESS](#) = 0 ,
 [NO_SERVER](#) = 2 ,
 [NO_PERMISSION](#) = 3 ,
 [BAD_ADDRESS](#) = 4 ,
 [PARSE_ERROR](#) = 6 ,
 [CORRUPT](#) = 7 ,
 [TYPE_MISMATCH](#) = 8 ,
 [IS_DIR](#) = 9 ,
 [IS_KEY](#) = 10 ,
 [OVERRIDDEN](#) = 11 ,
 [OAF_ERROR](#) = 12 ,
 [LOCAL_ENGINE](#) = 13 ,
 [LOCK_FAILED](#) = 14 ,
 [NO_WRITABLE_DATABASE](#) = 15 ,
 [IN_SHUTDOWN](#) = 16 }

Public Member Functions

- [Error](#) ([Code](#) error_code, const Glib::ustring &error_message)
- [Error](#) (GError *gobject)
- [Code](#) code () const

8.4.1 Detailed Description

Exception class for [Gnome::Conf::Client](#) errors.

8.4.2 Member Enumeration Documentation

8.4.2.1 Code

```
enum Gnome::Conf::Error::Code
```

Enumerator

SUCCESS	
NO_SERVER	
NO_PERMISSION	
BAD_ADDRESS	
PARSE_ERROR	
CORRUPT	
TYPE_MISMATCH	
IS_DIR	
IS_KEY	
OVERRIDDEN	
OAF_ERROR	
LOCAL_ENGINE	
LOCK_FAILED	
NO_WRITABLE_DATABASE	
IN_SHUTDOWN	

8.4.3 Constructor & Destructor Documentation

8.4.3.1 Error() [1/2]

```
Gnome::Conf::Error::Error (
    Code error_code,
    const Glib::ustring & error_message )
```

8.4.3.2 Error() [2/2]

```
Gnome::Conf::Error::Error (
    GError * gobject ) [explicit]
```

8.4.4 Member Function Documentation

8.4.4.1 code()

```
Code Gnome::Conf::Error::code ( ) const
```

The documentation for this class was generated from the following file:

- gconfmm/client.h

8.5 Gnome::Conf::Schema Class Reference

```
#include <gconfmm/schema.h>
```

Collaboration diagram for Gnome::Conf::Schema:

Public Member Functions

- [Schema](#) ()
- [Schema](#) (GConfSchema *castitem, bool make_a_copy=false)
- [Schema](#) (const [Schema](#) &src)
- [Schema](#) & [operator=](#) (const [Schema](#) &src)
- [~Schema](#) ()
- GConfSchema * [gobj](#) ()
- const GConfSchema * [gobj](#) () const
- GConfSchema * [gobj_copy](#) () const

Provides access to the underlying C instance. The caller is responsible for freeing it. Use when directly setting fields in structs.

- void [set_type](#) (ValueType type)
- void [set_list_type](#) (ValueType type)
- void [set_car_type](#) (ValueType type)
- void [set_cdr_type](#) (ValueType type)
- void [set_locale](#) (const **std::string** &locale)
- void [set_short_desc](#) (const Glib::ustring &desc)
- void [set_long_desc](#) (const Glib::ustring &desc)
- void [set_owner](#) (const Glib::ustring &owner)
- void [set_default_value](#) (const [Value](#) &value)
- [ValueType](#) [get_type](#) () const
- [ValueType](#) [get_list_type](#) () const
- [ValueType](#) [get_car_type](#) () const
- [ValueType](#) [get_cdr_type](#) () const
- **std::string** [get_locale](#) () const
- Glib::ustring [get_short_desc](#) () const
- Glib::ustring [get_long_desc](#) () const
- Glib::ustring [get_owner](#) () const
- [Value](#) [get_default_value](#) () const

Protected Attributes

- GConfSchema * [gobject_](#)

Related Functions

(Note that these are not member functions.)

- [Gnome::Conf::Schema wrap](#) (GConfSchema *object, bool take_copy=false)

A Glib::wrap() method for this object.

8.5.1 Constructor & Destructor Documentation

8.5.1.1 Schema() [1/3]

```
Gnome::Conf::Schema::Schema ( )
```

8.5.1.2 Schema() [2/3]

```
Gnome::Conf::Schema::Schema (
    GConfSchema * castitem,
    bool make_a_copy = false ) [explicit]
```

8.5.1.3 Schema() [3/3]

```
Gnome::Conf::Schema::Schema (
    const Schema & src )
```

8.5.1.4 ~Schema()

```
Gnome::Conf::Schema::~~Schema ( )
```

8.5.2 Member Function Documentation

8.5.2.1 get_car_type()

```
ValueType Gnome::Conf::Schema::get_car_type ( ) const
```

8.5.2.2 get_cdr_type()

```
ValueType Gnome::Conf::Schema::get_cdr_type ( ) const
```

8.5.2.3 get_default_value()

Value Gnome::Conf::Schema::get_default_value () const

8.5.2.4 get_list_type()

ValueType Gnome::Conf::Schema::get_list_type () const

8.5.2.5 get_locale()

std::string Gnome::Conf::Schema::get_locale () const

8.5.2.6 get_long_desc()

Glib::ustring Gnome::Conf::Schema::get_long_desc () const

8.5.2.7 get_owner()

Glib::ustring Gnome::Conf::Schema::get_owner () const

8.5.2.8 get_short_desc()

Glib::ustring Gnome::Conf::Schema::get_short_desc () const

8.5.2.9 get_type()

ValueType Gnome::Conf::Schema::get_type () const

8.5.2.10 gobj() [1/2]

GConfSchema * Gnome::Conf::Schema::gobj () [inline]

8.5.2.11 gobj() [2/2]

```
const GConfSchema * Gnome::Conf::Schema::gobj ( ) const [inline]
```

8.5.2.12 gobj_copy()

```
GConfSchema * Gnome::Conf::Schema::gobj_copy ( ) const
```

Provides access to the underlying C instance. The caller is responsible for freeing it. Use when directly setting fields in structs.

8.5.2.13 operator=()

```
Schema & Gnome::Conf::Schema::operator= (
    const Schema & src )
```

8.5.2.14 set_car_type()

```
void Gnome::Conf::Schema::set_car_type (
    ValueType type )
```

8.5.2.15 set_cdr_type()

```
void Gnome::Conf::Schema::set_cdr_type (
    ValueType type )
```

8.5.2.16 set_default_value()

```
void Gnome::Conf::Schema::set_default_value (
    const Value & value )
```

8.5.2.17 set_list_type()

```
void Gnome::Conf::Schema::set_list_type (
    ValueType type )
```

8.5.2.18 set_locale()

```
void Gnome::Conf::Schema::set_locale (
    const std::string & locale )
```

8.5.2.19 set_long_desc()

```
void Gnome::Conf::Schema::set_long_desc (
    const Glib::ustring & desc )
```

8.5.2.20 set_owner()

```
void Gnome::Conf::Schema::set_owner (
    const Glib::ustring & owner )
```

8.5.2.21 set_short_desc()

```
void Gnome::Conf::Schema::set_short_desc (
    const Glib::ustring & desc )
```

8.5.2.22 set_type()

```
void Gnome::Conf::Schema::set_type (
    ValueType type )
```

8.5.3 Friends And Related Function Documentation

8.5.3.1 wrap()

```
Gnome::Conf::Schema wrap (
    GConfSchema * object,
    bool take_copy = false ) [related]
```

A Glib::wrap() method for this object.

Parameters

<i>object</i>	The C instance.
<i>take_copy</i>	False if the result should take ownership of the C instance. True if it should take a new copy or ref.

Returns

A C++ instance that wraps this C instance.

8.5.4 Member Data Documentation

8.5.4.1 gobject_

```
GConfSchema* Gnome::Conf::Schema::gobject_ [protected]
```

The documentation for this class was generated from the following file:

- gconfmm/schema.h

8.6 Gnome::Conf::SetInterface Class Reference

Common Interface for key-value settable objects.

```
#include <gconfmm/setinterface.h>
```

Inheritance diagram for Gnome::Conf::SetInterface:

Public Member Functions

- virtual void [set](#) (const Glib::ustring &key, const [Value](#) &value)=0
- virtual void [set](#) (const Glib::ustring &key, bool **what**)=0
- virtual void [set](#) (const Glib::ustring &key, int **what**)=0
- virtual void [set](#) (const Glib::ustring &key, double **what**)=0
- virtual void [set](#) (const Glib::ustring &key, const Glib::ustring &**what**)=0
- virtual void [set](#) (const Glib::ustring &key, const [Schema](#) &**what**)=0
- void [set](#) (const Glib::ustring &key, const [ValuePair](#) &pair)
- void [set_int_list](#) (const Glib::ustring &key, const SListHandle_ValueInt &list)
- void [set_bool_list](#) (const Glib::ustring &key, const SListHandle_ValueBool &list)
- void [set_float_list](#) (const Glib::ustring &key, const SListHandle_ValueFloat &list)
- void [set_string_list](#) (const Glib::ustring &key, const SListHandle_ValueString &list)
- void [set_schema_list](#) (const Glib::ustring &key, const SListHandle_ValueSchema &list)

8.6.1 Detailed Description

Common Interface for key-value settable objects.

This class defines a common interface for GConfrm objects that implement the set() methods for configuration keys. It also provides the implementations for the set_*_list() family of methods.

The only classes that support this interface are [Client](#) and [ChangeSet](#).

The set_*_list() methods take as a parameter any STL-compatible container that has the appropriate value_type.

8.6.2 Member Function Documentation

8.6.2.1 set() [1/7]

```
virtual void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    bool what ) [pure virtual]
```

Implemented in [Gnome::Conf::ChangeSet](#), and [Gnome::Conf::Client](#).

8.6.2.2 set() [2/7]

```
virtual void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    const Glib::ustring & what ) [pure virtual]
```

Implemented in [Gnome::Conf::ChangeSet](#), and [Gnome::Conf::Client](#).

8.6.2.3 set() [3/7]

```
virtual void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    const Schema & what ) [pure virtual]
```

Implemented in [Gnome::Conf::ChangeSet](#), and [Gnome::Conf::Client](#).

8.6.2.4 set() [4/7]

```
virtual void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    const Value & value ) [pure virtual]
```

Implemented in [Gnome::Conf::ChangeSet](#), and [Gnome::Conf::Client](#).

8.6.2.5 set() [5/7]

```
void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    const ValuePair & pair )
```

8.6.2.6 set() [6/7]

```
virtual void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    double what ) [pure virtual]
```

Implemented in [Gnome::Conf::ChangeSet](#), and [Gnome::Conf::Client](#).

8.6.2.7 set() [7/7]

```
virtual void Gnome::Conf::SetInterface::set (
    const Glib::ustring & key,
    int what ) [pure virtual]
```

Implemented in [Gnome::Conf::ChangeSet](#), and [Gnome::Conf::Client](#).

8.6.2.8 set_bool_list()

```
void Gnome::Conf::SetInterface::set_bool_list (
    const Glib::ustring & key,
    const SListHandle_ValueBool & list )
```

8.6.2.9 set_float_list()

```
void Gnome::Conf::SetInterface::set_float_list (
    const Glib::ustring & key,
    const SListHandle_ValueFloat & list )
```

8.6.2.10 set_int_list()

```
void Gnome::Conf::SetInterface::set_int_list (
    const Glib::ustring & key,
    const SListHandle_ValueInt & list )
```

8.6.2.11 set_schema_list()

```
void Gnome::Conf::SetInterface::set_schema_list (
    const Glib::ustring & key,
    const SListHandle_ValueSchema & list )
```

8.6.2.12 set_string_list()

```
void Gnome::Conf::SetInterface::set_string_list (
    const Glib::ustring & key,
    const SListHandle_ValueString & list )
```

The documentation for this class was generated from the following file:

- gconfmm/setinterface.h

8.7 Gnome::Conf::Value Class Reference

Wrapper for primitive types.

```
#include <gconfmm/value.h>
```

Collaboration diagram for Gnome::Conf::Value:

Public Member Functions

- [Value](#) (GConfValue *castitem, bool make_a_copy=false)
- [Value](#) (const [Value](#) &src)
- [Value](#) & [operator=](#) (const [Value](#) &src)
- [~Value](#) ()
- GConfValue * [gobj](#) ()
- const GConfValue * [gobj](#) () const
- GConfValue * [gobj_copy](#) () const

Provides access to the underlying C instance. The caller is responsible for freeing it. Use when directly setting fields in structs.
- [Value](#) (ValueType type=VALUE_INVALID)

Create a [Value](#).
- void [set](#) (gint val)

Set the integer value of a [Value](#) whose type is VALUE_INT.
- void [set](#) (gdouble val)

Set the float value of a [Value](#) whose type is VALUE_FLOAT.
- void [set](#) (bool val)

Set the boolean value of a [Value](#) whose type is VALUE_BOOL.
- void [set](#) (const [Schema](#) &sc)

Set the [Schema](#) of a [Value](#) whose type is VALUE_SCHEMA.
- void [set_car](#) (const [Value](#) &car)

Set the car (in a pair, the first element) of a [Value](#) whose type is VALUE_PAIR.
- void [set_cdr](#) (const [Value](#) &cdr)

Set the cdr (in a pair, the second element) of a [Value](#) whose type is VALUE_PAIR.
- void [set](#) (const Glib::ustring &val)

Set the string of a [Value](#) whose type is VALUE_STRING.
- void [set_list_type](#) (ValueType type)

Sets the type of the elements of a [Value](#) with type VALUE_LIST.
- void [set_int_list](#) (const SListHandle_ValueInt &list)

Sets the [Value](#) to contain a list of integers.
- void [set_bool_list](#) (const SListHandle_ValueBool &list)

Sets the [Value](#) to contain a list of booleans.
- void [set_float_list](#) (const SListHandle_ValueFloat &list)

Sets the [Value](#) to contain a list of doubles.
- void [set_string_list](#) (const SListHandle_ValueString &list)

Sets the [Value](#) to contain a list of strings.
- void [set_schema_list](#) (const SListHandle_ValueSchema &list)

Sets the [Value](#) to contain a list of [Schema](#).
- ValueType [get_type](#) () const

Get the type of the [Value](#).
- ValueType [get_list_type](#) () const

Get the type of the list elements of the [Value](#).
- int [get_int](#) () const

Get the integer that the [Value](#) contains.
- bool [get_bool](#) () const

Get the boolean that the [Value](#) contains.
- double [get_float](#) () const

Get the double that the [Value](#) contains.
- Glib::ustring [get_string](#) () const

Get the string that the [Value](#) contains.
- [Schema](#) [get_schema](#) () const

- Get a copy of the [Schema](#) of the value.

 - [Value get_car](#) () const

Get a copy of the car of a [VALUE_PAIR Value](#).
- [Value get_cdr](#) () const

Get a copy of the cdr of a [VALUE_PAIR Value](#).
- [SListHandle_ValueFloat get_float_list](#) () const

Gets a list of doubles from the [Value](#).
- [SListHandle_ValueInt get_int_list](#) () const

Retrieves the list of integers from the [Value](#).
- [SListHandle_ValueBool get_bool_list](#) () const

Retrieves the list of booleans from the [Value](#).
- [SListHandle_ValueString get_string_list](#) () const

Retrieves the list of strings from the [Value](#).
- [SListHandle_ValueSchema get_schema_list](#) () const

Retrieves the list of Schemas from the [Value](#).
- [Glib::ustring to_string](#) () const

Convert the [Value](#) to a string.

Protected Attributes

- [GConfValue * gobject_](#)

Related Functions

(Note that these are not member functions.)

- [Gnome::Conf::Value wrap](#) ([GConfValue *object](#), [bool take_copy=false](#))
- A [Glib::wrap\(\)](#) method for this object.

8.7.1 Detailed Description

Wrapper for primitive types.

This class wraps the primitive types that are passed to and from instances of [Gnome::Conf::Client](#). It has an associated `ValueType`, which is specified at creation time, but can be changed with assignment. If the type is `VALUE_INVALID` then the effect of the set and get methods is undefined. Using a default-constructed [Value](#) without using any of the set methods produces undefined behaviour.

Compound Values of type `VALUE_PAIR` and `VALUE_LIST` can only have elements whose types are neither `VALUE_PAIR` or `VALUE_LIST` - they can only have primitive types.

The [Value](#) class has copy-by-value semantics - all arguments to the set methods are copied.

Note that while the type is named `VALUE_FLOAT`, the accessors for floating-point values use `double`, not `float`, to preserve accuracy.

8.7.2 Constructor & Destructor Documentation

8.7.2.1 Value() [1/3]

```
Gnome::Conf::Value::Value (
    GConfValue * castitem,
    bool make_a_copy = false ) [explicit]
```

8.7.2.2 Value() [2/3]

```
Gnome::Conf::Value::Value (
    const Value & src )
```

8.7.2.3 ~Value()

```
Gnome::Conf::Value::~~Value ( )
```

8.7.2.4 Value() [3/3]

```
Gnome::Conf::Value::Value (
    ValueType type = VALUE_INVALID )
```

Create a [Value](#).

You should call a `set()` method before using the [Value](#).

Parameters

<i>type</i>	The type of the produced value.
-------------	---------------------------------

8.7.3 Member Function Documentation**8.7.3.1 get_bool()**

```
bool Gnome::Conf::Value::get_bool ( ) const
```

Get the boolean that the [Value](#) contains.

8.7.3.2 get_bool_list()

```
SListHandle_ValueBool Gnome::Conf::Value::get_bool_list ( ) const
```

Retrieves the list of booleans from the [Value](#).

See also

[get_float_list](#)

8.7.3.3 get_car()

```
Value Gnome::Conf::Value::get_car ( ) const
```

Get a copy of the car of a VALUE_PAIR [Value](#).

8.7.3.4 get_cdr()

```
Value Gnome::Conf::Value::get_cdr ( ) const
```

Get a copy of the cdr of a VALUE_PAIR [Value](#).

8.7.3.5 get_float()

```
double Gnome::Conf::Value::get_float ( ) const
```

Get the double that the [Value](#) contains.

8.7.3.6 get_float_list()

```
SListHandle_ValueFloat Gnome::Conf::Value::get_float_list ( ) const
```

Gets a list of doubles from the [Value](#).

Typical usage is

```
std::vector<double> foo = value.get_float_list();
```

.

Returns

: an STL-compatible container with doubles as its value type. Assign to an **std::vector**, list or deque for proper use.

8.7.3.7 get_int()

```
int Gnome::Conf::Value::get_int ( ) const
```

Get the integer that the [Value](#) contains.

8.7.3.8 get_int_list()

```
SListHandle_ValueInt Gnome::Conf::Value::get_int_list ( ) const
```

Retrieves the list of integers from the [Value](#).

See also

[get_float_list](#)

8.7.3.9 get_list_type()

```
ValueType Gnome::Conf::Value::get_list_type ( ) const
```

Get the type of the list elements of the [Value](#).

Do not call this method on non-list Values.

Returns

the type of the list elements.

8.7.3.10 get_schema()

```
Schema Gnome::Conf::Value::get_schema ( ) const
```

Get a copy of the [Schema](#) of the value.

8.7.3.11 get_schema_list()

```
SListHandle_ValueSchema Gnome::Conf::Value::get_schema_list ( ) const
```

Retrieves the list of Schemas from the [Value](#).

@See [get_float_list](#)

8.7.3.12 get_string()

```
Glib::ustring Gnome::Conf::Value::get_string ( ) const
```

Get the string that the [Value](#) contains.

8.7.3.13 get_string_list()

```
SListHandle_ValueString Gnome::Conf::Value::get_string_list ( ) const
```

Retrieves the list of strings from the [Value](#).

See also

[get_float_list](#)

8.7.3.14 get_type()

```
ValueType Gnome::Conf::Value::get_type ( ) const
```

Get the type of the [Value](#).

Returns

the type of the [Value](#)

8.7.3.15 gobj() [1/2]

```
GConfValue * Gnome::Conf::Value::gobj ( ) [inline]
```

8.7.3.16 gobj() [2/2]

```
const GConfValue * Gnome::Conf::Value::gobj ( ) const [inline]
```

8.7.3.17 gobj_copy()

```
GConfValue * Gnome::Conf::Value::gobj_copy ( ) const
```

Provides access to the underlying C instance. The caller is responsible for freeing it. Use when directly setting fields in structs.

8.7.3.18 operator=()

```
Value & Gnome::Conf::Value::operator= (
    const Value & src )
```

8.7.3.19 set() [1/5]

```
void Gnome::Conf::Value::set (
    bool val )
```

Set the boolean value of a [Value](#) whose type is VALUE_BOOL.

8.7.3.20 set() [2/5]

```
void Gnome::Conf::Value::set (
    const Glib::ustring & val )
```

Set the string of a [Value](#) whose type is VALUE_STRING.

8.7.3.21 set() [3/5]

```
void Gnome::Conf::Value::set (
    const Schema & sc )
```

Set the [Schema](#) of a [Value](#) whose type is VALUE_SCHEMA.

8.7.3.22 set() [4/5]

```
void Gnome::Conf::Value::set (
    gdouble val )
```

Set the float value of a [Value](#) whose type is VALUE_FLOAT.

Parameters

<code>val</code>	the double this Value will be se to.
------------------	--

8.7.3.23 set() [5/5]

```
void Gnome::Conf::Value::set (
    gint val )
```

Set the integer value of a [Value](#) whose type is VALUE_INT.

8.7.3.24 set_bool_list()

```
void Gnome::Conf::Value::set_bool_list (
    const SListHandle_ValueBool & list )
```

Sets the [Value](#) to contain a list of bools.

See also

[set_int_list](#)

8.7.3.25 set_car()

```
void Gnome::Conf::Value::set_car (
    const Value & car )
```

Set the car (in a pair, the first element) of a [Value](#) whose type is VALUE_PAIR.

8.7.3.26 set_cdr()

```
void Gnome::Conf::Value::set_cdr (
    const Value & cdr )
```

Set the cdr (in a pair, the second element) of a [Value](#) whose type is VALUE_PAIR.

8.7.3.27 set_float_list()

```
void Gnome::Conf::Value::set_float_list (
    const SListHandle_ValueFloat & list )
```

Sets the [Value](#) to contain a list of doubles.

See also

[set_int_list](#)

8.7.3.28 set_int_list()

```
void Gnome::Conf::Value::set_int_list (
    const SListHandle_ValueInt & list )
```

Sets the [Value](#) to contain a list of integers.

`set_list_type(VALUE_INT)` must have been called prior this call.

Parameters

<i>list</i>	an STL-compatible container whose <code>value_type</code> is <code>int</code>
-------------	---

8.7.3.29 set_list_type()

```
void Gnome::Conf::Value::set_list_type (
    ValueType type )
```

Sets the type of the elements of a [Value](#) with type `VALUE_LIST`.

8.7.3.30 set_schema_list()

```
void Gnome::Conf::Value::set_schema_list (
    const SListHandle_ValueSchema & list )
```

Sets the [Value](#) to contain a list of [Schema](#).

See also

[set_int_list](#)

8.7.3.31 set_string_list()

```
void Gnome::Conf::Value::set_string_list (
    const SListHandle_ValueString & list )
```

Sets the [Value](#) to contain a list of strings.

See also

[set_int_list](#)

8.7.3.32 to_string()

```
Glib::ustring Gnome::Conf::Value::to_string ( ) const
```

Convert the [Value](#) to a string.

The string is not machine-parseable. Do not depend on the format of the string.

8.7.4 Friends And Related Function Documentation

8.7.4.1 wrap()

```
Gnome::Conf::Value wrap (
    GConfValue * object,
    bool take_copy = false ) [related]
```

A Glib::wrap() method for this object.

Parameters

<i>object</i>	The C instance.
<i>take_copy</i>	False if the result should take ownership of the C instance. True if it should take a new copy or ref.

Returns

A C++ instance that wraps this C instance.

8.7.5 Member Data Documentation

8.7.5.1 gobject_

GConfValue* Gnome::Conf::Value::gobject_ [protected]

The documentation for this class was generated from the following file:

- gconfmm/value.h

Index

- ~Client
 - Gnome::Conf::Client, [19](#)
- ~Entry
 - Gnome::Conf::Entry, [39](#)
- ~Schema
 - Gnome::Conf::Schema, [46](#)
- ~Value
 - Gnome::Conf::Value, [56](#)
- add_dir
 - Gnome::Conf::Client, [19](#)
- all_dirs
 - Gnome::Conf::Client, [19](#)
- all_entries
 - Gnome::Conf::Client, [20](#)
- BAD_ADDRESS
 - Gnome::Conf::Error, [44](#)
- Callback
 - Gnome::Conf, [14](#)
- change_set_commit
 - Gnome::Conf::Client, [20](#)
- change_set_from_current
 - Gnome::Conf::Client, [21](#)
- change_set_reverse
 - Gnome::Conf::Client, [21](#)
- clear_cache
 - Gnome::Conf::Client, [22](#)
- CLIENT_HANDLE_ALL
 - gconfmm Enums and Flags, [12](#)
- CLIENT_HANDLE_NONE
 - gconfmm Enums and Flags, [12](#)
- CLIENT_HANDLE_UNRETURNED
 - gconfmm Enums and Flags, [12](#)
- CLIENT_PRELOAD_NONE
 - gconfmm Enums and Flags, [12](#)
- CLIENT_PRELOAD_ONELEVEL
 - gconfmm Enums and Flags, [12](#)
- CLIENT_PRELOAD_RECURSIVE
 - gconfmm Enums and Flags, [12](#)
- ClientErrorHandlingMode
 - gconfmm Enums and Flags, [11](#)
- ClientPreloadType
 - gconfmm Enums and Flags, [12](#)
- Code
 - Gnome::Conf::Error, [43](#)
- code
 - Gnome::Conf::Error, [44](#)
- CORRUPT
 - Gnome::Conf::Error, [44](#)
- dir_exists
 - Gnome::Conf::Client, [22](#)
- Entry
 - Gnome::Conf::Entry, [39](#)
- Error
 - Gnome::Conf::Error, [44](#)
- error
 - Gnome::Conf::Client, [22](#)
- gconfmm Enums and Flags, [11](#)
 - CLIENT_HANDLE_ALL, [12](#)
 - CLIENT_HANDLE_NONE, [12](#)
 - CLIENT_HANDLE_UNRETURNED, [12](#)
 - CLIENT_PRELOAD_NONE, [12](#)
 - CLIENT_PRELOAD_ONELEVEL, [12](#)
 - CLIENT_PRELOAD_RECURSIVE, [12](#)
 - ClientErrorHandlingMode, [11](#)
 - ClientPreloadType, [12](#)
 - UNSET_INCLUDING_SCHEMA_NAMES, [12](#)
 - UnsetFlags, [12](#)
 - VALUE_BOOL, [12](#)
 - VALUE_FLOAT, [12](#)
 - VALUE_INT, [12](#)
 - VALUE_INVALID, [12](#)
 - VALUE_LIST, [12](#)
 - VALUE_PAIR, [12](#)
 - VALUE_SCHEMA, [12](#)
 - VALUE_STRING, [12](#)
 - ValueType, [12](#)
- get
 - Gnome::Conf::Client, [23](#)
- get_bool
 - Gnome::Conf::Client, [23](#)
 - Gnome::Conf::Value, [56](#)
- get_bool_list
 - Gnome::Conf::Client, [23](#)
 - Gnome::Conf::Value, [56](#)
- get_car
 - Gnome::Conf::Value, [57](#)
- get_car_type
 - Gnome::Conf::Schema, [46](#)
- get_cdr
 - Gnome::Conf::Value, [57](#)
- get_cdr_type
 - Gnome::Conf::Schema, [46](#)
- get_client_for_engine
 - Gnome::Conf::Client, [23](#)

- get_default_client
 - Gnome::Conf::Client, 23
- get_default_from_schema
 - Gnome::Conf::Client, 24
- get_default_value
 - Gnome::Conf::Schema, 46
- get_entry
 - Gnome::Conf::Client, 24, 25
- get_float
 - Gnome::Conf::Client, 25
 - Gnome::Conf::Value, 57
- get_float_list
 - Gnome::Conf::Client, 26
 - Gnome::Conf::Value, 57
- get_int
 - Gnome::Conf::Client, 26
 - Gnome::Conf::Value, 57
- get_int_list
 - Gnome::Conf::Client, 26
 - Gnome::Conf::Value, 58
- get_is_default
 - Gnome::Conf::Entry, 40
- get_is_writable
 - Gnome::Conf::Entry, 40
- get_key
 - Gnome::Conf::Entry, 40
- get_list_type
 - Gnome::Conf::Schema, 47
 - Gnome::Conf::Value, 58
- get_locale
 - Gnome::Conf::Schema, 47
- get_long_desc
 - Gnome::Conf::Schema, 47
- get_owner
 - Gnome::Conf::Schema, 47
- get_pair
 - Gnome::Conf::Client, 27
- get_schema
 - Gnome::Conf::Client, 27
 - Gnome::Conf::Value, 58
- get_schema_list
 - Gnome::Conf::Client, 27
 - Gnome::Conf::Value, 58
- get_schema_name
 - Gnome::Conf::Entry, 40
- get_short_desc
 - Gnome::Conf::Schema, 47
- get_string
 - Gnome::Conf::Client, 27
 - Gnome::Conf::Value, 58
- get_string_list
 - Gnome::Conf::Client, 28
 - Gnome::Conf::Value, 59
- get_type
 - Gnome::Conf::Schema, 47
 - Gnome::Conf::Value, 59
- get_value
 - Gnome::Conf::Entry, 40
- get_without_default
 - Gnome::Conf::Client, 28
- Glib, 13
- Gnome, 13
- Gnome::Conf, 13
 - Callback, 14
 - init, 14
 - ValuePair, 14
 - ValueTypePair, 14
- Gnome::Conf::ChangeSet, 15
- Gnome::Conf::Client, 15
 - ~Client, 19
 - add_dir, 19
 - all_dirs, 19
 - all_entries, 20
 - change_set_commit, 20
 - change_set_from_current, 21
 - change_set_reverse, 21
 - clear_cache, 22
 - dir_exists, 22
 - error, 22
 - get, 23
 - get_bool, 23
 - get_bool_list, 23
 - get_client_for_engine, 23
 - get_default_client, 23
 - get_default_from_schema, 24
 - get_entry, 24, 25
 - get_float, 25
 - get_float_list, 26
 - get_int, 26
 - get_int_list, 26
 - get_pair, 27
 - get_schema, 27
 - get_schema_list, 27
 - get_string, 27
 - get_string_list, 28
 - get_without_default, 28
 - gobj, 28
 - gobj_copy, 29
 - key_is_writable, 29
 - notify, 29
 - notify_add, 29
 - notify_remove, 30
 - on_error, 30
 - on_unreturned_error, 30
 - on_value_changed, 31
 - preload, 31
 - recursive_unset, 31
 - remove_dir, 32
 - set, 32–34
 - set_bool_list, 35
 - set_error_handling, 35
 - set_float_list, 35
 - set_int_list, 35
 - set_schema_list, 35
 - set_string_list, 36
 - signal_error, 36

- signal_value_changed, 36
- SListHandleBools, 18
- SListHandleFloats, 18
- SListHandleInts, 18
- suggest_sync, 36
- unset, 37
- value_changed, 37
- wrap, 37
- Gnome::Conf::Entry, 38
 - ~Entry, 39
 - Entry, 39
 - get_is_default, 40
 - get_is_writable, 40
 - get_key, 40
 - get_schema_name, 40
 - get_value, 40
 - gobj, 40, 41
 - gobj_copy, 41
 - gobject_, 42
 - operator=, 41
 - set_is_default, 41
 - set_is_writable, 41
 - set_schema_name, 41
 - set_value, 42
 - wrap, 42
- Gnome::Conf::Error, 43
 - BAD_ADDRESS, 44
 - Code, 43
 - code, 44
 - CORRUPT, 44
 - Error, 44
 - IN_SHUTDOWN, 44
 - IS_DIR, 44
 - IS_KEY, 44
 - LOCAL_ENGINE, 44
 - LOCK_FAILED, 44
 - NO_PERMISSION, 44
 - NO_SERVER, 44
 - NO_WRITABLE_DATABASE, 44
 - OAF_ERROR, 44
 - OVERRIDDEN, 44
 - PARSE_ERROR, 44
 - SUCCESS, 44
 - TYPE_MISMATCH, 44
- Gnome::Conf::Schema, 45
 - ~Schema, 46
 - get_car_type, 46
 - get_cdr_type, 46
 - get_default_value, 46
 - get_list_type, 47
 - get_locale, 47
 - get_long_desc, 47
 - get_owner, 47
 - get_short_desc, 47
 - get_type, 47
 - gobj, 47
 - gobj_copy, 48
 - gobject_, 50
 - operator=, 48
 - Schema, 46
 - set_car_type, 48
 - set_cdr_type, 48
 - set_default_value, 48
 - set_list_type, 48
 - set_locale, 48
 - set_long_desc, 49
 - set_owner, 49
 - set_short_desc, 49
 - set_type, 49
 - wrap, 49
- Gnome::Conf::SetInterface, 50
 - set, 51, 52
 - set_bool_list, 52
 - set_float_list, 52
 - set_int_list, 53
 - set_schema_list, 53
 - set_string_list, 53
- Gnome::Conf::Value, 53
 - ~Value, 56
 - get_bool, 56
 - get_bool_list, 56
 - get_car, 57
 - get_cdr, 57
 - get_float, 57
 - get_float_list, 57
 - get_int, 57
 - get_int_list, 58
 - get_list_type, 58
 - get_schema, 58
 - get_schema_list, 58
 - get_string, 58
 - get_string_list, 59
 - get_type, 59
 - gobj, 59
 - gobj_copy, 59
 - gobject_, 63
 - operator=, 60
 - set, 60, 61
 - set_bool_list, 61
 - set_car, 61
 - set_cdr, 61
 - set_float_list, 61
 - set_int_list, 62
 - set_list_type, 62
 - set_schema_list, 62
 - set_string_list, 62
 - to_string, 63
 - Value, 55, 56
 - wrap, 63
- gobj
 - Gnome::Conf::Client, 28
 - Gnome::Conf::Entry, 40, 41
 - Gnome::Conf::Schema, 47
 - Gnome::Conf::Value, 59
- gobj_copy
 - Gnome::Conf::Client, 29

- Gnome::Conf::Entry, 41
- Gnome::Conf::Schema, 48
- Gnome::Conf::Value, 59
- gobject_
 - Gnome::Conf::Entry, 42
 - Gnome::Conf::Schema, 50
 - Gnome::Conf::Value, 63
- IN_SHUTDOWN
 - Gnome::Conf::Error, 44
- init
 - Gnome::Conf, 14
- IS_DIR
 - Gnome::Conf::Error, 44
- IS_KEY
 - Gnome::Conf::Error, 44
- key_is_writable
 - Gnome::Conf::Client, 29
- LOCAL_ENGINE
 - Gnome::Conf::Error, 44
- LOCK_FAILED
 - Gnome::Conf::Error, 44
- NO_PERMISSION
 - Gnome::Conf::Error, 44
- NO_SERVER
 - Gnome::Conf::Error, 44
- NO_WRITABLE_DATABASE
 - Gnome::Conf::Error, 44
- notify
 - Gnome::Conf::Client, 29
- notify_add
 - Gnome::Conf::Client, 29
- notify_remove
 - Gnome::Conf::Client, 30
- OAF_ERROR
 - Gnome::Conf::Error, 44
- on_error
 - Gnome::Conf::Client, 30
- on_unreturned_error
 - Gnome::Conf::Client, 30
- on_value_changed
 - Gnome::Conf::Client, 31
- operator=
 - Gnome::Conf::Entry, 41
 - Gnome::Conf::Schema, 48
 - Gnome::Conf::Value, 60
- OVERRIDDEN
 - Gnome::Conf::Error, 44
- PARSE_ERROR
 - Gnome::Conf::Error, 44
- preload
 - Gnome::Conf::Client, 31
- recursive_unset
 - Gnome::Conf::Client, 31
- remove_dir
 - Gnome::Conf::Client, 32
- Schema
 - Gnome::Conf::Schema, 46
- set
 - Gnome::Conf::Client, 32–34
 - Gnome::Conf::SetInterface, 51, 52
 - Gnome::Conf::Value, 60, 61
- set_bool_list
 - Gnome::Conf::Client, 35
 - Gnome::Conf::SetInterface, 52
 - Gnome::Conf::Value, 61
- set_car
 - Gnome::Conf::Value, 61
- set_car_type
 - Gnome::Conf::Schema, 48
- set_cdr
 - Gnome::Conf::Value, 61
- set_cdr_type
 - Gnome::Conf::Schema, 48
- set_default_value
 - Gnome::Conf::Schema, 48
- set_error_handling
 - Gnome::Conf::Client, 35
- set_float_list
 - Gnome::Conf::Client, 35
 - Gnome::Conf::SetInterface, 52
 - Gnome::Conf::Value, 61
- set_int_list
 - Gnome::Conf::Client, 35
 - Gnome::Conf::SetInterface, 53
 - Gnome::Conf::Value, 62
- set_is_default
 - Gnome::Conf::Entry, 41
- set_is_writable
 - Gnome::Conf::Entry, 41
- set_list_type
 - Gnome::Conf::Schema, 48
 - Gnome::Conf::Value, 62
- set_locale
 - Gnome::Conf::Schema, 48
- set_long_desc
 - Gnome::Conf::Schema, 49
- set_owner
 - Gnome::Conf::Schema, 49
- set_schema_list
 - Gnome::Conf::Client, 35
 - Gnome::Conf::SetInterface, 53
 - Gnome::Conf::Value, 62
- set_schema_name
 - Gnome::Conf::Entry, 41
- set_short_desc
 - Gnome::Conf::Schema, 49
- set_string_list
 - Gnome::Conf::Client, 36
 - Gnome::Conf::SetInterface, 53
 - Gnome::Conf::Value, 62
- set_type

- Gnome::Conf::Schema, [49](#)
- set_value
 - Gnome::Conf::Entry, [42](#)
- signal_error
 - Gnome::Conf::Client, [36](#)
- signal_value_changed
 - Gnome::Conf::Client, [36](#)
- SListHandleBools
 - Gnome::Conf::Client, [18](#)
- SListHandleFloats
 - Gnome::Conf::Client, [18](#)
- SListHandleInts
 - Gnome::Conf::Client, [18](#)
- SUCCESS
 - Gnome::Conf::Error, [44](#)
- suggest_sync
 - Gnome::Conf::Client, [36](#)
- to_string
 - Gnome::Conf::Value, [63](#)
- TYPE_MISMATCH
 - Gnome::Conf::Error, [44](#)
- unset
 - Gnome::Conf::Client, [37](#)
- UNSET_INCLUDING_SCHEMA_NAMES
 - gconfmm Enums and Flags, [12](#)
- UnsetFlags
 - gconfmm Enums and Flags, [12](#)
- Value
 - Gnome::Conf::Value, [55](#), [56](#)
- VALUE_BOOL
 - gconfmm Enums and Flags, [12](#)
- value_changed
 - Gnome::Conf::Client, [37](#)
- VALUE_FLOAT
 - gconfmm Enums and Flags, [12](#)
- VALUE_INT
 - gconfmm Enums and Flags, [12](#)
- VALUE_INVALID
 - gconfmm Enums and Flags, [12](#)
- VALUE_LIST
 - gconfmm Enums and Flags, [12](#)
- VALUE_PAIR
 - gconfmm Enums and Flags, [12](#)
- VALUE_SCHEMA
 - gconfmm Enums and Flags, [12](#)
- VALUE_STRING
 - gconfmm Enums and Flags, [12](#)
- ValuePair
 - Gnome::Conf, [14](#)
- ValueType
 - gconfmm Enums and Flags, [12](#)
- ValueTypePair
 - Gnome::Conf, [14](#)
- wrap
 - Gnome::Conf::Client, [37](#)