

VOMS CC API Reference Manual

1.5.0

Generated by Doxygen 1.3.9.1

Sat Oct 15 12:33:23 2011

Contents

1	VOMS CC API Data Structure Index	1
1.1	VOMS CC API Data Structures	1
2	VOMS CC API File Index	3
2.1	VOMS CC API File List	3
3	VOMS CC API Data Structure Documentation	5
3.1	attribute Struct Reference	5
3.2	attributelist Struct Reference	6
3.3	contactdata Struct Reference	7
3.4	data Struct Reference	9
3.5	voms Struct Reference	10
3.6	vomsdata Struct Reference	14
4	VOMS CC API File Documentation	23
4.1	voms_api.h File Reference	23

Chapter 1

VOMS CC API Data Structure Index

1.1 VOMS CC API Data Structures

Here are the data structures with brief descriptions:

attribute	5
attributelist	6
contactdata	7
data (User's characteristics: can be repeated)	9
voms	10
vomsdata	14

Chapter 2

VOMS CC API File Index

2.1 VOMS CC API File List

Here is a list of all files with brief descriptions:

voms_api.h	23
--------------------------------------	----

Chapter 3

VOMS CC API Data Structure Documentation

3.1 attribute Struct Reference

```
#include <voms_api.h>
```

Data Fields

- std::string [name](#)
- std::string [qualifier](#)
- std::string [value](#)

3.1.1 Field Documentation

3.1.1.1 std::string [attribute::name](#)

attribute's group

Definition at line 57 of file voms_api.h.

3.1.1.2 std::string [attribute::qualifier](#)

attribute's qualifier

Definition at line 58 of file voms_api.h.

3.1.1.3 std::string [attribute::value](#)

attribute's value

Definition at line 59 of file voms_api.h.

The documentation for this struct was generated from the following file:

- [voms_api.h](#)

3.2 attributelist Struct Reference

```
#include <voms_api.h>
```

Data Fields

- std::string [grantor](#)
- std::vector< [attribute](#) > [attributes](#)

3.2.1 Field Documentation

3.2.1.1 std::vector<[attribute](#)> [attributelist::attributes](#)

The attributes themselves.

Definition at line 64 of file voms_api.h.

3.2.1.2 std::string [attributelist::grantor](#)

Who granted these attributes.

Definition at line 63 of file voms_api.h.

The documentation for this struct was generated from the following file:

- [voms_api.h](#)

3.3 contactdata Struct Reference

```
#include <voms_api.h>
```

Data Fields

- std::string [nick](#)
- std::string [host](#)
- std::string [contact](#)
- std::string [vo](#)
- int [port](#)
- int [version](#)

3.3.1 Field Documentation

3.3.1.1 std::string [contactdata::contact](#)

The subject of the server's certificate
Definition at line 82 of file voms_api.h.

3.3.1.2 std::string [contactdata::host](#)

The hostname of the server
Definition at line 81 of file voms_api.h.

3.3.1.3 std::string [contactdata::nick](#)

The alias of the server
Definition at line 80 of file voms_api.h.

3.3.1.4 int [contactdata::port](#)

The port on which the server is listening
Definition at line 84 of file voms_api.h.

3.3.1.5 int [contactdata::version](#)

The version of globus under which the server is running
Definition at line 86 of file voms_api.h.

3.3.1.6 std::string [contactdata::vo](#)

The VO served by this server
Definition at line 83 of file voms_api.h.

The documentation for this struct was generated from the following file:

- [voms_api.h](#)

3.4 data Struct Reference

User's characteristics: can be repeated.

```
#include <voms_api.h>
```

Data Fields

- `std::string` [group](#)
- `std::string` [role](#)
- `std::string` [cap](#)

3.4.1 Detailed Description

User's characteristics: can be repeated.

Definition at line 48 of file `voms_api.h`.

3.4.2 Field Documentation

3.4.2.1 `std::string` [data::cap](#)

user's capability

Definition at line 51 of file `voms_api.h`.

3.4.2.2 `std::string` [data::group](#)

user's group

Definition at line 49 of file `voms_api.h`.

3.4.2.3 `std::string` [data::role](#)

user's role

Definition at line 50 of file `voms_api.h`.

The documentation for this struct was generated from the following file:

- [voms_api.h](#)

3.5 voms Struct Reference

```
#include <voms_api.h>
```

Public Member Functions

- [voms](#) (const [voms](#) &)
- [voms](#) ()
- [voms](#) & [operator=](#) (const [voms](#) &)
- [~voms](#) ()
- AC * [GetAC](#) ()
- std::vector< [attributelist](#) > & [GetAttributes](#) ()
- std::vector< std::string > [GetTargets](#) ()

Data Fields

- int [version](#)
- int [siglen](#)
- std::string [signature](#)
- std::string [user](#)
- std::string [userca](#)
- std::string [server](#)
- std::string [serverca](#)
- std::string [voname](#)
- std::string [uri](#)
- std::string [date1](#)
- std::string [date2](#)
- [data_type](#) type
- std::vector< [data](#) > [std](#)
- std::string [custom](#)
- std::vector< std::string > [fqan](#)
- std::string [serial](#)

Friends

- class [vomsdata](#)
- int [TranslateVOMS](#) (struct vomsdatar *vd, std::vector< [voms](#) > &v, int *error)

3.5.1 Constructor & Destructor Documentation

3.5.1.1 `voms::voms (const voms &)`

3.5.1.2 `voms::voms ()`

3.5.1.3 `voms::~~voms ()`

3.5.2 Member Function Documentation

3.5.2.1 `AC* voms::GetAC ()`

3.5.2.2 `std::vector<attributelist> & voms::GetAttributes ()`

Generic attributes

3.5.2.3 `std::vector<std::string> voms::GetTargets ()`

3.5.2.4 `voms& voms::operator= (const voms &)`

3.5.3 Friends And Related Function Documentation

3.5.3.1 `int TranslateVOMS (struct vomsdatar * vd, std::vector< voms > & v, int * error)`
[friend]

3.5.3.2 `friend class vomsdata [friend]`

Definition at line 92 of file voms_api.h.

3.5.4 Field Documentation

3.5.4.1 `std::string voms::custom`

The data returned by an S command

Definition at line 106 of file voms_api.h.

3.5.4.2 `std::string voms::date1`

Beginning of validity of the user info

Definition at line 102 of file voms_api.h.

3.5.4.3 `std::string voms::date2`

End of validity of the user info

Definition at line 103 of file voms_api.h.

3.5.4.4 `std::vector<std::string> voms::fqan`

Keeps the data in the compact format

Definition at line 108 of file voms_api.h.

3.5.4.5 `std::string voms::serial`

Serial number. "0" if coming from non-ac

Definition at line 109 of file voms_api.h.

3.5.4.6 `std::string voms::server`

The VOMS server DN, as from its certificate

Definition at line 98 of file voms_api.h.

3.5.4.7 `std::string voms::serverca`

The CA which signed the VOMS certificate

Definition at line 99 of file voms_api.h.

3.5.4.8 `int voms::siglen`

The length of the VOMS server signature

Definition at line 94 of file voms_api.h.

3.5.4.9 `std::string voms::signature`

The VOMS server signature

Definition at line 95 of file voms_api.h.

3.5.4.10 `std::vector<data> voms::std`

User's characteristics

Definition at line 105 of file voms_api.h.

3.5.4.11 `data_type voms::type`

The type of data returned

Definition at line 104 of file voms_api.h.

3.5.4.12 `std::string voms::uri`

The URI of the VOMS server

Definition at line 101 of file voms_api.h.

3.5.4.13 `std::string voms::user`

The user's DN, as from his certificate

Definition at line 96 of file voms_api.h.

3.5.4.14 `std::string voms::userca`

The CA which signed the user's certificate

Definition at line 97 of file voms_api.h.

3.5.4.15 `int voms::version`

0 means data didn't originate from an AC

Definition at line 93 of file voms_api.h.

3.5.4.16 `std::string voms::voname`

The name of the VO to which the VOMS belongs

Definition at line 100 of file voms_api.h.

The documentation for this struct was generated from the following file:

- [voms_api.h](#)

3.6 vomsdata Struct Reference

```
#include <voms_api.h>
```

Public Member Functions

- [vomsdata](#) (std::string voms_dir="", std::string cert_dir="")
- bool [LoadSystemContacts](#) (std::string dir="")
- bool [LoadUserContacts](#) (std::string dir="")
- std::vector< [contactdata](#) > [FindByAlias](#) (std::string alias)
- std::vector< [contactdata](#) > [FindByVO](#) (std::string vo)
- void [Order](#) (std::string att)
- void [ResetOrder](#) (void)
- void [AddTarget](#) (std::string target)
- std::vector< std::string > [ListTargets](#) (void)
- void [ResetTargets](#) (void)
- std::string [ServerErrors](#) (void)
- bool [Retrieve](#) (X509 *cert, STACK_OF(X509)*chain, [recurse_type](#) how=RECURSE_CHAIN)
- bool [Contact](#) (std::string hostname, int port, std::string servsubject, std::string command)
- bool [Contact](#) (std::string hostname, int port, std::string servsubject, std::string command, int timeout)
- bool [ContactRaw](#) (std::string hostname, int port, std::string servsubject, std::string command, std::string &raw, int &version)
- bool [ContactRaw](#) (std::string hostname, int port, std::string servsubject, std::string command, std::string &raw, int &version, int timeout)
- void [SetVerificationType](#) ([verify_type](#) how)
- void [SetLifetime](#) (int lifetime)
- bool [Import](#) (std::string buffer)
- bool [Export](#) (std::string &data)
- bool [DefaultData](#) ([voms](#) &)
- std::string [ErrorMessage](#) (void)
- bool [RetrieveFromCtx](#) ([gss_ctx_id_t](#) context, [recurse_type](#) how)
- bool [RetrieveFromCred](#) ([gss_cred_id_t](#) credential, [recurse_type](#) how)
- bool [Retrieve](#) (X509_EXTENSION *ext)
- bool [RetrieveFromProxy](#) ([recurse_type](#) how)
- bool [Retrieve](#) (FILE *file, [recurse_type](#) how)
- bool [Retrieve](#) (AC *ac)
- [~vomsdata](#) ()
- [vomsdata](#) (const [vomsdata](#) &)
- void [SetRetryCount](#) (int retryCount)
- void [SetVerificationTime](#) (time_t)
- bool [LoadCredentials](#) (X509 *, EVP_PKEY *, STACK_OF(X509)*)
- bool [ContactRESTRaw](#) (const std::string &, int, const std::string &, std::string &, int, int)

Data Fields

- [verror_type](#) error
- std::vector< [voms](#) > data
- std::string workvo
- std::string extra_data

3.6.1 Constructor & Destructor Documentation

3.6.1.1 vomsdata::vomsdata (std::string *voms_dir* = " ", std::string *cert_dir* = " ")

Parameters:

voms_dir The directory which contains the certificate of the VOMS server

cert_dir The directory which contains the certificate of the CA

If *voms_dir* is empty, the value of the environment variable X509_VOMS_DIR is taken.

If *cert_dir* is empty, the value of the environment variable X509_CERT_DIR is taken.

3.6.1.2 vomsdata::~~vomsdata ()

3.6.1.3 vomsdata::vomsdata (const vomsdata &)

3.6.2 Member Function Documentation

3.6.2.1 void vomsdata::AddTarget (std::string *target*)

Adds a target to the AC.

Parameters:

target The target to be added. it should be a FQDN.

3.6.2.2 bool vomsdata::Contact (std::string *hostname*, int *port*, std::string *servsubject*, std::string *command*, int *timeout*)

Contacts a VOMS server to get a certificate

It is the equivalent of the voms_proxy_init command, but without the --include functionality.

Parameters:

hostname FQDN of the VOMS server

port the port on which the VOMS server is listening

servsubject the subject of the server's certificate

command the command sent to the server

Returns:

failure (F) or success (T)

3.6.2.3 bool vomsdata::Contact (std::string *hostname*, int *port*, std::string *servsubject*, std::string *command*)

Contacts a VOMS server to get a certificate

It is the equivalent of the voms_proxy_init command, but without the --include functionality.

Parameters:

hostname FQDN of the VOMS server

port the port on which the VOMS server is listening
servsubject the subject of the server's certificate
command the command sent to the server

Returns:

failure (F) or success (T)

3.6.2.4 **bool vomsdata::ContactRaw (std::string *hostname*, int *port*, std::string *servsubject*, std::string *command*, std::string & *raw*, int & *version*, int *timeout*)**

Same as Contact, however it does not start the verification process, and the message received from the server is not parsed.

Parameters:

hostname FQDN of the VOMS server
port the port on which the VOMS server is listening
servsubject the subject of the server's certificate
command the command sent to the server
raw OUTPUT PARAMETER the answer from the server
version OUTPUT PARAMETER the version of the answer

Returns:

failure (F) or success (T)

3.6.2.5 **bool vomsdata::ContactRaw (std::string *hostname*, int *port*, std::string *servsubject*, std::string *command*, std::string & *raw*, int & *version*)**

Same as Contact, however it does not start the verification process, and the message received from the server is not parsed.

Parameters:

hostname FQDN of the VOMS server
port the port on which the VOMS server is listening
servsubject the subject of the server's certificate
command the command sent to the server
raw OUTPUT PARAMETER the answer from the server
version OUTPUT PARAMETER the version of the answer

Returns:

failure (F) or success (T)

3.6.2.6 **bool vomsdata::ContactRESTRaw (const std::string &, int, const std::string &, std::string &, int, int)**

3.6.2.7 **bool vomsdata::DefaultData (voms &)**

Get the default data extension from those present in the pseudo certificate

3.6.2.8 std::string vomsdata::ErrorMessage (void)

Gets a textual description of the error.

Returns:

A string containing the error message.

3.6.2.9 bool vomsdata::Export (std::string & data)

Exports data from [vomsdata::data](#) to the format used for inclusion into a certificate.

The function doesn't verify the data

Parameters:

data The certificate extension

Returns:

Failure (F) or Success (T)

3.6.2.10 std::vector<contactdata> vomsdata::FindByAlias (std::string alias)

Finds servers which share a common alias.

Parameters:

alias The alias to look for.

Returns:

The servers found. The order in which they are returned is unspecified.

3.6.2.11 std::vector<contactdata> vomsdata::FindByVO (std::string vo)

Finds servers which serve a common VO

Parameters:

vo The VO name to look for.

Returns:

The servers found. The order in which they are returned is unspecified.

3.6.2.12 bool vomsdata::Import (std::string buffer)

Converts data from the format used for inclusion into a certificate to the internal format

The function does verify the data.

Parameters:

buffer contains the data to be converted

Returns:

Failure (F) or Success (T)

3.6.2.13 `std::vector<std::string> vomsdata::ListTargets (void)`

Returns the list of targets.

3.6.2.14 `bool vomsdata::LoadCredentials (X509 *, EVP_PKEY *, STACK_OF(X509)*)`**3.6.2.15** `bool vomsdata::LoadSystemContacts (std::string dir = " ")`

Loads the system wide configuration files.

Parameters:

dir The directory in which the files are stored.

If *dir* is empty, defaults to /opt/edg/etc/vomses.

Returns:

True if all went OK, false otherwise.

3.6.2.16 `bool vomsdata::LoadUserContacts (std::string dir = " ")`

Loads the user-specific configuration files.

Parameters:

dir The directory in which the files are stored.

If *dir* is empty, defaults to \$VOMS_USERCONF. If this is empty too, defaults to \$HOME/.edg/vomses, or to ~/.edg/vomses as a last resort.

Returns:

True if all went OK, false otherwise.

3.6.2.17 `void vomsdata::Order (std::string att)`

Sets up the ordering of the results.

Defines the ordering of the data returned by [Contact\(\)](#). Results are ordered in the same order as the calls to this function.

Parameters:

att The attribute to be ordered.

3.6.2.18 `void vomsdata::ResetOrder (void)`

Resets the ordering.

3.6.2.19 `void vomsdata::ResetTargets (void)`

Resets the target list.

3.6.2.20 bool vomsdata::Retrieve (AC * *ac*)

Gets VOMS information from the AC

Parameters:

ext The extension to parse.

Returns:

failure (F) or success (T)

3.6.2.21 bool vomsdata::Retrieve (FILE * *file*, recurse_type *how*)

Gets VOMS information from a proxy saved as a file.

Parameters:

file the file name

how Recursion type

Returns:

failure (F) or success (T)

Note: Does NOT verify that the proxy is valid. Such verification must be obtained through other means.

3.6.2.22 bool vomsdata::Retrieve (X509_EXTENSION * *ext*)

Gets VOMS information from the given extension

Parameters:

ext The extension to parse.

Returns:

failure (F) or success (T)

3.6.2.23 bool vomsdata::Retrieve (X509 * *cert*, STACK_OF(X509)* *chain*, recurse_type *how* = RECURSE_CHAIN)

Extracts the VOMS extension from an X.509 certificate. The function doesn't check the validity of the certificates, but it does check the content of the user data.

Parameters:

cert The certificate with the VOMS extensions

chain The chain of the validation certificates (only the intermediate ones)

how Recursion type

Returns:

failure (F) or success (T)

3.6.2.24 bool vomsdata::RetrieveFromCred ([gss_cred_id_t](#) *credential*, [recurse_type](#) *how*)

Gets VOMS information from the given globus credential

Parameters:

credential The credential from which to retrieve the certificate.

how Recursion type

Returns:

failure (F) or success (T)

3.6.2.25 bool vomsdata::RetrieveFromCtx ([gss_ctx_id_t](#) *context*, [recurse_type](#) *how*)

Gets VOMS information from the given globus context

Parameters:

context The context from which to retrieve the certificate.

how Recursion type

Returns:

failure (F) or success (T)

3.6.2.26 bool vomsdata::RetrieveFromProxy ([recurse_type](#) *how*)

Gets VOMS information from an existing globus proxy

Parameters:

how Recursion type

Returns:

failure (F) or success (T)

3.6.2.27 std::string vomsdata::ServerErrors (void)

Gets the error message returned by the server

3.6.2.28 void vomsdata::SetLifetime (int *lifetime*)

Set requested lifetime for the [Contact\(\)](#) call.

Parameters:

lifetime Requested lifetime, in seconds

3.6.2.29 void vomsdata::SetRetryCount (int *retryCount*)

3.6.2.30 void vomsdata::SetVerificationTime (time_t)

3.6.2.31 void vomsdata::SetVerificationType ([verify_type](#) *how*)

Sets the type of verification done on the data.

Parameters:

how The type of verification.

3.6.3 Field Documentation

3.6.3.1 std::vector<[voms](#)> [vomsdata::data](#)

User's info, as in the certificate extension. It may contain data gathered from more than one VOMS server, Definition at line 361 of file voms_api.h.

3.6.3.2 [verror_type](#) [vomsdata::error](#)

Error code

Definition at line 206 of file voms_api.h.

3.6.3.3 std::string [vomsdata::extra_data](#)

The data specified by the user with the `--include` switch.

Note that this field doesn't contain the result of a request to the VOMS server, but instead data specified by the user.

The reason for the introduction of this extension is to let a user include important data into his proxy certificate, like, for example, a kerberos ticket

Definition at line 365 of file voms_api.h.

3.6.3.4 std::string [vomsdata::workvo](#)

The value of the `-vo` option of the `voms-proxy-init` command

Definition at line 364 of file voms_api.h.

The documentation for this struct was generated from the following file:

- [voms_api.h](#)

Chapter 4

VOMS CC API File Documentation

4.1 voms_api.h File Reference

```
#include <fstream>
#include <string>
#include <vector>
#include <openssl/x509.h>
#include <openssl/bio.h>
#include <sys/types.h>
#include "newformat.h"
```

Data Structures

- struct [data](#)
User's characteristics: can be repeated.
- struct [attribute](#)
- struct [attributelist](#)
- struct [contactdata](#)
- struct [voms](#)
- struct [vomsdata](#)
- class [vomsdata::Initializer](#)

Defines

- #define [NOGLOBUS](#)

Typedefs

- typedef void * [gss_cred_id_t](#)
- typedef void * [gss_ctx_id_t](#)
- typedef bool(* [check_sig](#))(X509 *, void *, [verror_type](#) &)

Enumerations

- enum `data_type` { `TYPE_NODATA`, `TYPE_STD`, `TYPE_CUSTOM` }
The type of data returned.
- enum `recurse_type` { `RECURSE_CHAIN`, `RECURSE_NONE`, `RECURSE_DEEP` }
- enum `verify_type` {
`VERIFY_FULL` = 0xffffffff, `VERIFY_NONE` = 0x00000000, `VERIFY_DATE` = 0x00000001,
`VERIFY_TARGET` = 0x00000002,
`VERIFY_KEY` = 0x00000004, `VERIFY_SIGN` = 0x00000008, `VERIFY_ORDER` = 0x00000010,
`VERIFY_ID` = 0x00000020,
`VERIFY_CERTLIST` = 0x00000040 }
- enum `verror_type` {
`VERR_NONE`, `VERR_NOCKET`, `VERR_NOIDENT`, `VERR_COMM`,
`VERR_PARAM`, `VERR_NOEXT`, `VERR_NOINIT`, `VERR_TIME`,
`VERR_IDCHECK`, `VERR_EXTRINFO`, `VERR_FORMAT`, `VERR_NODATA`,
`VERR_PARSE`, `VERR_DIR`, `VERR_SIGN`, `VERR_SERVER`,
`VERR_MEM`, `VERR_VERIFY`, `VERR_TYPE`, `VERR_ORDER`,
`VERR_SERVERCODE`, `VERR_NOTAVAIL`, `VERR_FILE` }
Error codes.

Functions

- int `getVOMSMajorVersionNumber` (void)
- int `getVOMSMinorVersionNumber` (void)
- int `getVOMSPatchVersionNumber` (void)

4.1.1 Define Documentation

4.1.1.1 #define NOGLOBUS

Definition at line 33 of file voms_api.h.

4.1.2 Typedef Documentation

4.1.2.1 typedef bool(* `check_sig`)(X509 *, void *, `verror_type` &)

Definition at line 183 of file voms_api.h.

4.1.2.2 typedef void* `gss_cred_id_t`

Definition at line 36 of file voms_api.h.

4.1.2.3 typedef void* `gss_ctx_id_t`

Definition at line 37 of file voms_api.h.

4.1.3 Enumeration Type Documentation

4.1.3.1 enum [data_type](#)

The type of data returned.

Enumeration values:

TYPE_NODATA no data
TYPE_STD group, role, capability triplet
TYPE_CUSTOM result of an S command

Definition at line 70 of file voms_api.h.

4.1.3.2 enum [recurse_type](#)

Enumeration values:

RECURSE_CHAIN
RECURSE_NONE
RECURSE_DEEP

Definition at line 136 of file voms_api.h.

4.1.3.3 enum [verify_type](#)

Enumeration values:

VERIFY_FULL
VERIFY_NONE
VERIFY_DATE
VERIFY_TARGET
VERIFY_KEY
VERIFY_SIGN
VERIFY_ORDER
VERIFY_ID
VERIFY_CERTLIST

Definition at line 142 of file voms_api.h.

4.1.3.4 enum [verror_type](#)

Error codes.

Enumeration values:

VERR_NONE
VERR_NOSOCKET Socket problem
VERR_NOIDENT Cannot identify itself (certificate problem)
VERR_COMM Server problem

VERR_PARAM Wrong parameters
VERR_NOEXT VOMS extension missing
VERR_NOINIT Initialization error
VERR_TIME Error in time checking
VERR_IDCHECK User data in extension different from the real ones
VERR_EXTRAINFO VO name and URI missing
VERR_FORMAT Wrong data format
VERR_NODATA Empty extension
VERR_PARSE Parse error
VERR_DIR Directory error
VERR_SIGN Signature error
VERR_SERVER Unidentifiable VOMS server
VERR_MEM Memory problems
VERR_VERIFY Generic verification error
VERR_TYPE Returned data of unknown type
VERR_ORDER Ordering different than required
VERR_SERVERCODE Error message from the server
VERR_NOTAVAIL Method not available
VERR_FILE Error reading data from file

Definition at line 156 of file voms_api.h.

4.1.4 Function Documentation

4.1.4.1 `int getVOMSMajorVersionNumber (void)`

4.1.4.2 `int getVOMSMinorVersionNumber (void)`

4.1.4.3 `int getVOMSPatchVersionNumber (void)`

Index

- ~voms
 - voms, [11](#)
- ~vomldata
 - vomldata, [15](#)
- AddTarget
 - vomldata, [15](#)
- attribute, [5](#)
 - name, [5](#)
 - qualifier, [5](#)
 - value, [5](#)
- attributelist, [6](#)
 - attributes, [6](#)
 - grantor, [6](#)
- attributes
 - attributelist, [6](#)
- cap
 - data, [9](#)
- check_sig
 - voms_api.h, [24](#)
- Contact
 - vomldata, [15](#)
- contact
 - contactdata, [7](#)
- contactdata, [7](#)
 - contact, [7](#)
 - host, [7](#)
 - nick, [7](#)
 - port, [7](#)
 - version, [7](#)
 - vo, [7](#)
- ContactRaw
 - vomldata, [16](#)
- ContactRESTRaw
 - vomldata, [16](#)
- custom
 - voms, [11](#)
- data, [9](#)
 - cap, [9](#)
 - group, [9](#)
 - role, [9](#)
 - vomldata, [21](#)
- data_type
 - voms_api.h, [25](#)
- date1
 - voms, [11](#)
- date2
 - voms, [11](#)
- DefaultData
 - vomldata, [16](#)
- error
 - vomldata, [21](#)
- ErrorMessage
 - vomldata, [16](#)
- Export
 - vomldata, [17](#)
- extra_data
 - vomldata, [21](#)
- FindByAlias
 - vomldata, [17](#)
- FindByVO
 - vomldata, [17](#)
- fqn
 - voms, [11](#)
- GetAC
 - voms, [11](#)
- GetAttributes
 - voms, [11](#)
- GetTargets
 - voms, [11](#)
- getVOMSMajorVersionNumber
 - voms_api.h, [26](#)
- getVOMSMinorVersionNumber
 - voms_api.h, [26](#)
- getVOMSPatchVersionNumber
 - voms_api.h, [26](#)
- grantor
 - attributelist, [6](#)
- group
 - data, [9](#)
- gss_cred_id_t
 - voms_api.h, [24](#)
- gss_ctx_id_t
 - voms_api.h, [24](#)
- host

- contactdata, 7
- Import
 - vomsdata, 17
- ListTargets
 - vomsdata, 17
- LoadCredentials
 - vomsdata, 18
- LoadSystemContacts
 - vomsdata, 18
- LoadUserContacts
 - vomsdata, 18
- name
 - attribute, 5
- nick
 - contactdata, 7
- NOGLOBUS
 - voms_api.h, 24
- operator=
 - voms, 11
- Order
 - vomsdata, 18
- port
 - contactdata, 7
- qualifier
 - attribute, 5
- RECURSE_CHAIN
 - voms_api.h, 25
- RECURSE_DEEP
 - voms_api.h, 25
- RECURSE_NONE
 - voms_api.h, 25
- recurse_type
 - voms_api.h, 25
- ResetOrder
 - vomsdata, 18
- ResetTargets
 - vomsdata, 18
- Retrieve
 - vomsdata, 18, 19
- RetrieveFromCred
 - vomsdata, 19
- RetrieveFromCtx
 - vomsdata, 20
- RetrieveFromProxy
 - vomsdata, 20
- role
 - data, 9
- serial
 - voms, 12
- server
 - voms, 12
- serverca
 - voms, 12
- ServerErrors
 - vomsdata, 20
- SetLifetime
 - vomsdata, 20
- SetRetryCount
 - vomsdata, 20
- SetVerificationTime
 - vomsdata, 21
- SetVerificationType
 - vomsdata, 21
- siglen
 - voms, 12
- signature
 - voms, 12
- std
 - voms, 12
- TranslateVOMS
 - voms, 11
- type
 - voms, 12
- TYPE_CUSTOM
 - voms_api.h, 25
- TYPE_NODATA
 - voms_api.h, 25
- TYPE_STD
 - voms_api.h, 25
- uri
 - voms, 12
- user
 - voms, 12
- userca
 - voms, 13
- value
 - attribute, 5
- VERIFY_CERTLIST
 - voms_api.h, 25
- VERIFY_DATE
 - voms_api.h, 25
- VERIFY_FULL
 - voms_api.h, 25
- VERIFY_ID
 - voms_api.h, 25
- VERIFY_KEY
 - voms_api.h, 25
- VERIFY_NONE

- voms_api.h, [25](#)
- VERIFY_ORDER
 - voms_api.h, [25](#)
- VERIFY_SIGN
 - voms_api.h, [25](#)
- VERIFY_TARGET
 - voms_api.h, [25](#)
- verify_type
 - voms_api.h, [25](#)
- VERR_COMM
 - voms_api.h, [25](#)
- VERR_DIR
 - voms_api.h, [26](#)
- VERR_EXTRAINFO
 - voms_api.h, [26](#)
- VERR_FILE
 - voms_api.h, [26](#)
- VERR_FORMAT
 - voms_api.h, [26](#)
- VERR_IDCHECK
 - voms_api.h, [26](#)
- VERR_MEM
 - voms_api.h, [26](#)
- VERR_NODATA
 - voms_api.h, [26](#)
- VERR_NOEXT
 - voms_api.h, [26](#)
- VERR_NOIDENT
 - voms_api.h, [25](#)
- VERR_NOINIT
 - voms_api.h, [26](#)
- VERR_NONE
 - voms_api.h, [25](#)
- VERR_NOSOCKET
 - voms_api.h, [25](#)
- VERR_NOTAVAIL
 - voms_api.h, [26](#)
- VERR_ORDER
 - voms_api.h, [26](#)
- VERR_PARAM
 - voms_api.h, [25](#)
- VERR_PARSE
 - voms_api.h, [26](#)
- VERR_SERVER
 - voms_api.h, [26](#)
- VERR_SERVERCODE
 - voms_api.h, [26](#)
- VERR_SIGN
 - voms_api.h, [26](#)
- VERR_TIME
 - voms_api.h, [26](#)
- VERR_TYPE
 - voms_api.h, [26](#)
- VERR_VERIFY
 - voms_api.h, [26](#)
- verror_type
 - voms_api.h, [25](#)
- version
 - contactdata, [7](#)
 - voms, [13](#)
- vo
 - contactdata, [7](#)
- voms, [10](#)
 - ~voms, [11](#)
 - custom, [11](#)
 - date1, [11](#)
 - date2, [11](#)
 - fqan, [11](#)
 - GetAC, [11](#)
 - GetAttributes, [11](#)
 - GetTargets, [11](#)
 - operator=, [11](#)
 - serial, [12](#)
 - server, [12](#)
 - serverca, [12](#)
 - siglen, [12](#)
 - signature, [12](#)
 - std, [12](#)
 - TranslateVOMS, [11](#)
 - type, [12](#)
 - uri, [12](#)
 - user, [12](#)
 - userca, [13](#)
 - version, [13](#)
 - voms, [11](#)
 - vomsdata, [11](#)
 - voname, [13](#)
- voms_api.h
 - RECURSE_CHAIN, [25](#)
 - RECURSE_DEEP, [25](#)
 - RECURSE_NONE, [25](#)
 - TYPE_CUSTOM, [25](#)
 - TYPE_NODATA, [25](#)
 - TYPE_STD, [25](#)
 - VERIFY_CERTLIST, [25](#)
 - VERIFY_DATE, [25](#)
 - VERIFY_FULL, [25](#)
 - VERIFY_ID, [25](#)
 - VERIFY_KEY, [25](#)
 - VERIFY_NONE, [25](#)
 - VERIFY_ORDER, [25](#)
 - VERIFY_SIGN, [25](#)
 - VERIFY_TARGET, [25](#)
 - VERR_COMM, [25](#)
 - VERR_DIR, [26](#)
 - VERR_EXTRAINFO, [26](#)
 - VERR_FILE, [26](#)
 - VERR_FORMAT, [26](#)

- VERR_IDCHECK, 26
- VERR_MEM, 26
- VERR_NODATA, 26
- VERR_NOEXT, 26
- VERR_NOIDENT, 25
- VERR_NOINIT, 26
- VERR_NONE, 25
- VERR_NOSOCKET, 25
- VERR_NOTAVAIL, 26
- VERR_ORDER, 26
- VERR_PARAM, 25
- VERR_PARSE, 26
- VERR_SERVER, 26
- VERR_SERVERCODE, 26
- VERR_SIGN, 26
- VERR_TIME, 26
- VERR_TYPE, 26
- VERR_VERIFY, 26
- voms_api.h, 23
 - check_sig, 24
 - data_type, 25
 - getVOMSMajorVersionNumber, 26
 - getVOMSMinorVersionNumber, 26
 - getVOMSPatchVersionNumber, 26
 - gss_cred_id_t, 24
 - gss_ctx_id_t, 24
 - NOGLOBUS, 24
 - recurse_type, 25
 - verify_type, 25
 - verror_type, 25
- vomsdata, 14
 - ~vomsdata, 15
 - AddTarget, 15
 - Contact, 15
 - ContactRaw, 16
 - ContactRESTRaw, 16
 - data, 21
 - DefaultData, 16
 - error, 21
 - ErrorMessage, 16
 - Export, 17
 - extra_data, 21
 - FindByAlias, 17
 - FindByVO, 17
 - Import, 17
 - ListTargets, 17
 - LoadCredentials, 18
 - LoadSystemContacts, 18
 - LoadUserContacts, 18
 - Order, 18
 - ResetOrder, 18
 - ResetTargets, 18
 - Retrieve, 18, 19
 - RetrieveFromCred, 19
 - RetrieveFromCtx, 20
 - RetrieveFromProxy, 20
 - ServerErrors, 20
 - SetLifetime, 20
 - SetRetryCount, 20
 - SetVerificationTime, 21
 - SetVerificationType, 21
 - voms, 11
 - vomsdata, 15
 - workvo, 21
- voname
 - voms, 13
- workvo
 - vomsdata, 21