

MLAPRONIDL: OCaml interface for APRON library

Bertrand Jeannet

April 2, 2017

The files of the APRON Library distribution, including all the files in the MLAPRONIDL subpackage, but excluding the files in the ppl, product, examples, and test subdirectories, are distributed under LGPL License with an exception allowing the redistribution of statically linked executables. The files in the ppl, product, examples, and test subdirectories are distributed under GPL License. Please read the

COPYING files packaged in the distribution.

Copyright (C) Bertrand Jeannet and Antoine Mine 2005-2009 for the MLAPRONIDL subpackage.

Contents

| | |
|--|-----------|
| 1 Module Introduction | 9 |
| 1.1 Requirements and installation | 10 |
| 1.2 Requirements and installation | 10 |
| 1.3 Requirements and installation | 11 |
| 1.4 Requirements and installation | 12 |
| 1.5 Requirements and installation | 13 |
| 1.6 Hints on programming idioms | 14 |
| 1.7 Requirements and installation | 14 |
| 1.8 Hints on programming idioms | 15 |
| 1.9 Requirements and installation | 15 |
| 1.10 Hints on programming idioms | 16 |
| 1.11 Requirements and installation | 19 |
| 1.12 Hints on programming idioms | 20 |
| 1.13 Requirements and installation | 22 |
| 1.14 Hints on programming idioms | 23 |
| 1.15 Requirements and installation | 26 |
| 1.16 Hints on programming idioms | 27 |
| 1.17 Compiling and linking client programs against APRON | 30 |
| 1.18 Requirements and installation | 30 |
| 1.19 Hints on programming idioms | 31 |
| 1.20 Compiling and linking client programs against APRON | 34 |
| | |
| I Coefficients | 36 |
| | |
| 2 Module Scalar : APRON Scalar numbers. | 37 |
| | |
| 3 Module Interval : APRON Intervals on scalars | 39 |
| | |
| 4 Module Coeff : APRON Coefficients (either scalars or intervals) | 41 |
| | |
| II Managers and Abstract Domains | 43 |
| | |
| 5 Module Manager : APRON Managers | 44 |
| | |
| 6 Module Box : Intervals abstract domain | 47 |
| 6.1 Type conversions | 47 |
| 6.2 Compilation information | 48 |

| CONTENTS | CONTENTS |
|--|-----------|
| 7 Module Oct : Octagon abstract domain. | 50 |
| 7.1 Type conversions | 51 |
| 7.2 Compilation information | 52 |
| 8 Module Polka : Convex Polyhedra and Linear Equalities abstract domains | 53 |
| 8.1 Type conversions | 54 |
| 8.2 Compilation information | 55 |
| 9 Module Ppl : Convex Polyhedra and Linear Congruences abstract domains (PPL wrapper) | 57 |
| 9.1 Type conversions | 58 |
| 9.2 Compilation information | 59 |
| 10 Module PolkaGrid : Reduced product of NewPolka polyhedra and PPL grids | 61 |
| 10.1 Type conversions | 61 |
| 10.2 Compilation information | 62 |
| III Level 1 of the interface | 64 |
| 11 Module Var : APRON Variables | 65 |
| 12 Module Environment : APRON Environments binding dimensions to names | 66 |
| 13 Module Linexpr1 : APRON Expressions of level 1 | 68 |
| 14 Module Lincons1 : APRON Constraints and array of constraints of level 1 | 70 |
| 14.1 Type array | 72 |
| 15 Module Generator1 : APRON Generators and array of generators of level 1 | 73 |
| 15.1 Type earray | 74 |
| 16 Module Texpr1 : APRON Expressions of level 1 | 76 |
| 16.1 Constructors and Destructor | 77 |
| 16.2 Tests | 77 |
| 16.3 Operations | 77 |
| 16.4 Printing | 78 |
| 17 Module Tcons1 : APRON tree constraints and array of tree constraints of level 1 | 79 |
| 17.1 Type array | 80 |
| 18 Module Abstract1 : APRON Abstract values of level 1 | 81 |
| 18.1 General management | 81 |
| 18.2 Constructor, accessors, tests and property extraction | 82 |
| 18.3 Constructor, accessors, tests and property extraction | 82 |
| 18.4 Operations | 84 |
| 18.5 Additional operations | 87 |
| 19 Module Parser : APRON Parsing of expressions | 88 |
| 19.1 Introduction | 88 |
| 19.2 Introduction | 89 |
| 19.3 Interface | 90 |

| CONTENTS | CONTENTS |
|--|------------|
| IV Level 0 of the interface | 92 |
| 20 Module Dim : APRON Dimensions and related types | 93 |
| 21 Module Linexpr0 : APRON Linear expressions of level 0 | 95 |
| 22 Module Lincons0 : APRON Linear constraints of level 0 | 97 |
| 23 Module Generator0 : APRON Generators of level 0 | 98 |
| 24 Module Texpr0 | 99 |
| 24.1 Constructors and Destructor | 100 |
| 24.2 Tests | 100 |
| 24.3 Printing | 100 |
| 24.4 Internal usage for level 1 | 101 |
| 25 Module Tcons0 : APRON tree expressions constraints of level 0 | 102 |
| 26 Module Abstract0 : APRON Abstract value of level 0 | 103 |
| 26.1 General management | 103 |
| 26.2 Constructor, accessors, tests and property extraction | 104 |
| 26.3 Operations | 105 |
| 26.4 Additional operations | 108 |
| V MLGmpIDL modules | 110 |
| 27 Module Mpz : GMP multi-precision integers | 111 |
| 27.1 Pretty printing | 111 |
| 27.2 Initialization Functions | 111 |
| 27.3 Assignment Functions | 112 |
| 27.4 Assignment Functions | 112 |
| 27.5 Combined Initialization and Assignment Functions | 112 |
| 27.6 Conversion Functions | 112 |
| 27.7 User Conversions | 112 |
| 27.8 User Conversions | 112 |
| 27.9 Arithmetic Functions | 113 |
| 27.10 Arithmetic Functions | 113 |
| 27.11 Division Functions | 113 |
| 27.12 Division Functions | 113 |
| 27.13 Division Functions | 113 |
| 27.14 Exponentiation Functions | 115 |
| 27.15 Root Extraction Functions | 115 |
| 27.16 Number Theoretic Functions | 115 |
| 27.17 Comparison Functions | 116 |
| 27.18 Logical and Bit Manipulation Functions | 116 |
| 27.19 Input and Output Functions: not interfaced | 116 |
| 27.20 Input and Output Functions: not interfaced | 116 |
| 27.21 Random Number Functions: see <code>Gmp_random</code> [31] module | 116 |
| 27.22 Input and Output Functions: not interfaced | 116 |

| CONTENTS | CONTENTS |
|--|------------|
| 27.23 Random Number Functions: see <code>Gmp_random</code> [31] module | 116 |
| 27.24 Input and Output Functions: not interfaced | 116 |
| 27.25 Random Number Functions: see <code>Gmp_random</code> [31] module | 116 |
| 27.26 Integer Import and Export Functions | 116 |
| 27.27 Miscellaneous Functions | 117 |
| 28 Module Mpq : GMP multi-precision rationals | 118 |
| 28.1 Pretty printing | 118 |
| 28.2 Initialization and Assignment Functions | 118 |
| 28.3 Additional Initialization and Assignements functions | 119 |
| 28.4 Additional Initialization and Assignements functions | 119 |
| 28.5 Conversion Functions | 119 |
| 28.6 User Conversions | 119 |
| 28.7 User Conversions | 119 |
| 28.8 Arithmetic Functions | 119 |
| 28.9 Comparison Functions | 120 |
| 28.10 Applying Integer Functions to Rationals | 120 |
| 28.11 Input and Output Functions: not interfaced | 120 |
| 29 Module Mpfr : GMP multi-precision floating-point numbers | 121 |
| 29.1 Pretty printing | 121 |
| 29.2 Initialization Functions | 121 |
| 29.3 Assignment Functions | 122 |
| 29.4 Combined Initialization and Assignment Functions | 122 |
| 29.5 Conversion Functions | 122 |
| 29.6 User Conversions | 122 |
| 29.7 User Conversions | 122 |
| 29.8 Arithmetic Functions | 123 |
| 29.9 Comparison Functions | 123 |
| 29.10 Input and Output Functions: not interfaced | 124 |
| 29.11 Input and Output Functions: not interfaced | 124 |
| 29.12 Random Number Functions: see <code>Gmp_random</code> [31] module | 124 |
| 29.13 Input and Output Functions: not interfaced | 124 |
| 29.14 Random Number Functions: see <code>Gmp_random</code> [31] module | 124 |
| 29.15 Input and Output Functions: not interfaced | 124 |
| 29.16 Random Number Functions: see <code>Gmp_random</code> [31] module | 124 |
| 29.17 Miscellaneous Float Functions | 124 |
| 30 Module Mpfr : MPFR multi-precision floating-point numbers | 125 |
| 30.1 Pretty printing | 125 |
| 30.2 Rounding Modes | 126 |
| 30.3 Exceptions | 126 |
| 30.4 Initialization Functions | 126 |
| 30.5 Assignment Functions | 126 |
| 30.6 Combined Initialization and Assignment Functions | 127 |
| 30.7 Conversion Functions | 127 |
| 30.8 User Conversions | 127 |
| 30.9 User Conversions | 127 |

| CONTENTS | CONTENTS |
|--|------------|
| 30.10 Basic Arithmetic Functions | 128 |
| 30.11 Comparison Functions | 129 |
| 30.12 Special Functions | 129 |
| 30.13 Input and Output Functions: not interfaced | 130 |
| 30.14 Input and Output Functions: not interfaced | 130 |
| 30.15 Input and Output Functions: not interfaced | 130 |
| 30.16 Miscellaneous Float Functions | 130 |
| 31 Module Gmp_random : GMP random generation functions | 132 |
| 31.1 Random State Initialization | 132 |
| 31.2 Random State Seeding | 132 |
| 31.3 Random Number Functions | 132 |
| 31.4 Random Number Functions | 132 |
| 31.5 Random Number Functions | 132 |
| 32 Module Mpzf : GMP multi-precision integers, functional version | 134 |
| 32.1 Pretty-printing | 134 |
| 32.2 Constructors | 134 |
| 32.3 Conversions | 134 |
| 32.4 Arithmetic Functions | 135 |
| 32.5 Comparison Functions | 135 |
| 33 Module Mpqf : GMP multi-precision rationals, functional version | 136 |
| 33.1 Pretty-printing | 136 |
| 33.2 Constructors | 136 |
| 33.3 Conversions | 137 |
| 33.4 Arithmetic Functions | 137 |
| 33.5 Comparison Functions | 137 |
| 33.6 Extraction Functions | 137 |
| 34 Module Mpfrf : MPFR multi-precision floating-point version, functional version | 138 |
| 34.1 Pretty-printing | 138 |
| 34.2 Constructors | 138 |
| 34.3 Conversions | 139 |
| 34.4 Arithmetic Functions | 139 |
| 34.5 Comparison Functions | 139 |

Chapter 1

Module Introduction

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module Apron, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients:** scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- **Manager**[5]: managers
- **Box**[6]: interval domain
- **Oct**[7]: octagon domain
- **Polka**[8]: convex polyhedra and linear equalities domains
- **T1p**: Taylor1plus abstract domain
- **Pp1**[9]: PPL convex polyhedra and linear congruences domains
- **PolkaGrid**[10]: reduced product of convex polyhedra and PPL linear congruences

3. **Level 1 of the interface (user-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

4. **Level 0 of the interface (lower-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module Apron, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients:** scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- **Manager**[5]: managers
- **Box**[6]: interval domain
- **Oct**[7]: octagon domain
- **Polka**[8]: convex polyhedra and linear equalities domains
- **T1p**: Taylor1plus abstract domain
- **Pp1**[9]: PPL convex polyhedra and linear congruences domains

-
- **PolkaGrid**[10]: reduced product of convex polyhedra and PPL linear congruences
 - 3. **Level 1 of the interface (user-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)
 - 4. **Level 0 of the interface (lower-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.1 Requirements and installation

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module Apron, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients**: scalar numbers, intervals, ...
2. **Managers and Abstract Domains**
 - **Manager**[5]: managers
 - **Box**[6]: interval domain
 - **Oct**[7]: octagon domain
 - **Polka**[8]: convex polyhedra and linear equalities domains
 - **T1p**: Taylor1plus abstract domain
 - **Ppl**[9]: PPL convex polyhedra and linear congruences domains
 - **PolkaGrid**[10]: reduced product of convex polyhedra and PPL linear congruences
3. **Level 1 of the interface (user-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)
4. **Level 0 of the interface (lower-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.2 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module Apron, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients**: scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- **Manager**[5]: managers
- **Box**[6]: interval domain
- **Oct**[7]: octagon domain
- **Polka**[8]: convex polyhedra and linear equalities domains
- **T1p**: Taylor1plus abstract domain
- **Ppl**[9]: PPL convex polyhedra and linear congruences domains
- **PolkaGrid**[10]: reduced product of convex polyhedra and PPL linear congruences

3. **Level 1 of the interface (user-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

4. **Level 0 of the interface (lower-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.3 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.3.1 Installation

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module Apron, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients**: scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- **Manager**[5]: managers
- **Box**[6]: interval domain
- **Oct**[7]: octagon domain
- **Polka**[8]: convex polyhedra and linear equalities domains

-
- `T1p`: Taylor1plus abstract domain
 - `Ppl`[9]: PPL convex polyhedra and linear congruences domains
 - `PolkaGrid`[10]: reduced product of convex polyhedra and PPL linear congruences
3. **Level 1 of the interface (user-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)
 4. **Level 0 of the interface (lower-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.4 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.4.1 Installation

- **Library:**

Set the file `./Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cmi`, but also `.idl` files.

- **Documentation:**

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the `html` subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients**: scalar numbers, intervals, ...

2. Managers and Abstract Domains

- **Manager**[5]: managers
- **Box**[6]: interval domain
- **Oct**[7]: octagon domain
- **Polka**[8]: convex polyhedra and linear equalities domains
- **T1p**: Taylor1plus abstract domain
- **Pp1**[9]: PPL convex polyhedra and linear congruences domains
- **PolkaGrid**[10]: reduced product of convex polyhedra and PPL linear congruences

3. **Level 1 of the interface (user-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

4. **Level 0 of the interface (lower-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.5 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.5.1 Installation

- **Library**:

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cmi`, but also `.idl` files.

- **Documentation:**

The documentation is generated with ocamldoc.

'make mlapronidl.pdf'

'make html' (put the HTML files in the html subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

1.6 Hints on programming idioms

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients:** scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- `Manager`[5]: managers
- `Box`[6]: interval domain
- `Oct`[7]: octagon domain
- `Polka`[8]: convex polyhedra and linear equalities domains
- `T1p`: Taylor1plus abstract domain
- `Pp1`[9]: PPL convex polyhedra and linear congruences domains
- `PolkaGrid`[10]: reduced product of convex polyhedra and PPL linear congruences

3. **Level 1 of the interface (user-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

4. **Level 0 of the interface (lower-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.7 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.7.1 Installation

- **Library:**

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cml`, but also `.idl` files.

- **Documentation:**

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the html subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

1.8 Hints on programming idioms

1.8.1 Allocating managers

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients:** scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- `Manager`[5]: managers
- `Box`[6]: interval domain
- `Oct`[7]: octagon domain
- `Polka`[8]: convex polyhedra and linear equalities domains
- `T1p`: Taylor1plus abstract domain
- `Pp1`[9]: PPL convex polyhedra and linear congruences domains
- `PolkaGrid`[10]: reduced product of convex polyhedra and PPL linear congruences

3. **Level 1 of the interface (user-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

4. **Level 0 of the interface (lower-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.9 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)

-
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
 - MLGMPIDL to GMP and MPFR libraries
 - OCaml 3.09 or up
 - Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.9.1 Installation

- **Library:**

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cmi`, but also `.idl` files.

- **Documentation:**

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the `html` subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

1.10 Hints on programming idioms

1.10.1 Allocating managers

The user might have some difficulties to exploit the genericity of the interface at first glance (it was actually my case).

Assume your main analysis function looks like:

```
let analyze_and_display equations (man : 'a Apron.Manager.t) : unit =
  ...
```

where `equations` is the equation system, `man` the APRON manager, and '`a` the effective abstract domain/implementation to be used in the analysis.

1. You might want to write code like

```
let manager_alloc option = match option with
  | `Box -> Box.manager_alloc ()
  | `Oct -> Oct.manager_alloc ()
;;
let main option equations =
  let man = manager_alloc opt in
```

CHAPTER 1. Module Introduction

```
analyze_and_display man equations
;;
```

but this does not work because `manager_alloc` cannot be typed (the types of `(Box.manager_alloc ()) : Box.t Apron.Manager.t` and `(Oct.manager_alloc ()) : Oct.t Apron.Manager.t` cannot be unified).

2. Using continuations does not work either:

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (fun apron -> analyze_and_display equations equations apron)
;;
```

because the argument `continuation` is monomorphic inside the body of `manager_alloc_and_continue` (i.e, it is not generalized):

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
Error: This expression has type Oct.t Apron.Manager.t
      but an expression was expected of type Box.t Apron.Manager.t
```

You can read detailed explanations about this issue on OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ.html#arguments_poly]

I can suggest 3 solutions:

1. Following OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ/FAQ_EXPERT-eng.html#arguments_poly], you can modify attempt 2 above as follows:

```
let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ())
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option equations
;;
```

Now this can be type-checked:

```
val manager_alloc_and_continue : [< `Box | `Oct ] -> 'a -> unit = <fun>
```

This is not very elegant: the call to `analyze_and_display` is hard-coded in `manager_alloc_and_continue`, and one has to pass all its arguments (like `equations`) to `manager_alloc_and_continue`.

2. It is possible to not give up with continuations by encapsulating them into a record (resp. an immediate object), because record fields (resp. methods) may be polymorphic.

- Using records:

```
type continuation = {
  f : 'a. 'a Apron.Manager.t -> unit;
} ;;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation.f (Box.manager_alloc ())
```

```

| `Oct -> continuation.f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  {f = fun apron -> analyze_and_display equations apron}
;;

```

- Using immediate objects:

```

type continuation = < f : 'a . 'a Apron.Manager.t -> unit >;;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

Compared to records, using immediate objects requires to repeat polymorphic type annotations. On the other hand, one does not need to define a new type `continuation`:

```

let manager_alloc_and_continue option (continuation:< f : 'a . 'a Apron.Manager.t -
> unit >)
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

3. A last possibility is to use the type conversion functions provided in `Box`[6] and `Oct`[7] (as well as in the other domain modules). One can modify attempt 1 as follows:

```

let manager_alloc option = match option with
  | `Box -> Box.manager_of_box (Box.manager_alloc ())
  | `Oct -> Oct.manager_of_oct (Oct.manager_alloc ())
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
val manager_alloc : [< `Box | `Oct ] -> 'a Apron.Manager.t = <fun>

```

The purpose of functions `Box.manager_of_box`[6.1] and `Oct.manager_of_oct`[7.1] is to generalize the type of their arguments (this is implemented with the `Obj.magic` function... but this is safe).

This is the most simple and flexible way.

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients**: scalar numbers, intervals, ...

2. Managers and Abstract Domains

- Manager[5]: managers
 - Box[6]: interval domain
 - Oct[7]: octagon domain
 - Polka[8]: convex polyhedra and linear equalities domains
 - T1p: Taylor1plus abstract domain
 - Ppl[9]: PPL convex polyhedra and linear congruences domains
 - PolkaGrid[10]: reduced product of convex polyhedra and PPL linear congruences
3. **Level 1 of the interface (user-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)
 4. **Level 0 of the interface (lower-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.11 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.11.1 Installation

• Library:

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cmi`, but also `.idl` files.

• Documentation:

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the `html` subdirectory)

• Miscellaneous:

'make clean' and 'make distclean' have the usual behaviour.

1.12 Hints on programming idioms

1.12.1 Allocating managers

The user might have some difficulties to exploit the genericity of the interface at first glance (it was actually my case).

Assume your main analysis function looks like:

```
let analyze_and_display equations (man : 'a Apron.Manager.t) : unit =
  ...
```

where `equations` is the equation system, `man` the APRON manager, and '`a` the effective abstract domain/implementation to be used in the analysis.

1. You might want to write code like

```
let manager_alloc option = match option with
  | `Box -> Box.manager_alloc ()
  | `Oct -> Oct.manager_alloc ()
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
```

but this does not work because `manager_alloc` cannot be typed (the types of `(Box.manager_alloc ())` : `Box.t Apron.Manager.t` and `(Oct.manager_alloc ())` : `Oct.t Apron.Manager.t` cannot be unified).

2. Using continuations does not work either:

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
    (fun apron -> analyze_and_display equations equations apron)
;;
```

because the argument `continuation` is monomorphic inside the body of `manager_alloc_and_continue` (i.e, it is not generalized):

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
Error: This expression has type Oct.t Apron.Manager.t
      but an expression was expected of type Box.t Apron.Manager.t
```

You can read detailed explanations about this issue on OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ.html#arguments_poly]

I can suggest 3 solutions:

1. Following OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ/FAQ_EXPERT-eng.html#arguments_poly] you can modify attempt 2 above as follows:

```
let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ())
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ())
```

```
;;
let main option equations =
    manager_alloc_and_continue option equations
;;
```

Now this can be type-checked:

```
val manager_alloc_and_continue : [< `Box | `Oct ] -> 'a -> unit = <fun>
```

This is not very elegant: the call to `analyze_and_display` is hard-coded in `manager_alloc_and_continue`, and one has to pass all its arguments (like `equations`) to `manager_alloc_and_continue`.

2. It is possible to not give up with continuations by encapsulating them into a record (resp. an immediate object), because record fields (resp. methods) may be polymorphic.

- Using records:

```
type continuation = {
  f : 'a. 'a Apron.Manager.t -> unit;
};;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation.f (Box.manager_alloc ())
  | `Oct -> continuation.f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  {f = fun apron -> analyze_and_display equations apron}
;;
```

- Using immediate objects:

```
type continuation = < f : 'a. 'a Apron.Manager.t -> unit >;;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;
```

Compared to records, using immediate objects requires to repeat polymorphic type annotations. On the other hand, one does not need to define a new type `continuation`:

```
let manager_alloc_and_continue option (continuation:< f : 'a. 'a Apron.Manager.t -
> unit >)
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;
```

3. A last possibility is to use the type conversion functions provided in `Box`[6] and `Oct`[7] (as well as in the other domain modules). One can modify attempt 1 as follows:

```

let manager_alloc option = match option with
  | `Box -> Box.manager_of_box (Box.manager_alloc ())
  | `Oct -> Oct.manager_of_oct (Oct.manager_alloc ())
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
val manager_alloc : [< `Box | `Oct ] -> 'a Apron.Manager.t = <fun>

```

The purpose of functions `Box.manager_of_box`[6.1] and `Oct.manager_of_oct`[7.1] is to generalize the type of their arguments (this is implemented with the `Obj.magic` function... but this is safe). This is the most simple and flexible way.

1.12.2 Breaking (locally) genericity

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients**: scalar numbers, intervals, ...
2. **Managers and Abstract Domains**
 - `Manager`[5]: managers
 - `Box`[6]: interval domain
 - `Oct`[7]: octagon domain
 - `Polka`[8]: convex polyhedra and linear equalities domains
 - `T1p`: Taylor1plus abstract domain
 - `Pp1`[9]: PPL convex polyhedra and linear congruences domains
 - `PolkaGrid`[10]: reduced product of convex polyhedra and PPL linear congruences
3. **Level 1 of the interface (user-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)
4. **Level 0 of the interface (lower-level)**: manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.13 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.13.1 Installation

- **Library:**

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cml`, but also `.idl` files.

- **Documentation:**

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the `html` subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

1.14 Hints on programming idioms

1.14.1 Allocating managers

The user might have some difficulties to exploit the genericity of the interface at first glance (it was actually my case).

Assume your main analysis function looks like:

```
let analyze_and_display equations (man : 'a Apron.Manager.t) : unit =
  ...
```

where `equations` is the equation system, `man` the APRON manager, and '`a`' the effective abstract domain/implementation to be used in the analysis.

1. You might want to write code like

```
let manager_alloc option = match option with
  | `Box -> Box.manager_alloc ()
  | `Oct -> Oct.manager_alloc ()
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
```

but this does not work because `manager_alloc` cannot be typed (the types of `(Box.manager_alloc ())` : `Box.t Apron.Manager.t` and `(Oct.manager_alloc ())` : `Oct.t Apron.Manager.t` cannot be unified).

2. Using continuations does not work either:

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
```

```
(fun apron -> analyze_and_display equations equations apron)
;;
```

because the argument `continuation` is monomorphic inside the body of `manager_alloc_and_continue` (i.e, it is not generalized):

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
Error: This expression has type Oct.t Apron.Manager.t
      but an expression was expected of type Box.t Apron.Manager.t
```

You can read detailed explanations about this issue on OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ_EXPERT-eng.html#arguments_poly]

I can suggest 3 solutions:

1. Following OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ_EXPERT-eng.html#arguments_poly] you can modify attempt 2 above as follows:

```
let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ())
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option equations
;;
```

Now this can be type-checked:

```
val manager_alloc_and_continue : [< `Box | `Oct ] -> 'a -> unit = <fun>
```

This is not very elegant: the call to `analyze_and_display` is hard-coded in `manager_alloc_and_continue`, and one has to pass all its arguments (like `equations`) to `manager_alloc_and_continue`.

2. It is possible to not give up with continuations by encapsulating them into a record (resp. an immediate object), because record fields (resp. methods) may be polymorphic.

- Using records:

```
type continuation = {
  f : 'a. 'a Apron.Manager.t -> unit;
};;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation.f (Box.manager_alloc ())
  | `Oct -> continuation.f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  {f = fun apron -> analyze_and_display equations apron}
;;
```

- Using immediate objects:

```
type continuation = < f : 'a. 'a Apron.Manager.t -> unit >;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
```

```

manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

Compared to records, using immediate objects requires to repeat polymorphic type annotations. On the other hand, one does not need to define a new type continuation:

```

let manager_alloc_and_continue option (continuation:< f : 'a . 'a Apron.Manager.t -
> unit >)
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

3. A last possibility is to use the type conversion functions provided in `Box`[6] and `Oct`[7] (as well as in the other domain modules). One can modify attempt 1 as follows:

```

let manager_alloc option = match option with
  | `Box -> Box.manager_of_box (Box.manager_alloc ())
  | `Oct -> Oct.manager_of_oct (Oct.manager_alloc ())
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
val manager_alloc : [< `Box | `Oct ] -> 'a Apron.Manager.t = <fun>

```

The purpose of functions `Box.manager_of_box`[6.1] and `Oct.manager_of_oct`[7.1] is to generalize the type of their arguments (this is implemented with the `Obj.magic` function... but this is safe).

This is the most simple and flexible way.

1.14.2 Breaking (locally) genericity

Assume that you are inside the body of the same
`analyze_and_display: equations -> 'a Apron.Manager.t -> unit`
function and that you want at some point

- either to modify an option of the manager `man`, depending on the effective underlying domain (like `Polka.set_max_coeff_size[8]`);
- or similarly to perform a specific operation on an abstract value.

You can modify the solution 1 above so as to pass a `modify: 'a Apron.Manager.t -> unit` function to `analyze_and_display`:

```

let analyze_and_display equations
  (man : 'a Apron.Manager.t)
  (modify : 'a Apron.Manager.t -> unit)
=
...
;;

```

```

let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ()) box_modify
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ()) oct_modify
;;
let main option equations =
  manager_alloc_and_continue option equations
;;

```

The most flexible way however is to use the “dynamic cast” functions `Box.manager_to_box[6.1]`, `Box.Abstract0.to_box[6.1]`, `Oct.manager_to_oct[7.1]`, `Oct.Abstract0.to_oct[7.1]`. These functions raise a `Failure` exception in case of (dynamic) typing error, but this can be avoided by the test functions `Box.manager_is_box[6.1]` and `Oct.manager_is_oct[7.1]`

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients:** scalar numbers, intervals, ...

2. **Managers and Abstract Domains**

- `Manager[5]`: managers
- `Box[6]`: interval domain
- `Oct[7]`: octagon domain
- `Polka[8]`: convex polyhedra and linear equalities domains
- `T1p`: Taylor1plus abstract domain
- `Pp1[9]`: PPL convex polyhedra and linear congruences domains
- `PolkaGrid[10]`: reduced product of convex polyhedra and PPL linear congruences

3. **Level 1 of the interface (user-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

4. **Level 0 of the interface (lower-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.15 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.15.1 Installation

- **Library:**

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cmi`, but also `.idl` files.

- **Documentation:**

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the `html` subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

1.16 Hints on programming idioms

1.16.1 Allocating managers

The user might have some difficulties to exploit the genericity of the interface at first glance (it was actually my case).

Assume your main analysis function looks like:

```
let analyze_and_display equations (man : 'a Apron.Manager.t) : unit =
  ...
```

where `equations` is the equation system, `man` the APRON manager, and '`a`' the effective abstract domain/implementation to be used in the analysis.

1. You might want to write code like

```
let manager_alloc option = match option with
  | `Box -> Box.manager_alloc ()
  | `Oct -> Oct.manager_alloc ()
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
```

but this does not work because `manager_alloc` cannot be typed (the types of `(Box.manager_alloc ())` : `Box.t Apron.Manager.t` and `(Oct.manager_alloc ())` : `Oct.t Apron.Manager.t` cannot be unified).

2. Using continuations does not work either:

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
```

```
(fun apron -> analyze_and_display equations equations apron)
;;
```

because the argument `continuation` is monomorphic inside the body of `manager_alloc_and_continue` (i.e, it is not generalized):

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
Error: This expression has type Oct.t Apron.Manager.t
      but an expression was expected of type Box.t Apron.Manager.t
```

You can read detailed explanations about this issue on OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ_EXPERT-eng.html#arguments_poly]

I can suggest 3 solutions:

1. Following OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ_EXPERT-eng.html#arguments_poly] you can modify attempt 2 above as follows:

```
let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ())
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option equations
;;
```

Now this can be type-checked:

```
val manager_alloc_and_continue : [< `Box | `Oct ] -> 'a -> unit = <fun>
```

This is not very elegant: the call to `analyze_and_display` is hard-coded in `manager_alloc_and_continue`, and one has to pass all its arguments (like `equations`) to `manager_alloc_and_continue`.

2. It is possible to not give up with continuations by encapsulating them into a record (resp. an immediate object), because record fields (resp. methods) may be polymorphic.

- Using records:

```
type continuation = {
  f : 'a. 'a Apron.Manager.t -> unit;
};;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation.f (Box.manager_alloc ())
  | `Oct -> continuation.f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  {f = fun apron -> analyze_and_display equations apron}
;;
```

- Using immediate objects:

```
type continuation = < f : 'a. 'a Apron.Manager.t -> unit >;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
```

```

manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

Compared to records, using immediate objects requires to repeat polymorphic type annotations. On the other hand, one does not need to define a new type continuation:

```

let manager_alloc_and_continue option (continuation:< f : 'a . 'a Apron.Manager.t -
> unit >)
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

3. A last possibility is to use the type conversion functions provided in `Box`[6] and `Oct`[7] (as well as in the other domain modules). One can modify attempt 1 as follows:

```

let manager_alloc option = match option with
  | `Box -> Box.manager_of_box (Box.manager_alloc ())
  | `Oct -> Oct.manager_of_oct (Oct.manager_alloc ())
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
val manager_alloc : [< `Box | `Oct ] -> 'a Apron.Manager.t = <fun>

```

The purpose of functions `Box.manager_of_box`[6.1] and `Oct.manager_of_oct`[7.1] is to generalize the type of their arguments (this is implemented with the `Obj.magic` function... but this is safe).

This is the most simple and flexible way.

1.16.2 Breaking (locally) genericity

Assume that you are inside the body of the same
`analyze_and_display: equations -> 'a Apron.Manager.t -> unit`
function and that you want at some point

- either to modify an option of the manager `man`, depending on the effective underlying domain (like `Polka.set_max_coeff_size[8]`);
- or similarly to perform a specific operation on an abstract value.

You can modify the solution 1 above so as to pass a `modify: 'a Apron.Manager.t -> unit` function to `analyze_and_display`:

```

let analyze_and_display equations
  (man : 'a Apron.Manager.t)
  (modify : 'a Apron.Manager.t -> unit)
=
...
;;

```

```

let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ()) box_modify
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ()) oct_modify
;;
let main option equations =
  manager_alloc_and_continue option equations
;;

```

The most flexible way however is to use the “dynamic cast” functions `Box.manager_to_box[6.1]`, `Box.Abstract0.to_box[6.1]`, `Oct.manager_to_oct[7.1]`, `Oct.Abstract0.to_oct[7.1]`. These functions raise a `Failure` exception in case of (dynamic) typing error, but this can be avoided by the test functions `Box.manager_is_box[6.1]` and `Oct.manager_is_oct[7.1]`

1.17 Compiling and linking client programs against APRON

This package is an OCaml interface for the APRON library/interface. The interface is accessed via the module `Apron`, which is decomposed into 15 submodules, corresponding to C modules, and which can be organized in 4 groups

1. **Coefficients:** scalar numbers, intervals, ...
2. **Managers and Abstract Domains**
 - `Manager[5]`: managers
 - `Box[6]`: interval domain
 - `Oct[7]`: octagon domain
 - `Polka[8]`: convex polyhedra and linear equalities domains
 - `T1p`: Taylor1plus abstract domain
 - `Ppl[9]`: PPL convex polyhedra and linear congruences domains
 - `PolkaGrid[10]`: reduced product of convex polyhedra and PPL linear congruences
3. **Level 1 of the interface (user-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)
4. **Level 0 of the interface (lower-level):** manipulation of generic datatypes (expressions, constraints, ..., and generic abstract domain interface)

1.18 Requirements and installation

(See README of general APRON distribution for more details)

- APRON library
- GMP library version 4.2 or up (tested with version 4.2.1 and 4.3.1)
- MPFR library version 2.2 or up (tested with version 2.2.1 and 2.3.1)
- MLGMPIDL to GMP and MPFR libraries
- OCaml 3.09 or up
- Camlidl (tested with 1.05)

For compiling from repository (strongly recommended):

- GNU M4 preprocessor
- GNU sed

It is important to have the GNU versions !

1.18.1 Installation

- **Library:**

Set the file `../Makefile.config` to your own setting.

type 'make', and then 'make install'

The OCaml part of the library is named `apron.cma` (`.cmxa`, `.a`). The C part of the library, which is automatically referenced by `apron.cma/apron.cmxa`, is named `libapron_caml.a`, `libapron_caml.so`, `dllapron_caml.so` (which is a soft link to the previous library) (debug versions: `libapron_caml_debug.a`, `libapron_caml_debug.so`, `dllapron_caml_debug.so`)

'make install' installs not only `.mli`, `.cml`, but also `.idl` files.

- **Documentation:**

The documentation is generated with `ocamldoc`.

'make mlapronidl.pdf'

'make html' (put the HTML files in the `html` subdirectory)

- **Miscellaneous:**

'make clean' and 'make distclean' have the usual behaviour.

1.19 Hints on programming idioms

1.19.1 Allocating managers

The user might have some difficulties to exploit the genericity of the interface at first glance (it was actually my case).

Assume your main analysis function looks like:

```
let analyze_and_display equations (man : 'a Apron.Manager.t) : unit =
  ...
```

where `equations` is the equation system, `man` the APRON manager, and '`a`' the effective abstract domain/implementation to be used in the analysis.

1. You might want to write code like

```
let manager_alloc option = match option with
  | `Box -> Box.manager_alloc ()
  | `Oct -> Oct.manager_alloc ()
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
```

but this does not work because `manager_alloc` cannot be typed (the types of `(Box.manager_alloc ())` : `Box.t Apron.Manager.t` and `(Oct.manager_alloc ())` : `Oct.t Apron.Manager.t` cannot be unified).

2. Using continuations does not work either:

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
```

```
(fun apron -> analyze_and_display equations equations apron)
;;
```

because the argument `continuation` is monomorphic inside the body of `manager_alloc_and_continue` (i.e, it is not generalized):

```
let manager_alloc_and_continue option (continuation:'a Apron.Manager.t -> 'b) =
  match option with
  | `Box -> continuation (Box.manager_alloc ())
  | `Oct -> continuation (Oct.manager_alloc ())
;;
Error: This expression has type Oct.t Apron.Manager.t
      but an expression was expected of type Box.t Apron.Manager.t
```

You can read detailed explanations about this issue on OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ_EXPERT-eng.html#arguments_poly]

I can suggest 3 solutions:

1. Following OCaml FAQ [http://caml.inria.fr/pub/old_caml_site/FAQ_EXPERT-eng.html#arguments_poly] you can modify attempt 2 above as follows:

```
let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ())
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option equations
;;
```

Now this can be type-checked:

```
val manager_alloc_and_continue : [< `Box | `Oct ] -> 'a -> unit = <fun>
```

This is not very elegant: the call to `analyze_and_display` is hard-coded in `manager_alloc_and_continue`, and one has to pass all its arguments (like `equations`) to `manager_alloc_and_continue`.

2. It is possible to not give up with continuations by encapsulating them into a record (resp. an immediate object), because record fields (resp. methods) may be polymorphic.

- Using records:

```
type continuation = {
  f : 'a. 'a Apron.Manager.t -> unit;
};;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation.f (Box.manager_alloc ())
  | `Oct -> continuation.f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  {f = fun apron -> analyze_and_display equations apron}
;;
```

- Using immediate objects:

```
type continuation = < f : 'a. 'a Apron.Manager.t -> unit >;
let manager_alloc_and_continue option (continuation:continuation) =
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
```

```

manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

Compared to records, using immediate objects requires to repeat polymorphic type annotations. On the other hand, one does not need to define a new type continuation:

```

let manager_alloc_and_continue option (continuation:< f : 'a . 'a Apron.Manager.t -
> unit >)
  match option with
  | `Box -> continuation#f (Box.manager_alloc ())
  | `Oct -> continuation#f (Oct.manager_alloc ())
;;
let main option equations =
  manager_alloc_and_continue option
  (object method f: 'a . 'a Apron.Manager.t -> unit =
    fun apron -> analyze_and_display equations apron
  end)
;;

```

3. A last possibility is to use the type conversion functions provided in `Box`[6] and `Oct`[7] (as well as in the other domain modules). One can modify attempt 1 as follows:

```

let manager_alloc option = match option with
  | `Box -> Box.manager_of_box (Box.manager_alloc ())
  | `Oct -> Oct.manager_of_oct (Oct.manager_alloc ())
;;
let main option equations =
  let man = manager_alloc opt in
  analyze_and_display man equations
;;
val manager_alloc : [< `Box | `Oct ] -> 'a Apron.Manager.t = <fun>

```

The purpose of functions `Box.manager_of_box`[6.1] and `Oct.manager_of_oct`[7.1] is to generalize the type of their arguments (this is implemented with the `Obj.magic` function... but this is safe).

This is the most simple and flexible way.

1.19.2 Breaking (locally) genericity

Assume that you are inside the body of the same
`analyze_and_display: equations -> 'a Apron.Manager.t -> unit`
function and that you want at some point

- either to modify an option of the manager `man`, depending on the effective underlying domain (like `Polka.set_max_coeff_size[8]`);
- or similarly to perform a specific operation on an abstract value.

You can modify the solution 1 above so as to pass a `modify: 'a Apron.Manager.t -> unit` function to `analyze_and_display`:

```

let analyze_and_display equations
  (man : 'a Apron.Manager.t)
  (modify : 'a Apron.Manager.t -> unit)
  =
  ...
;;

```

```

let manager_alloc_and_continue option equations =
  match option with
  | `Box -> analyze_and_display equations (Box.manager_alloc ()) box_modify
  | `Oct -> analyze_and_display equations (Oct.manager_alloc ()) oct_modify
;;
let main option equations =
  manager_alloc_and_continue option equations
;;

```

The most flexible way however is to use the “dynamic cast” functions `Box.manager_to_box`[6.1], `Box.Abstract0.to_box`[6.1], `Oct.manager_to_oct`[7.1], `Oct.Abstract0.to_oct`[7.1]. These functions raise a `Failure` exception in case of (dynamic) typing error, but this can be avoided by the test functions `Box.manager_is_box`[6.1] and `Oct.manager_is_oct`[7.1]

1.20 Compiling and linking client programs against APRON

To make things clearer, we assume an example file `mlexample.ml` which uses both NewPolka (convex polyhedra) and Box (intervals) libraries, in their versions where rationals are GMP rationals (which is the default). We assume that C and OCaml interface and library files are located in directory `$APRON/lib`.

The native-code compilation command looks like

```
ocamlopt -I $APRON/lib -o mlexample.opt \
  bigarray.cmxa gmp.cmxa apron.cmxa boxMPFR.cmxa polkaMPQ.cmxa mlexample.ml
```

Comments:

1. You need at least the libraries `bigarray` (standard OCaml distribution), `gmp`, and `apron` (standard APRON distribution), plus the one implementing an effective abstract domains: here, `boxMPFR`, and `polkaMPQ`.
2. The C libraries associated to those OCaml libraries (e.g., `gmp_caml`, `boxMPFR_caml`, \ldots) are automatically looked for, as well as the the libraries implementing abstract domains (e.g., `polkaMPQ`, `boxMPFR`).
- If other versions of abstract domains library are wanted, you should use the `-noautolink` option as explained below.
3. If in `Makefile.config`, the `HAS_SHARED` variable is set to a non-empty value, dynamic versions of those libraires are also available, but makes sure that all the needed libraries are in the dynamic search path indicated by `$LD_LIBRARY_PATH`.

If dynamic libraries are available, the byte-code compilation process looks like

```
ocamlc -I $MLGMPIDL/lib -I $APRON/lib -o mlexample.byte \
  bigarray.cma gmp.cma apron.cma boxMPFR.cma polkaMPQ.cma mlexample.ml
```

Comments:

1. The `ocamlrun` bytecode interpreter will automatically load the dynamic libraries, using environment variables `$LD_LIBRARY_PATH` (and possibly `$CAML_LD_LIBRARY_PATH`, see OCaml documentation, section on OCaml/C interface).
2. You can very easily use the interactive toplevel interpreter: type '`ocaml -I $MLGMPIDL/lib -I $APRON/lib`' and then enter:

```

#load "bigarray.cma";;
#load "gmp.cma";;
#load "apron.cma";;
#load "polkaMPQ.cma";;
...

```

3. This is also the only way to load and use in the OCaml debugger pretty-printers depending on C code, like

```
#load "bigarray.cma";;
#load "gmp.cma";;
#load "apron.cma";;

#install_printer Apron.Abstract1.print;;
```

If only static libraries are available, you can:

1. Create a custom runtime and use it as follows:

```
ocamlc -I $MLGMPIDL/lib -I $APRON/lib -make-runtime -o myrun \
bigarray.cma gmp.cma apron.cma boxMPFR.cma polkaMPQ.cma

ocamlc -I $MLGMPIDL/lib -I $APRON/lib -use-runtime myrun -o \mlexample.byte \
bigarray.cma gmp.cma apron.cma box.cma polka.cma mlexample.ml
```

Comments:

- (a) One first build a custom bytecode interpreter that includes the new native-code needed;
 - (b) One then compile the `mlexample.ml` file, using the generated bytecode interpreter.
2. If you want to use the interactive toplevel interpreter, you have to generate a custom toplevel interpreter using the `ocamlmktop` command (see OCaml documentation, section on OCaml/C interface):

```
ocamlmktop -I $MLGMPIDL/lib -I $APRON/lib -o mytop \
bigarray.cma gmp.cma apron.cma boxMPFR.cma polkaMPQ.cma
```

The automatic search for C libraries associated to these OCaml libraries can be disabled by the option `-noautolink` supported by both `ocamlc` and `ocamlopt` commands. For instance, the command for native-code compilation can alternatively looks like:

```
ocamlopt -I $MLGMPIDL/lib -I $APRON/lib -noautolink -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa boxMPFR.cmxa polkaMPQ.cmxa mlexample.ml \
-cclib "-L$MLGMPIDL/lib -L$APRON/lib \
-lpolkaMPQ_caml_debug -lpolkaMPQ_debug \
-lboxMPFR_caml_debug -lboxMPFR_debug \
-lapron_caml_debug -lapron_debug \
-lgmp_caml -L$MPFR -lmpfr -L$GMP/lib -lgmp \
-L$CAMILIDL/lib/ocaml -lcamlidl \
-lbigarray"
```

or more simply, if dynamic libraries are available (because some dynamic libraries are automatically referenced by others):

```
ocamlopt -I $MLGMPIDL/lib -I $APRON/lib -noautolink -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa boxMPFR.cmxa polkaMPQ.cmxa mlexample.ml \
-cclib "-L$MLGMPIDL/lib -L$APRON/lib \
-lpolkaMPQ_caml_debug \
-lboxMPFR_caml_debug \
-lapron_caml_debug \
-lgmp_caml \
-lbigarray"
```

This is mandatory if you want to use non-default versions of libraries (here, debug versions).

The option `-verbose` helps to understand what is happening in case of problem.

More details are given in the modules implementing a specific abstract domain.

Part I

Coefficients

Chapter 2

Module Scalar : APRON Scalar numbers.

```
type t =
| Float of float
| Mpqf of Mpqf.t
| Mpfrf of Mpfrf.t
```

APRON Scalar numbers.

APRON Scalar numbers.

See `Mpqf`[33] for operations on GMP multiprecision rational numbers and `Mpfr`[30] for operations on MPFR multi-precision floating-point numbers.

```
val of_mpq : Mpq.t -> t
val of_mpqf : Mpqf.t -> t
val of_int : int -> t
val of_frac : int -> int -> t
```

Create a scalar of type `Mpqf` from resp.

- A multi-precision rational `Mpq.t`
- A multi-precision rational `Mpqf.t`
- an integer
- a fraction x/y

```
val of_mpfr : Mpfr.t -> t
```

```
val of_mpfrf : Mpfrf.t -> t
```

Create a scalar of type `Mpfrf` with the given value

```
val of_float : float -> t
```

Create a scalar of type `Float` with the given value

```
val of_infty : int -> t
```

Create a scalar of type `Float` with the value multiplied by infinity (resulting in minus infinity, zero, or infinity)

```
val is_infty : t -> int
```

Infinity test. `is_infty x` returns `-1` if `x` is $-\infty$, `1` if `x` is $+\infty$, and `0` if `x` is finite.

`val sgn : t -> int`

Return the sign of the coefficient, which may be a negative value, zero or a positive value.

`val cmp : t -> t -> int`

Compare two coefficients, possibly converting to `Mpqf.t`. `compare x y` returns a negative number if `x` is less than `y`, 0 if they are equal, and a positive number if `x` is greater than `y`.

`val cmp_int : t -> int -> int`

Compare a coefficient with an integer

`val equal : t -> t -> bool`

Equality test, possibly using a conversion to `Mpqf.t`. Return `true` if the 2 values are equal. Two infinite values of the same signs are considered as equal.

`val equal_int : t -> int -> bool`

Equality test with an integer

`val neg : t -> t`

Negation

`val to_string : t -> string`

Conversion to string, using `string_of_double`, `Mpqf.to_string` or `Mpfr.to_string`

`val print : Format.formatter -> t -> unit`

Print a coefficient

Chapter 3

Module Interval : APRON Intervals on scalars

```
type t = {
  mutable inf : Scalar.t ;
  mutable sup : Scalar.t ;
}

APRON Intervals on scalars

val of_scalar : Scalar.t -> Scalar.t -> t
  Build an interval from a lower and an upper bound

val of_infsup : Scalar.t -> Scalar.t -> t
  deprecated

val of_mpq : Mpq.t -> Mpq.t -> t
val of_mpqf : Mpqf.t -> Mpqf.t -> t
val of_int : int -> int -> t
val of_frac : int -> int -> int -> int -> t
val of_float : float -> float -> t
val of_mpfr : Mpfr.t -> Mpfr.t -> t
  Create an interval from resp. two
  • multi-precision rationals Mpq.t
  • multi-precision rationals Mpqf.t
  • integers
  • fractions  $x/y$  and  $z/w$ 
  • machine floats
  • Mpfr floats

val is_top : t -> bool
  Does the interval represent the universe ( $[-\infty, +\infty]$ ) ?

val is_bottom : t -> bool
  Does the interval contain no value ( $[a, b]$  with  $a > b$ ) ?

val is_leq : t -> t -> bool
```

Inclusion test. `is_leq x y` returns `true` if `x` is included in `y`

`val cmp : t -> t -> int`

Non Total Comparison: 0: equality -1: i1 included in i2 +1: i2 included in i1 -2: i1.inf less than or equal to i2.inf +2: i1.inf greater than i2.inf

`val equal : t -> t -> bool`

Equality test

`val is_zero : t -> bool`

Is the interval equal to 0,0 ?

`val equal_int : t -> int -> bool`

Is the interval equal to i,i ?

`val neg : t -> t`

Negation

`val top : t`

`val bottom : t`

Top and bottom intervals (using DOUBLE coefficients)

`val set_infsup : t -> Scalar.t -> Scalar.t -> unit`

Fill the interval with the given lower and upper bounds

`val set_top : t -> unit`

`val set_bottom : t -> unit`

Fill the interval with top (resp. bottom) value

`val print : Format.formatter -> t -> unit`

Print an interval, under the format [inf,sup]

Chapter 4

Module Coeff : APRON Coefficients (either scalars or intervals)

```
type union_5 =
  | Scalar of Scalar.t
  | Interval of Interval.t

type t = union_5

APRON Coefficients (either scalars or intervals)

val s_of_mpq : Mpq.t -> t
val s_of_mpqf : Mpqf.t -> t
val s_of_int : int -> t
val s_of_frac : int -> int -> t

Create a scalar coefficient of type Mpqf.t from resp.

• A multi-precision rational Mpq.t
• A multi-precision rational Mpqf.t
• an integer
• a fraction x/y

val s_of_float : float -> t

Create an interval coefficient of type Float with the given value

val s_of_mpfr : Mpfr.t -> t

Create an interval coefficient of type Mpfr with the given value

val i_of_scalar : Scalar.t -> Scalar.t -> t

Build an interval from a lower and an upper bound

val i_of_mpq : Mpq.t -> Mpq.t -> t
val i_of_mpqf : Mpqf.t -> Mpqf.t -> t
val i_of_int : int -> int -> t
val i_of_frac : int -> int -> int -> int -> t
val i_of_float : float -> float -> t
val i_of_mpfr : Mpfr.t -> Mpfr.t -> t

Create an interval coefficient from resp. two
```

- multi-precision rationals Mpq.t
- multi-precision rationals Mpqf.t
- integers
- fractions x/y and z/w
- machine floats
- Mpfr floats

```
val is_scalar : t -> bool
val is_interval : t -> bool
val cmp : t -> t -> int
```

Non Total Comparison:

- If the 2 coefficients are both scalars, corresp. to Scalar.cmp
- If the 2 coefficients are both intervals, corresp. to Interval.cmp
- otherwise, -3 if the first is a scalar, 3 otherwise

```
val equal : t -> t -> bool
```

Equality test

```
val is_zero : t -> bool
```

Is the coefficient equal to scalar 0 or interval 0,0 ?

```
val equal_int : t -> int -> bool
```

Is the coefficient equal to scalar b or interval b,b ?

```
val neg : t -> t
```

Negation

```
val reduce : t -> t
```

Convert interval to scalar if possible

```
val print : Format.formatter -> t -> unit
```

Printing

Part II

Managers and Abstract Domains

Chapter 5

Module Manager : APRON Managers

```
type funid =
| Funid_unknown
| Funid_copy
| Funid_free
| Funid_asize
| Funid_minimize
| Funid_canonicalize
| Funid_hash
| Funid_approximate
| Funid_fprint
| Funid_fprintfdiff
| Funid_fdump
| Funid_serialize_raw
| Funid_deserialize_raw
| Funid_bottom
| Funid_top
| Funid_of_box
| Funid_dimension
| Funid_is_bottom
| Funid_is_top
| Funid_is_leq
| Funid_is_eq
| Funid_is_dimension_unconstrained
| Funid_sat_interval
| Funid_sat_lincons
| Funid_sat_tcons
| Funid_bound_dimension
| Funid_bound_linexpr
| Funid_bound_texpr
| Funid_to_box
| Funid_to_lincons_array
| Funid_to_tcons_array
| Funid_to_generator_array
| Funid_meet
| Funid_meet_array
| Funid_meet_lincons_array
| Funid_meet_tcons_array
| Funid_join
| Funid_join_array
```

```

| Funid_add_ray_array
| Funid_assign_linexpr_array
| Funid_substitute_linexpr_array
| Funid_assign_texpr_array
| Funid_substitute_texpr_array
| Funid_add_dimensions
| Funid_remove_dimensions
| Funid_permute_dimensions
| Funid_forget_array
| Funid_expand
| Funid_fold
| Funid_widening
| Funid_closure
| Funid_change_environment
| Funid_rename_array

type funopt = {
  algorithm : int ;
  timeout : int ;
  max_object_size : int ;
  flag_exact_wanted : bool ;
  flag_best_wanted : bool ;
}

type exc =
| Exc_none
| Exc_timeout
| Exc_out_of_space
| Exc_overflow
| Exc_invalid_argument
| Exc_not_implemented

type exclog = {
  exn : exc ;
  funid : funid ;
  msg : string ;
}

```

type 'a t

APRON Managers

The type parameter '`'a`' allows to distinguish managers allocated by different underlying abstract domains.
APRON Managers

The type parameter '`'a`' allows to distinguish managers allocated by different underlying abstract domains.
Concerning the other types,

- `funid` defines identifiers for the generic function working on abstract values;
- `funopt` defines the options associated to generic functions;
- `exc` defines the different kind of exceptions;
- `exclog` defines the exceptions raised by APRON functions.

`val get_library : 'a t -> string`

Get the name of the effective library which allocated the manager

`val get_version : 'a t -> string`

Get the version of the effective library which allocated the manager

`val funopt_make : unit -> funopt`

Return the default options for any function (0 or `false` for all fields)

`val get_funopt : 'a t -> funid -> funopt`

Get the options sets for the function. The result is a copy of the internal structure and may be freely modified. `funid` should be different from `Funid_change_environment` and `Funid_rename_array` (no option associated to them).

`val set_funopt : 'a t -> funid -> funopt -> unit`

Set the options for the function. `funid` should be different from `Funid_change_environment` and `Funid_rename_array` (no option associated to them).

`val get_flag_exact : 'a t -> bool`

Get the corresponding result flag

`val get_flag_best : 'a t -> bool`

Get the corresponding result flag

`exception Error of exclog`

Exception raised by functions of the interface

`val string_of_funid : funid -> string``val string_of_exc : exc -> string``val print_funid : Format.formatter -> funid -> unit``val print_funopt : Format.formatter -> funopt -> unit``val print_exc : Format.formatter -> exc -> unit``val print_exclog : Format.formatter -> exclog -> unit`

Printing functions

`val set_deserialize : 'a t -> unit`

Set / get the global manager used for deserialization

`val get_deserialize : unit -> 'a t`

Chapter 6

Module Box : Intervals abstract domain

```
type t
```

Type of boxes.

Boxes constrains each dimension/variable x_i to belong to an interval I_i .

Abstract values which are boxes have the type `t Apron.AbstractX.t`.

Managers allocated for boxes have the type `t Apron.manager.t`.

```
val manager_alloc : unit -> t Apron.Manager.t
```

Create a Box manager.

6.1 Type conversions

```
val manager_is_box : 'a Apron.Manager.t -> bool
```

Return `true` iff the argument manager is a box manager

```
val manager_of_box : t Apron.Manager.t -> 'a Apron.Manager.t
```

Make a box manager generic

```
val manager_to_box : 'a Apron.Manager.t -> t Apron.Manager.t
```

Instanciate the type of a box manager. Raises `Failure` if the argument manager is not a box manager

```
module Abstract0 :
```

```
sig
```

```
  val is_box : 'a Apron.Abstract0.t -> bool
```

Return `true` iff the argument value is a box value

```
  val of_box : Box.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
```

Make a box value generic

```
  val to_box : 'a Apron.Abstract0.t -> Box.t Apron.Abstract0.t
```

Instanciate the type of a box value. Raises `Failure` if the argument value is not a box value

```

end

module Abstract1 :
sig
  val is_box : 'a Apron.Abstract1.t -> bool
    Return true iff the argument value is a box value

  val of_box : Box.t Apron.Abstract1.t -> 'a Apron.Abstract1.t
    Make a box value generic

  val to_box : 'a Apron.Abstract1.t -> Box.t Apron.Abstract1.t
    Instanciate the type of a box value. Raises Failure if the argument value is not a box value

end

module Policy :
sig
  val is_box : 'a Apron.Policy.t -> bool
    Return true iff the argument value is a box value

  val of_box : Box.t Apron.Policy.t -> 'a Apron.Policy.t
    Make a box value generic

  val to_box : 'a Apron.Policy.t -> Box.t Apron.Policy.t
    Instanciate the type of a box value. Raises Failure if the argument value is not a box value

  val print :
    (int -> string) -> Format.formatter -> Box.t Apron.Policy.t -> unit
  val print0 : Format.formatter -> Box.t Apron.Policy.t -> unit
  val print1 :
    Apron.Environment.t -> Format.formatter -> Box.t Apron.Policy.t -> unit
end

val policy_manager_alloc : t Apron.Manager.t -> t Apron.Policy.man

```

6.2 Compilation information

See [1.20] for complete explanations. We just show examples with the file `mlexample.ml`.

6.2.1 Bytecode compilation

```

ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.byte \
  bigarray.cma gmp.cma apron.cma boxMPQ.cma mlexample.ml
ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -make-runtime -o myrun \
  bigarray.cma gmp.cma apron.cma boxMPQ.cma

ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -use-runtime myrun -o mlexample.byte \
  bigarray.cma gmp.cma apron.cma boxMPQ.cma mlexample.ml

```

6.2.2 Native-code compilation

```
ocamlopt -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa boxMPQ.cmxa mlexample.ml
```

6.2.3 Without auto-linking feature

```
ocamlopt -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -noautolink -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa boxMPQ.cmxa mlexample.ml \
-cclib "-L$MLGMPIDL_PREFIX/lib -L$APRON_PREFIX/lib \
-lboxMPQ_caml_debug -lboxMPQ_debug \
-lapron_caml_debug -lapron_debug \
-lgmp_caml -L$MPFR_PREFIX/lib -lmpfr -L$GMP/lib_PREFIX/lib -lgmp \
-L$CAMLIDL_PREFIX/lib/ocaml -lcamlidl \
-lbigarray"
```

Chapter 7

Module Oct : Octagon abstract domain.

```
type internal
Octagon abstract domain.

type t
Type of octagons.
Octagons are defined by conjunctions of inequalities of the form  $+/-x_i +/- x_j \geq 0$ .
Abstract values which are octagons have the type t Apron.AbstractX.t.
Managers allocated for octagons have the type t Apron.manager.t.

val manager_alloc : unit -> t Apron.Manager.t
Allocate a new manager to manipulate octagons.

val manager_get_internal : t Apron.Manager.t -> internal
No internal parameters for now...

val of_generator_array :
  t Apron.Manager.t ->
  int -> int -> Apron.Generator0.t array -> t Apron.Abstract0.t
Approximate a set of generators to an abstract value, with best precision.

val widening_thresholds :
  t Apron.Manager.t ->
  t Apron.Abstract0.t ->
  t Apron.Abstract0.t -> Apron.Scalar.t array -> t Apron.Abstract0.t
Widening with scalar thresholds.

val narrowing :
  t Apron.Manager.t ->
  t Apron.Abstract0.t -> t Apron.Abstract0.t -> t Apron.Abstract0.t
Standard narrowing.

val add_epsilon :
  t Apron.Manager.t ->
  t Apron.Abstract0.t -> Apron.Scalar.t -> t Apron.Abstract0.t
Perturbation.
```

```
val add_epsilon_bin :  
  t Apron.Manager.t ->  
  t Apron.Abstract0.t ->  
  t Apron.Abstract0.t -> Apron.Scalar.t -> t Apron.Abstract0.t  
  Perturbation.  
  
val pre_widening : int  
  Algorithms.
```

7.1 Type conversions

```
val manager_is_oct : 'a Apron.Manager.t -> bool  
  Return true iff the argument manager is an octagon manager  
  
val manager_of_oct : t Apron.Manager.t -> 'a Apron.Manager.t  
  Make an octagon manager generic  
  
val manager_to_oct : 'a Apron.Manager.t -> t Apron.Manager.t  
  Instanciate the type of an octagon manager. Raises Failure if the argument manager is not an  
  octagon manager  
  
module Abstract0 :  
  sig  
    val is_oct : 'a Apron.Abstract0.t -> bool  
      Return true iff the argument value is an oct value  
    val of_oct : Oct.t Apron.Abstract0.t -> 'a Apron.Abstract0.t  
      Make an oct value generic  
    val to_oct : 'a Apron.Abstract0.t -> Oct.t Apron.Abstract0.t  
      Instanciate the type of an oct value. Raises Failure if the argument value is not an oct value  
  end  
  
module Abstract1 :  
  sig  
    val is_oct : 'a Apron.Abstract1.t -> bool  
      Return true iff the argument value is an oct value  
    val of_oct : Oct.t Apron.Abstract1.t -> 'a Apron.Abstract1.t  
      Make an oct value generic  
    val to_oct : 'a Apron.Abstract1.t -> Oct.t Apron.Abstract1.t  
      Instanciate the type of an oct value. Raises Failure if the argument value is not an oct value  
  end
```

7.2 Compilation information

See [1.20] for complete explanations. We just show examples with the file `mlexample.ml`.

7.2.1 Bytecode compilation

```
ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.byte \
bigarray.cma gmp.cma apron.cma octD.cma mlexample.ml
ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -make-runtime -o myrun \
bigarray.cma gmp.cma apron.cma octD.cma

ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -use-runtime myrun -o mlexample.byte \
bigarray.cma gmp.cma apron.cma octD.cma mlexample.ml
```

7.2.2 Native-code compilation

```
ocamlopt -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa octD.cmxa mlexample.ml
```

7.2.3 Without auto-linking feature

```
ocamlopt -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -noautolink -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa octD.cmxa mlexample.ml \
-cclib "-L$MLGMPIDL_PREFIX/lib -L$APRON_PREFIX/lib \
-loctD_caml_debug -loctD_debug \
-lapron_caml_debug -lapron_debug \
-lgmp_caml -L$MPFR_PREFIX/lib -lmpfr -L$GMP_PREFIX/lib -lgmp \
-L$CAMLIDL_PREFIX/lib/ocaml -lcamlidl \
-lbigarray"
```

Chapter 8

Module Polka : Convex Polyhedra and Linear Equalities abstract domains

```
type internal
```

Convex Polyhedra and Linear Equalities abstract domains

```
type loose
```

```
type strict
```

Two flavors for convex polyhedra: loose or strict.

Loose polyhedra cannot have strict inequality constraints like $x > 0$. They are algorithmically more efficient (less generators, simpler normalization).

Convex polyhedra are defined by the conjunction of a set of linear constraints of the form

$a_0*x_0 + \dots + a_n*x_n + b \geq 0$ or $a_0*x_0 + \dots + a_n*x_n + b > 0$ where a_0, \dots, a_n, b, c are constants and x_0, \dots, x_n variables.

```
type equalities
```

Linear equalities.

Linear equalities are conjunctions of linear equalities of the form $a_0*x_0 + \dots + a_n*x_n + b = 0$.

```
type 'a t
```

Type of convex polyhedra/linear equalities, where ' a ' is `loose`, `strict` or `equalities`.

Abstract values which are convex polyhedra have the type `(loose t) Apron.Abstract0.t` or `(loose t) Apron.Abstract1.t` or `(strict t) Apron.Abstract0.t` or `(strict t) Apron.Abstract1.t`.

Abstract values which are conjunction of linear equalities have the type `(equalities t) Apron.Abstract0.t` or `(equalities t) Apron.Abstract1.t`.

Managers allocated by `NewPolka` have the type `'a t Apron.Manager.t`.

```
val manager_alloc_loose : unit -> loose t Apron.Manager.t
```

Create a `NewPolka` manager for loose convex polyhedra.

```
val manager_alloc_strict : unit -> strict t Apron.Manager.t
```

Create a `NewPolka` manager for strict convex polyhedra.

```
val manager_alloc_equalities : unit -> equalities t Apron.Manager.t
```

Create a NewPolka manager for conjunctions of linear equalities.

```
val manager_get_internal : 'a t Apron.Manager.t -> internal
```

Get the internal submanager of a NewPolka manager.

Various options. See the C documentation

```
val set_max_coeff_size : internal -> int -> unit
```

```
val set_approximate_max_coeff_size : internal -> int -> unit
```

```
val get_max_coeff_size : internal -> int
```

```
val get_approximate_max_coeff_size : internal -> int
```

8.1 Type conversions

```
val manager_is_polka : 'a Apron.Manager.t -> bool
```

```
val manager_is_polka_loose : 'a Apron.Manager.t -> bool
```

```
val manager_is_polka_strict : 'a Apron.Manager.t -> bool
```

```
val manager_is_polka_equalities : 'a Apron.Manager.t -> bool
```

Return true iff the argument manager is a polka manager

```
val manager_of_polka : 'a t Apron.Manager.t -> 'b Apron.Manager.t
```

```
val manager_of_polka_loose : loose t Apron.Manager.t -> 'a Apron.Manager.t
```

```
val manager_of_polka_strict : strict t Apron.Manager.t -> 'a Apron.Manager.t
```

```
val manager_of_polka_equalities :
```

```
equalities t Apron.Manager.t -> 'a Apron.Manager.t
```

Makes a polka manager generic

```
val manager_to_polka : 'a Apron.Manager.t -> 'b t Apron.Manager.t
```

```
val manager_to_polka_loose : 'a Apron.Manager.t -> loose t Apron.Manager.t
```

```
val manager_to_polka_strict : 'a Apron.Manager.t -> strict t Apron.Manager.t
```

```
val manager_to_polka_equalities :
```

```
'a Apron.Manager.t -> equalities t Apron.Manager.t
```

Instanciate the type of a polka manager. Raises Failure if the argument manager is not a polka manager

```
module Abstract0 :
```

```
sig
```

```
val is_polka : 'a Apron.Abstract0.t -> bool
```

```
val is_polka_loose : 'a Apron.Abstract0.t -> bool
```

```
val is_polka_strict : 'a Apron.Abstract0.t -> bool
```

```
val is_polka_equalities : 'a Apron.Abstract0.t -> bool
```

Return true iff the argument manager is a polka value

```
val of_polka : 'a Polka.t Apron.Abstract0.t -> 'b Apron.Abstract0.t
```

```
val of_polka_loose :
```

```
Polka.loose Polka.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
```

```
val of_polka_strict :
```

```
Polka.strict Polka.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
```

```
val of_polka_equalities :
```

```
Polka.equalities Polka.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
```

Makes a polka value generic

```
val to_polka : 'a Apron.Abstract0.t -> 'b Polka.t Apron.Abstract0.t
val to_polka_loose :
  'a Apron.Abstract0.t -> Polka.loose Polka.t Apron.Abstract0.t
val to_polka_strict :
  'a Apron.Abstract0.t -> Polka.strict Polka.t Apron.Abstract0.t
val to_polka_equalities :
  'a Apron.Abstract0.t -> Polka.equalities Polka.t Apron.Abstract0.t
```

Instantiate the type of a polka value. Raises Failure if the argument manager is not a polka manager

end

module Abstract1 :

sig

```
val is_polka : 'a Apron.Abstract1.t -> bool
val is_polka_loose : 'a Apron.Abstract1.t -> bool
val is_polka_strict : 'a Apron.Abstract1.t -> bool
val is_polka_equalities : 'a Apron.Abstract1.t -> bool
```

Return true iff the argument manager is a polka value

```
val of_polka : 'a Polka.t Apron.Abstract1.t -> 'b Apron.Abstract1.t
val of_polka_loose :
  Polka.loose Polka.t Apron.Abstract1.t -> 'a Apron.Abstract1.t
val of_polka_strict :
  Polka.strict Polka.t Apron.Abstract1.t -> 'a Apron.Abstract1.t
val of_polka_equalities :
  Polka.equalities Polka.t Apron.Abstract1.t -> 'a Apron.Abstract1.t
```

Makes a polka value generic

```
val to_polka : 'a Apron.Abstract1.t -> 'b Polka.t Apron.Abstract1.t
val to_polka_loose :
  'a Apron.Abstract1.t -> Polka.loose Polka.t Apron.Abstract1.t
val to_polka_strict :
  'a Apron.Abstract1.t -> Polka.strict Polka.t Apron.Abstract1.t
val to_polka_equalities :
  'a Apron.Abstract1.t -> Polka.equalities Polka.t Apron.Abstract1.t
```

Instantiate the type of a polka value. Raises Failure if the argument manager is not a polka manager

end

8.2 Compilation information

See [1.20] for complete explanations. We just show examples with the file `mlexample.ml`.

8.2.1 Bytecode compilation

```
ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.byte \
bigarray.cma gmp.cma apron.cma polkaMPQ.cma mlexample.ml
ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -make-runtime -o myrun \
bigarray.cma gmp.cma apron.cma polkaMPQ.cma
ocamlc -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -use-runtime myrun -o mlexample.byte \
bigarray.cma gmp.cma apron.cma polkaMPQ.cma mlexample.ml
```

8.2.2 Native-code compilation

```
ocamlopt -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa polkaMPQ.cmxa mlexample.ml
```

8.2.3 Without auto-linking feature

```
ocamlopt -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -noautolink -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa polkaMPQ.cmxa mlexample.ml \
-cclib "-L$MLGMPIDL_PREFIX/lib -L$APRON_PREFIX/lib \
-lpolkaMPQ_caml_debug -lpolkaMPQ_debug \
-lapron_caml_debug -lapron_debug \
-lgmp_caml -L$MPFR_PREFIX/lib -lmpfr -L$GMP_PREFIX/lib -lgmp \
-L$CAMLIDL_PREFIX/lib/ocaml -lcamlidl \
-lbigarray"
```

Chapter 9

Module Ppl : Convex Polyhedra and Linear Congruences abstract domains (PPL wrapper)

This module is a wrapper around the Parma Polyhedra Library.

```
type loose  
type strict
```

Two flavors for convex polyhedra: loose or strict.

Loose polyhedra cannot have strict inequality constraints like $x > 0$. They are algorithmically more efficient (less generators, simpler normalization). Convex polyhedra are defined by the conjunction of a set of linear constraints of the form $a_0*x_0 + \dots + a_n*x_n + b \geq 0$ or $a_0*x_0 + \dots + a_n*x_n + b > 0$ where a_0, \dots, a_n, b, c are constants and x_0, \dots, x_n variables.

```
type grid
```

Linear congruences.

Linear congruences are defined by the conjunction of equality constraints modulo a rational number, of the form $a_0*x_0 + \dots + a_n*x_n = b \bmod c$, where a_0, \dots, a_n, b, c are constants and x_0, \dots, x_n variables.

```
type 'a t
```

Type of convex polyhedra/linear congruences, where '`'a`' is `loose`, `strict` or `grid`.

Abstract values which are convex polyhedra have the type `loose t Apron.AbstractX.t` or `strict t Apron.AbstractX.t`. Abstract values which are conjunction of linear congruences equalities have the type `grid t Apron.AbstractX.t`. Managers allocated by PPL have the type `'a t Apron.Manager.t`.

```
val manager_alloc_loose : unit -> loose t Apron.Manager.t
```

Allocate a PPL manager for loose convex polyhedra.

```
val manager_alloc_strict : unit -> strict t Apron.Manager.t
```

Allocate a PPL manager for strict convex polyhedra.

```
val manager_alloc_grid : unit -> grid t Apron.Manager.t
```

Allocate a new manager for linear congruences (grids)

9.1 Type conversions

```

val manager_is_ppl_loose : 'a Apron.Manager.t -> bool
val manager_is_ppl_strict : 'a Apron.Manager.t -> bool
val manager_is_ppl_grid : 'a Apron.Manager.t -> bool
    Return true iff the argument manager is a ppl manager

val manager_of_ppl : 'a t Apron.Manager.t -> 'b Apron.Manager.t
val manager_of_ppl_loose : loose t Apron.Manager.t -> 'a Apron.Manager.t
val manager_of_ppl_strict : strict t Apron.Manager.t -> 'a Apron.Manager.t
val manager_of_ppl_grid : grid t Apron.Manager.t -> 'a Apron.Manager.t
    Make a ppl manager generic

val manager_to_ppl : 'a Apron.Manager.t -> 'b t Apron.Manager.t
val manager_to_ppl_loose : 'a Apron.Manager.t -> loose t Apron.Manager.t
val manager_to_ppl_strict : 'a Apron.Manager.t -> strict t Apron.Manager.t
val manager_to_ppl_grid : 'a Apron.Manager.t -> grid t Apron.Manager.t
    Instanciate the type of a ppl manager. Raises Failure if the argument manager is not a ppl
    manager

module Abstract0 :
  sig
    val is_ppl : 'a Apron.Abstract0.t -> bool
    val is_ppl_loose : 'a Apron.Abstract0.t -> bool
    val is_ppl_strict : 'a Apron.Abstract0.t -> bool
    val is_ppl_grid : 'a Apron.Abstract0.t -> bool
        Return true iff the argument manager is a ppl value

    val of_ppl : 'a Ppl.t Apron.Abstract0.t -> 'b Apron.Abstract0.t
    val of_ppl_loose : Ppl.loose Ppl.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
    val of_ppl_strict :
      Ppl.strict Ppl.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
    val of_ppl_grid : Ppl.grid Ppl.t Apron.Abstract0.t -> 'a Apron.Abstract0.t
        Make a ppl value generic

    val to_ppl : 'a Apron.Abstract0.t -> 'b Ppl.t Apron.Abstract0.t
    val to_ppl_loose : 'a Apron.Abstract0.t -> Ppl.loose Ppl.t Apron.Abstract0.t
    val to_ppl_strict :
      'a Apron.Abstract0.t -> Ppl.strict Ppl.t Apron.Abstract0.t
    val to_ppl_grid : 'a Apron.Abstract0.t -> Ppl.grid Ppl.t Apron.Abstract0.t
        Instanciate the type of a ppl value. Raises Failure if the argument manager is not a ppl
        manager

```

```

end

module Abstract1 :
sig

  val is_ppl : 'a Apron.Abstract1.t -> bool
  val is_ppl_loose : 'a Apron.Abstract1.t -> bool
  val is_ppl_strict : 'a Apron.Abstract1.t -> bool
  val is_ppl_grid : 'a Apron.Abstract1.t -> bool

  Return true iff the argument manager is a ppl value

  val of_ppl : 'a Ppl.t Apron.Abstract1.t -> 'b Apron.Abstract1.t
  val of_ppl_loose : Ppl.loose Ppl.t Apron.Abstract1.t -> 'a Apron.Abstract1.t
  val of_ppl_strict :
    Ppl.strict Ppl.t Apron.Abstract1.t -> 'a Apron.Abstract1.t
  val of_ppl_grid : Ppl.grid Ppl.t Apron.Abstract1.t -> 'a Apron.Abstract1.t

  Make a ppl value generic

  val to_ppl : 'a Apron.Abstract1.t -> 'b Ppl.t Apron.Abstract1.t
  val to_ppl_loose : 'a Apron.Abstract1.t -> Ppl.loose Ppl.t Apron.Abstract1.t
  val to_ppl_strict :
    'a Apron.Abstract1.t -> Ppl.strict Ppl.t Apron.Abstract1.t
  val to_ppl_grid : 'a Apron.Abstract1.t -> Ppl.grid Ppl.t Apron.Abstract1.t

  Instanciate the type of a ppl value. Raises Failure if the argument manager is not a ppl
  manager

end

```

9.2 Compilation information

See [1.20] for complete explanations. We just show examples with the file `mlexample.ml`. Do not forget the `-cc "g++"` option: PPL is a C++ library which requires a C++ linker.

9.2.1 Bytecode compilation

```

ocamlc -cc "g++"-I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.byte \
bigarray.cma gmp.cma apron.cma ppl.cma mlexample.ml
ocamlc -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -make-runtime -o myrun \
bigarray.cma gmp.cma apron.cma ppl.cma

ocamlc -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -use-runtime myrun -o mlex-
ample.byte \
bigarray.cma gmp.cma apron.cma ppl.cma mlexample.ml

```

9.2.2 Native-code compilation

```

ocamlopt -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa ppl.cmxa mlexample.ml

```

9.2.3 Without auto-linking feature

```
ocamlopt -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -noautolink -o mlexample.opt \
  bigarray.cmxa gmp.cmxa apron.cmxa ppl.cmxa mlexample.ml \
  -cclib "-L$MLGMPIDL_PREFIX/lib -L$APRON_PREFIX/lib -L$PPL_PREFIX/lib \
  -lap_ppl_caml_debug -lap_ppl_debug -lppl -lgmpxx \
  -lapron_caml_debug -lapron_debug \
  -lgmp_caml -L$MPFR_PREFIX/lib -lmpfr -L$GMP_PREFIX/lib -lgmp \
  -L$CAMLIDL_PREFIX/lib/ocaml -lcamlidl \
  -lbigarray"
```

Chapter 10

Module PolkaGrid : Reduced product of NewPolka polyhedra and PPL grids

```
type 'a t
```

Type of abstract values, where 'a is Polka.loose or Polka.strict.

```
val manager_alloc :  
  'a Polka.t Apron.Manager.t ->  
  Ppl.grid Ppl.t Apron.Manager.t -> 'a t Apron.Manager.t
```

Create a PolkaGrid manager from a (loose or strict) polka manager, and a PPL grid manager

```
val manager_decompose :  
  'a t Apron.Manager.t ->  
  'a Polka.t Apron.Manager.t * Ppl.grid Ppl.t Apron.Manager.t
```

Decompose the manager

```
val decompose :  
  'a t Apron.Abstract0.t ->  
  'a Polka.t Apron.Abstract0.t * Ppl.grid Ppl.t Apron.Abstract0.t
```

Decompose an abstract value

```
val compose :  
  'a t Apron.Manager.t ->  
  'a Polka.t Apron.Abstract0.t ->  
  Ppl.grid Ppl.t Apron.Abstract0.t -> 'a t Apron.Abstract0.t
```

Compose an abstract value

10.1 Type conversions

```
val manager_is_polkagrid : 'a Apron.Manager.t -> bool
```

Return true iff the argument manager is a polkagrid manager

```
val manager_of_polkagrid : 'a t Apron.Manager.t -> 'b Apron.Manager.t
```

Makes a polkagrid manager generic

```
val manager_to_polkagrid : 'a Apron.Manager.t -> 'b t Apron.Manager.t
```

Instantiate the type of a polkagrid manager. Raises `Failure` if the argument manager is not a polkagrid manager

```
module Abstract0 :
```

```
  sig
```

```
    val is_polkagrid : 'a Apron.Abstract0.t -> bool
```

Return `true` iff the argument manager is a polkagrid value

```
    val of_polkagrid : 'a PolkaGrid.t Apron.Abstract0.t -> 'b Apron.Abstract0.t
```

Makes a polkagrid value generic

```
    val to_polkagrid : 'a Apron.Abstract0.t -> 'b PolkaGrid.t Apron.Abstract0.t
```

Instantiate the type of a polkagrid value. Raises `Failure` if the argument manager is not a polkagrid manager

```
  end
```

```
module Abstract1 :
```

```
  sig
```

```
    val is_polkagrid : 'a Apron.Abstract1.t -> bool
```

Return `true` iff the argument manager is a polkagrid value

```
    val of_polkagrid : 'a PolkaGrid.t Apron.Abstract1.t -> 'b Apron.Abstract1.t
```

Makes a polkagrid value generic

```
    val to_polkagrid : 'a Apron.Abstract1.t -> 'b PolkaGrid.t Apron.Abstract1.t
```

Instantiate the type of a polkagrid value. Raises `Failure` if the argument manager is not a polkagrid manager

```
  end
```

10.2 Compilation information

See [1.20] for complete explanations. We just show examples with the file `mlexample.ml`.

Do not forget the `-cc "g++"` option: PPL is a C++ library which requires a C++ linker.

10.2.1 Bytecode compilation

```
ocamlc -cc "g++"-I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.byte \
  bigarray.cma gmp.cma apron.cma polkaMPQ.cma ppl.cma polkaGrid.cma mlexample.ml
ocamlc -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -make-runtime -o myrun \
  bigarray.cma gmp.cma apron.cma polkaMPQ.cma ppl.cma polkaGrid.cma
```

```
ocamlc -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -use-runtime myrun -o mlex-
ample.byte \
  bigarray.cma gmp.cma apron.cma polkaMPQ.cma ppl.cma polkaGrid.cma mlexample.ml
```

10.2.2 Native-code compilation

```
ocamlopt -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa polkaMPQ.cmxa ppl.cmxa polkaGrid.cmxa mlexample.ml
```

10.2.3 Without auto-linking feature

```
ocamlopt -cc "g++" -I $MLGMPIDL_PREFIX/lib -I $APRON_PREFIX/lib -noautolink -o mlexample.opt \
bigarray.cmxa gmp.cmxa apron.cmxa polkaMPQ.cmxa ppl.cmxa polkaGrid.cmxa mlexample.ml \
-cclib "-L$MLGMPIDL_PREFIX/lib -L$APRON_PREFIX/lib -L$PPL_PREFIX/lib \
-lpolkaGrid_caml_debug -lap_pkgrid_debug \
-lpolkaMPQ_caml_debug -lpolkaMPQ_debug \
-lap_ppl_caml_debug -lap_ppl_debug -lppl -lgmpxx \
-lapron_caml_debug -lapron_debug \
-lgmp_caml -L$MPFR_PREFIX/lib -lmpfr -L$GMP_PREFIX/lib -lgmp \
-L$CAMLIDL_PREFIX/lib/ocaml -lcamlidl \
-lbigarray"
```

Part III

Level 1 of the interface

Chapter 11

Module Var : APRON Variables

```
type t
APRON Variables
val of_string : string -> t
    Constructor
val compare : t -> t -> int
    Comparison function
val to_string : t -> string
    Conversion to string
val hash : t -> int
    Hash function
val print : Format.formatter -> t -> unit
    Printing function
val set_var_operations : unit -> unit
    Initialisation of abstract type operations in C library
```

Chapter 12

Module Environment : APRON Environments binding dimensions to names

```
type typvar =
  | INT
  | REAL

type t
APRON Environments binding dimensions to names

val make : Var.t array -> Var.t array -> t
  Making an environment from a set of integer and real variables. Raise Failure in case of name conflict.

val add : t -> Var.t array -> Var.t array -> t
  Adding to an environment a set of integer and real variables. Raise Failure in case of name conflict.

val remove : t -> Var.t array -> t
  Remove from an environment a set of variables. Raise Failure in case of non-existing variables.

val rename : t -> Var.t array -> Var.t array -> t
  Renaming in an environment a set of variables. Raise Failure in case of interferences with the variables that are not renamed.

val rename_perm : t -> Var.t array -> Var.t array -> t * Dim.perm
  Similar to previous function, but returns also the permutation on dimensions induced by the renaming.

val lce : t -> t -> t
  Compute the least common environment of 2 environments, that is, the environment composed of all the variables of the 2 environments. Raise Failure if the same variable has different types in the 2 environments.

val lce_change : t ->
  t -> t * Dim.change option * Dim.change option
  Similar to the previous function, but returns also the transformations required to convert from e1 (resp. e2) to the lce. If None is returned, this means that e1 (resp. e2) is identical to the lce.
```

val dimchange : t -> t -> Dim.change

dimchange e1 e2 computes the transformation for converting from an environment **e1** to a superenvironment **e2**. Raises **Failure** if **e2** is not a superenvironment.

val dimchange2 : t -> t -> Dim.change2

dimchange2 e1 e2 computes the transformation for converting from an environment **e1** to a (compatible) environment **e2**, by first adding (some) variables of **e2** and then removing (some) variables of **e1**. Raises **Failure** if the two environments are incompatible.

val equal : t -> t -> bool

Test equality if two environments

val compare : t -> t -> int

Compare two environment. **compare env1 env2** return **-2** if the environments are not compatible (a variable has different types in the 2 environments), **-1** if **env1** is a subset of **env2**, **0** if equality, **+1** if **env1** is a superset of **env2**, and **+2** otherwise (the lce exists and is a strict superset of both)

val hash : t -> int

Hashing function for environments

val dimension : t -> Dim.dimension

Return the dimension of the environment

val size : t -> int

Return the size of the environment

val mem_var : t -> Var.t -> bool

Return true if the variable is present in the environment.

val typ_of_var : t -> Var.t -> typvar

Return the type of variables in the environment. If the variable does not belong to the environment, raise a **Failure** exception.

val vars : t -> Var.t array * Var.t array

Return the (lexicographically ordered) sets of integer and real variables in the environment

val var_of_dim : t -> Dim.t -> Var.t

Return the variable corresponding to the given dimension in the environment. Raise **Failure** if the dimension is out of the range of the environment (greater than or equal to **dim env**)

val dim_of_var : t -> Var.t -> Dim.t

Return the dimension associated to the given variable in the environment. Raise **Failure** if the variable does not belong to the environment.

val print :
 ?first:(unit, Format.formatter, unit) Pervasives.format ->
 ?sep:(unit, Format.formatter, unit) Pervasives.format ->
 ?last:(unit, Format.formatter, unit) Pervasives.format ->
 Format.formatter -> t -> unit

Printing

Chapter 13

Module Linexpr1 : APRON Expressions of level 1

```
type t = {
  mutable linexpr0 : Linexpr0.t ;
  mutable env : Environment.t ;
}

APRON Expressions of level 1

val make : ?sparse:bool -> Environment.t -> t
  Build a linear expression defined on the given argument, which is sparse by default.

val minimize : t -> unit
  In case of sparse representation, remove zero coefficients

val copy : t -> t
  Copy

val print : Format.formatter -> t -> unit
  Print the linear expression

val set_list : t -> (Coeff.t * Var.t) list -> Coeff.t option -> unit
  Set simultaneously a number of coefficients.

  set_list expr [(c1,"x"); (c2,"y")] (Some cst) assigns coefficients c1 to variable "x",
  coefficient c2 to variable "y", and coefficient cst to the constant. If (Some cst) is replaced by
  None, the constant coefficient is not assigned.

val set_array : t -> (Coeff.t * Var.t) array -> Coeff.t option -> unit
  Set simultaneously a number of coefficients, as set_list.

val iter : (Coeff.t -> Var.t -> unit) -> t -> unit
  Iter the function on the pair coefficient/variable of the linear expression

val get_cst : t -> Coeff.t
  Get the constant

val set_cst : t -> Coeff.t -> unit
  Set the constant
```

CHAPTER 13. Module Linexpr1 : APRON Expressions of level 1

`val get_coeff : t → Var.t → Coeff.t`

Get the coefficient of the variable

`val set_coeff : t → Var.t → Coeff.t → unit`

Set the coefficient of the variable

`val extend_environment : t → Environment.t → t`

Change the environment of the expression for a super-environment. Raise `Failure` if it is not the case

`val extend_environment_with : t → Environment.t → unit`

Side-effect version of the previous function

`val is_integer : t → bool`

Does the linear expression depend only on integer variables ?

`val is_real : t → bool`

Does the linear expression depend only on real variables ?

`val get_linexpr0 : t → Linexpr0.t`

Get the underlying expression of level 0 (which is not a copy).

`val get_env : t → Environment.t`

Get the environment of the expression

Chapter 14

Module Lincons1 : APRON Constraints and array of constraints of level 1

```
type t = {
  mutable lincons0 : Lincons0.t ;
  mutable env : Environment.t ;
}

type earray = {
  mutable lincons0_array : Lincons0.t array ;
  mutable array_env : Environment.t ;
}

APRON Constraints and array of constraints of level 1

type typ = Lincons0.typ =
| EQ
| SUPEQ
| SUP
| DISEQ
| EQMOD of Scalar.t

val make : Linexpr1.t -> typ -> t
  Make a linear constraint. Modifying later the linear expression (not advisable) modifies
  correspondingly the linear constraint and conversely, except for changes of environments

val copy : t -> t
  Copy (deep copy)

val string_of_typ : typ -> string
  Convert a constraint type to a string (=,>=, or >)

val print : Format.formatter -> t -> unit
  Print the linear constraint

val get_typ : t -> typ
  Get the constraint type

val iter : (Coeff.t -> Var.t -> unit) -> t -> unit
```

CHAPTER 14. Module Lincons1 : APRON Constraints and array of constraints of level 1

Iter the function on the pair coefficient/variable of the underlying linear expression

`val get_cst : t -> Coeff.t`

Get the constant of the underlying linear expression

`val set_typ : t -> typ -> unit`

Set the constraint type

`val set_list : t -> (Coeff.t * Var.t) list -> Coeff.t option -> unit`

Set simultaneously a number of coefficients.

`set_list` expr [(c1,"x"); (c2,"y")] (Some cst) assigns coefficients c1 to variable "x", coefficient c2 to variable "y", and coefficient cst to the constant. If (Some cst) is replaced by None, the constant coefficient is not assigned.

`val set_array : t -> (Coeff.t * Var.t) array -> Coeff.t option -> unit`

Set simultaneously a number of coefficients, as `set_list`.

`val set_cst : t -> Coeff.t -> unit`

Set the constant of the underlying linear expression

`val get_coeff : t -> Var.t -> Coeff.t`

Get the coefficient of the variable in the underlying linear expression

`val set_coeff : t -> Var.t -> Coeff.t -> unit`

Set the coefficient of the variable in the underlying linear expression

`val make_unsat : Environment.t -> t`

Build the unsatisfiable constraint $-1 \geq 0$

`val is_unsat : t -> bool`

Is the constraint not satisfiable ?

`val extend_environment : t -> Environment.t -> t`

Change the environment of the constraint for a super-environment. Raise `Failure` if it is not the case

`val extend_environment_with : t -> Environment.t -> unit`

Side-effect version of the previous function

`val get_env : t -> Environment.t`

Get the environment of the linear constraint

`val get_linexpr1 : t -> Linexpr1.t`

Get the underlying linear expression. Modifying the linear expression (*not advisable*) modifies correspondingly the linear constraint and conversely, except for changes of environments

`val get_lincons0 : t -> Lincons0.t`

Get the underlying linear constraint of level 0. Modifying the constraint of level 0 (*not advisable*) modifies correspondingly the linear constraint and conversely, except for changes of environments

14.1 Type array

`val array_make : Environment.t -> int -> earray`

Make an array of linear constraints with the given size and defined on the given environment.

The elements are initialized with the constraint $0=0$.

`val array_print :`
`?first:(unit, Format.formatter, unit) Pervasives.format ->`
`?sep:(unit, Format.formatter, unit) Pervasives.format ->`
`?last:(unit, Format.formatter, unit) Pervasives.format ->`
`Format.formatter -> earray -> unit`

Print an array of constraints

`val array_length : earray -> int`

Get the size of the array

`val array_get_env : earray -> Environment.t`

Get the environment of the array

`val array_get : earray -> int -> t`

Get the element of the given index (which is not a copy)

`val array_set : earray -> int -> t -> unit`

Set the element of the given index (without any copy). The array and the constraint should be defined on the same environment; otherwise a `Failure` exception is raised.

`val array_extend_environment : earray -> Environment.t -> earray`

Change the environment of the array of constraints for a super-environment. Raise `Failure` if it is not the case

`val array_extend_environment_with : earray -> Environment.t -> unit`

Side-effect version of the previous function

Chapter 15

Module Generator1 : APRON Generators and array of generators of level 1

```
type t = {
  mutable generator0 : Generator0.t ;
  mutable env : Environment.t ;
}

type earray = {
  mutable generator0_array : Generator0.t array ;
  mutable array_env : Environment.t ;
}

APRON Generators and array of generators of level 1

type typ = Generator0.typ =
| LINE
| RAY
| VERTEX
| LINEMOD
| RAYMOD

val make : Linexpr1.t -> Generator0.typ -> t
  Make a generator. Modifying later the linear expression (not advisable) modifies correspondingly
  the generator and conversely, except for changes of environments

val copy : t -> t
  Copy (deep copy)

val print : Format.formatter -> t -> unit
  Print the generator

val get_typ : t -> Generator0.typ
  Get the generator type

val iter : (Coeff.t -> Var.t -> unit) -> t -> unit
  Iter the function on the pair coefficient/variable of the underlying linear expression

val set_typ : t -> Generator0.typ -> unit
```

Set the generator type

`val set_list : t -> (Coeff.t * Var.t) list -> unit`

Set simultaneously a number of coefficients.

`set_list expr [(c1,"x"); (c2,"y")]` assigns coefficients `c1` to variable "x" and coefficient `c2` to variable "y".

`val set_array : t -> (Coeff.t * Var.t) array -> unit`

Set simultaneously a number of coefficients, as `set_list`.

`val get_coeff : t -> Var.t -> Coeff.t`

Get the coefficient of the variable in the underlying linear expression

`val set_coeff : t -> Var.t -> Coeff.t -> unit`

Set the coefficient of the variable in the underlying linear expression

`val extend_environment : t -> Environment.t -> t`

Change the environment of the generator for a super-environment. Raise `Failure` if it is not the case

`val extend_environment_with : t -> Environment.t -> unit`

Side-effect version of the previous function

15.1 Type earray

`val array_make : Environment.t -> int -> earray`

Make an array of generators with the given size and defined on the given environment. The elements are initialized with the line 0.

`val array_print : ?first:(unit, Format.formatter, unit) Pervasives.format -> ?sep:(unit, Format.formatter, unit) Pervasives.format -> ?last:(unit, Format.formatter, unit) Pervasives.format -> Format.formatter -> earray -> unit`

Print an array of generators

`val array_length : earray -> int`

Get the size of the array

`val array_get : earray -> int -> t`

Get the element of the given index (which is not a copy)

`val array_set : earray -> int -> t -> unit`

Set the element of the given index (without any copy). The array and the generator should be defined on the same environment; otherwise a `Failure` exception is raised.

`val array_extend_environment : earray -> Environment.t -> earray`

Change the environment of the array of generators for a super-environment. Raise `Failure` if it is not the case

`val array_extend_environment_with : earray -> Environment.t -> unit`

CHAPTER 15. Module Generator1 : APRON Generators and array of generators of level 1

Side-effect version of the previous function

val get_env : t -> Environment.t

Get the environment of the generator

val get_linexpr1 : t -> Linexpr1.t

Get the underlying linear expression. Modifying the linear expression (*not advisable*) modifies correspondingly the generator and conversely, except for changes of environments

val get_generator0 : t -> Generator0.t

Get the underlying generator of level 0. Modifying the generator of level 0 (*not advisable*) modifies correspondingly the generator and conversely, except for changes of environments

Chapter 16

Module Texpr1 : APRON Expressions of level 1

```
type t = {
  mutable texpr0 : Texpr0.t ;
  mutable env : Environment.t ;
}
```

APRON Expressions of level 1

```
type unop = Texpr0.unop =
| Neg
| Cast
| Sqrt
```

Unary operators

```
type binop = Texpr0.binop =
| Add
| Sub
| Mul
| Div
| Mod
| Pow
```

Binary operators

```
type typ = Texpr0.typ =
| Real
| Int
| Single
| Double
| Extended
| Quad
```

Destination type for rounding

```
type round = Texpr0.round =
| Near
| Zero
| Up
| Down
| Rnd
```

Rounding direction

```
type expr =
| Cst of Coeff.t
| Var of Var.t
| Unop of unop * expr * typ * round
| Binop of binop * expr * expr * typ * round
```

User type for tree expressions

16.1 Constructors and Destructor

```
val of_expr : Environment.t -> expr -> t
  General constructor (actually the most efficient)

val copy : t -> t
  Copy

val of_linexpr : Linexpr1.t -> t
  Conversion

val to_expr : t -> expr
  General destructor
```

16.1.1 Incremental constructors

```
val cst : Environment.t -> Coeff.t -> t
val var : Environment.t -> Var.t -> t
val unop : Texpr0.unop -> t -> Texpr0.typ -> Texpr0.round -> t
val binop : Texpr0.binop ->
  t -> t -> Texpr0.typ -> Texpr0.round -> t
```

16.2 Tests

```
val is_interval_cst : t -> bool
val is_interval_linear : t -> bool
val is_interval_polynomial : t -> bool
val is_interval_polyfrac : t -> bool
val is_scalar : t -> bool
```

16.3 Operations

```
val extend_environment : t -> Environment.t -> t
  Change the environment of the expression for a super-environment. Raise Failure if it is not the case

val extend_environment_with : t -> Environment.t -> unit
  Side-effect version of the previous function

val get_texpr0 : t -> Texpr0.t
```

Get the underlying expression of level 0 (which is not a copy).

```
val get_env : t -> Environment.t  
Get the environment of the expression
```

16.4 Printing

```
val string_of_unop : unop -> string  
val string_of_binop : binop -> string  
val string_of_typ : typ -> string  
val string_of_round : round -> string  
val print_unop : Format.formatter -> unop -> unit  
val print_binop : Format.formatter -> binop -> unit  
val print_typ : Format.formatter -> typ -> unit  
val print_round : Format.formatter -> round -> unit  
val print_expr : Format.formatter -> expr -> unit  
  
Print a tree expression  
  
val print : Format.formatter -> t -> unit  
Print an abstract tree expression
```

Chapter 17

Module Tcons1 : APRON tree constraints and array of tree constraints of level 1

```
type t = {
  mutable tcons0 : Tcons0.t ;
  mutable env : Environment.t ;
}

type earray = {
  mutable tcons0_array : Tcons0.t array ;
  mutable array_env : Environment.t ;
}

APRON tree constraints and array of tree constraints of level 1

type typ = Lincons0.typ =
| EQ
| SUPEQ
| SUP
| DISEQ
| EQMOD of Scalar.t

val make : Texpr1.t -> typ -> t

  Make a tree expression constraint. Modifying later the linear expression (not advisable) modifies correspondingly the tree expression constraint and conversely, except for changes of environments

val copy : t -> t
  Copy (deep copy)

val string_of_typ : typ -> string
  Convert a constraint type to a string (=,>=, or >)

val print : Format.formatter -> t -> unit
  Print the tree expression constraint

val get_typ : t -> typ
  Get the constraint type

val set_typ : t -> typ -> unit
```

Set the constraint type

`val extend_environment : t -> Environment.t -> t`

Change the environment of the constraint for a super-environment. Raise `Failure` if it is not the case

`val extend_environment_with : t -> Environment.t -> unit`

Side-effect version of the previous function

`val get_env : t -> Environment.t`

Get the environment of the tree expression constraint

`val get_texpr1 : t -> Texpr1.t`

Get the underlying linear expression. Modifying the linear expression (*not advisable*) modifies correspondingly the tree expression constraint and conversely, except for changes of environments

`val get_tcons0 : t -> Tcons0.t`

Get the underlying tree expression constraint of level 0. Modifying the constraint of level 0 (*not advisable*) modifies correspondingly the tree expression constraint and conversely, except for changes of environments

17.1 Type array

`val array_make : Environment.t -> int -> earray`

Make an array of tree expression constraints with the given size and defined on the given environment. The elements are initialized with the constraint 0=0.

`val array_print : ?first:(unit, Format.formatter, unit) Pervasives.format -> ?sep:(unit, Format.formatter, unit) Pervasives.format -> ?last:(unit, Format.formatter, unit) Pervasives.format -> Format.formatter -> earray -> unit`

Print an array of constraints

`val array_length : earray -> int`

Get the size of the array

`val array_get_env : earray -> Environment.t`

Get the environment of the array

`val array_get : earray -> int -> t`

Get the element of the given index (which is not a copy)

`val array_set : earray -> int -> t -> unit`

Set the element of the given index (without any copy). The array and the constraint should be defined on the same environment; otherwise a `Failure` exception is raised.

`val array_extend_environment : earray -> Environment.t -> earray`

Change the environment of the array of constraints for a super-environment. Raise `Failure` if it is not the case

`val array_extend_environment_with : earray -> Environment.t -> unit`

Side-effect version of the previous function

Chapter 18

Module Abstract1 : APRON Abstract values of level 1

```
type 'a t = {  
    mutable abstract0 : 'a Abstract0.t ;  
    mutable env : Environment.t ;  
}
```

APRON Abstract values of level 1

The type parameter 'a allows to distinguish abstract values with different underlying abstract domains.

```
type box1 = {  
    mutable interval_array : Interval.t array ;  
    mutable box1_env : Environment.t ;  
}
```

18.1 General management

18.1.1 Memory

```
val copy : 'a Manager.t -> 'a t -> 'a t
```

Copy a value

```
val size : 'a Manager.t -> 'a t -> int
```

Return the abstract size of a value

18.1.2 Control of internal representation

```
val minimize : 'a Manager.t -> 'a t -> unit
```

Minimize the size of the representation of the value. This may result in a later recomputation of internal information.

```
val canonicalize : 'a Manager.t -> 'a t -> unit
```

Put the abstract value in canonical form. (not yet clear definition)

```
val hash : 'a Manager.t -> 'a t -> int
```

```
val approximate : 'a Manager.t -> 'a t -> int -> unit
```

approximate man abs alg perform some transformation on the abstract value, guided by the argument `alg`. The transformation may lose information. The argument `alg` overrides the field algorithm of the structure of type `Manager.funopt` associated to `ap_abstract0_approximate` (commodity feature).

18.1.3 Printing

```
val fdump : 'a Manager.t -> 'a t -> unit
```

Dump on the `stdout` C stream the internal representation of an abstract value, for debugging purposes

```
val print : Format.formatter -> 'a t -> unit
```

Print as a set of constraints

18.1.4 Serialization

18.2 Constructor, accessors, tests and property extraction

18.2.1 Basic constructors

18.2.2 Serialization

18.3 Constructor, accessors, tests and property extraction

18.3.1 Basic constructors

All these functions request explicitly an environment in their arguments.

```
val bottom : 'a Manager.t -> Environment.t -> 'a t
```

Create a bottom (empty) value defined on the given environment

```
val top : 'a Manager.t -> Environment.t -> 'a t
```

Create a top (universe) value defined on the given environment

```
val of_box :
  'a Manager.t ->
  Environment.t -> Var.t array -> Interval.t array -> 'a t
```

Abstract an hypercube.

`of_box man env tvar tinterval` abstracts an hypercube defined by the arrays `tvar` and `tinterval`. The result is defined on the environment `env`, which should contain all the variables in `tvar` (and defines their type)

18.3.2 Accessors

```
val manager : 'a t -> 'a Manager.t
```

```
val env : 'a t -> Environment.t
```

```
val abstract0 : 'a t -> 'a Abstract0.t
```

Return resp. the underlying manager, environment and abstract value of level 0

18.3.3 Tests

```
val is_bottom : 'a Manager.t -> 'a t -> bool
    Emptiness test

val is_top : 'a Manager.t -> 'a t -> bool
    Universality test

val is_leq : 'a Manager.t -> 'a t -> 'a t -> bool
    Inclusion test. The 2 abstract values should be compatible.

val is_eq : 'a Manager.t -> 'a t -> 'a t -> bool
    Equality test. The 2 abstract values should be compatible.

val sat_lincons : 'a Manager.t -> 'a t -> Lincons1.t -> bool
    Does the abstract value satisfy the linear constraint ?

val sat_tcons : 'a Manager.t -> 'a t -> Tcons1.t -> bool
    Does the abstract value satisfy the tree expression constraint ?

val sat_interval : 'a Manager.t -> 'a t -> Var.t -> Interval.t -> bool
    Does the abstract value satisfy the constraint dim in interval ?

val is_variable_unconstrained : 'a Manager.t -> 'a t -> Var.t -> bool
    Is the variable unconstrained in the abstract value ? If yes, this means that the existential
    quantification of the dimension does not change the value.
```

18.3.4 Extraction of properties

```
val bound_variable : 'a Manager.t -> 'a t -> Var.t -> Interval.t
    Return the interval of variation of the variable in the abstract value.

val bound_linexpr : 'a Manager.t -> 'a t -> Linexpr1.t -> Interval.t
    Return the interval of variation of the linear expression in the abstract value.
    Implement a form of linear programming, where the argument linear expression is the one to
    optimize under the constraints induced by the abstract value.

val bound_texpr : 'a Manager.t -> 'a t -> Texpr1.t -> Interval.t
    Return the interval of variation of the tree expression in the abstract value.

val to_box : 'a Manager.t -> 'a t -> box1
    Convert the abstract value to an hypercube

val to_lincons_array : 'a Manager.t -> 'a t -> Lincons1.earray
    Convert the abstract value to a conjunction of linear constraints.
    Convert the abstract value to a conjunction of tree expressions constraints.

val to_tcons_array : 'a Manager.t -> 'a t -> Tcons1.earray
val to_generator_array : 'a Manager.t -> 'a t -> Generator1.earray
    Convert the abstract value to a set of generators that defines it.
```

18.4 Operations

18.4.1 Meet and Join

`val meet : 'a Manager.t -> 'a t -> 'a t -> 'a t`

Meet of 2 abstract values.

`val meet_array : 'a Manager.t -> 'a t array -> 'a t`

Meet of a non empty array of abstract values.

`val meet_lincons_array : 'a Manager.t -> 'a t -> Lincons1.earray -> 'a t`

Meet of an abstract value with an array of linear constraints.

`val meet_tcons_array : 'a Manager.t -> 'a t -> Tcons1.earray -> 'a t`

Meet of an abstract value with an array of tree expressions constraints.

`val join : 'a Manager.t -> 'a t -> 'a t -> 'a t`

Join of 2 abstract values.

`val join_array : 'a Manager.t -> 'a t array -> 'a t`

Join of a non empty array of abstract values.

`val add_ray_array : 'a Manager.t -> 'a t -> Generator1.earray -> 'a t`

Add the array of generators to the abstract value (time elapse operator).

The generators should either lines or rays, not vertices.

18.4.1.0.1 Side-effect versions of the previous functions

`val meet_with : 'a Manager.t -> 'a t -> 'a t -> unit`

`val meet_lincons_array_with : 'a Manager.t -> 'a t -> Lincons1.earray -> unit`

`val meet_tcons_array_with : 'a Manager.t -> 'a t -> Tcons1.earray -> unit`

`val join_with : 'a Manager.t -> 'a t -> 'a t -> unit`

`val add_ray_array_with : 'a Manager.t -> 'a t -> Generator1.earray -> unit`

18.4.2 Assignement and Substitutions

`val assign_linexpr_array :`

`'a Manager.t ->`

`'a t ->`

`Var.t array -> Linexpr1.t array -> 'a t option -> 'a t`

Parallel assignement of an array of dimensions by an array of same size of linear expressions

`val substitute_linexpr_array :`

`'a Manager.t ->`

`'a t ->`

`Var.t array -> Linexpr1.t array -> 'a t option -> 'a t`

Parallel substitution of an array of dimensions by an array of same size of linear expressions

`val assign_texpr_array :`

`'a Manager.t ->`

`'a t ->`

`Var.t array -> Texpr1.t array -> 'a t option -> 'a t`

CHAPTER 18. Module Abstract1 : APRON Abstract values of level 1

Parallel assignement of an array of dimensions by an array of same size of tree expressions

```
val substitute_texpr_array :  
  'a Manager.t ->  
  'a t ->  
  Var.t array -> Texpr1.t array -> 'a t option -> 'a t
```

Parallel substitution of an array of dimensions by an array of same size of tree expressions

18.4.2.0.1 Side-effect versions of the previous functions

```
val assign_linexpr_array_with :  
  'a Manager.t ->  
  'a t ->  
  Var.t array -> Linexpr1.t array -> 'a t option -> unit  
val substitute_linexpr_array_with :  
  'a Manager.t ->  
  'a t ->  
  Var.t array -> Linexpr1.t array -> 'a t option -> unit  
val assign_texpr_array_with :  
  'a Manager.t ->  
  'a t ->  
  Var.t array -> Texpr1.t array -> 'a t option -> unit  
val substitute_texpr_array_with :  
  'a Manager.t ->  
  'a t ->  
  Var.t array -> Texpr1.t array -> 'a t option -> unit
```

18.4.3 Projections

18.4.4 Projections

These functions implements forgetting (existential quantification) of (array of) variables. Both functional and side-effect versions are provided. The Boolean, if true, adds a projection onto 0-plane.

```
val forget_array : 'a Manager.t -> 'a t -> Var.t array -> bool -> 'a t  
val forget_array_with : 'a Manager.t -> 'a t -> Var.t array -> bool -> unit
```

18.4.5 Change and permutation of dimensions

```
val change_environment :  
  'a Manager.t -> 'a t -> Environment.t -> bool -> 'a t
```

Change the environment of the abstract values.

Variables that are removed are first existentially quantified, and variables that are introduced are unconstrained. The Boolean, if true, adds a projection onto 0-plane for these ones.

```
val minimize_environment : 'a Manager.t -> 'a t -> 'a t
```

Remove from the environment of the abstract value and from the abstract value itself variables that are unconstrained in it.

```
val rename_array :  
  'a Manager.t ->  
  'a t -> Var.t array -> Var.t array -> 'a t
```

Parallel renaming of the environment of the abstract value.

The new variables should not interfere with the variables that are not renamed.

```
val change_environment_with :
  'a Manager.t -> 'a t -> Environment.t -> bool -> unit
val minimize_environment_with : 'a Manager.t -> 'a t -> unit
val rename_array_with :
  'a Manager.t -> 'a t -> Var.t array -> Var.t array -> unit
```

18.4.6 Expansion and folding of dimensions

18.4.7 Expansion and folding of dimensions

These functions allows to expand one dimension into several ones having the same properties with respect to the other dimensions, and to fold several dimensions into one. Formally,

- expand $P(x,y,z) \mid w = P(x,y,z) \text{ inter } P(x,y,w)$ if z is expanded in z and w
- fold $Q(x,y,z,w) \mid w = \exists w:Q(x,y,z,w) \cup (\exists z:Q(x,y,z,w))(z \leftarrow w)$ if z and w are folded onto z

```
val expand : 'a Manager.t -> 'a t -> Var.t -> Var.t array -> 'a t
```

Expansion: `expand a var tvar` expands the variable `var` into itself and the additional variables in `tvar`, which are given the same type as `var`.

It results in $(n+1)$ unrelated variables having same relations with other variables. The additional variables are added to the environment of the argument for making the environment of the result, so they should not belong to the initial environment.

```
val fold : 'a Manager.t -> 'a t -> Var.t array -> 'a t
```

Folding: `fold a tvar` fold the variables in the array `tvar` of size $n \geq 1$ and put the result in the first variable of the array. The other variables of the array are then removed, both from the environment and the abstract value.

```
val expand_with : 'a Manager.t -> 'a t -> Var.t -> Var.t array -> unit
val fold_with : 'a Manager.t -> 'a t -> Var.t array -> unit
```

18.4.8 Widening

```
val widening : 'a Manager.t -> 'a t -> 'a t -> 'a t
```

Widening. Assumes that the first abstract value is included in the second one.

```
val widening_threshold :
  'a Manager.t ->
  'a t -> 'a t -> Lincons1.earray -> 'a t
```

18.4.9 Closure operation

```
val closure : 'a Manager.t -> 'a t -> 'a t
```

Closure: transform strict constraints into non-strict ones.

```
val closure_with : 'a Manager.t -> 'a t -> unit
```

Side-effect version

18.5 Additional operations

```

val of_lincons_array :
  'a Manager.t -> Environment.t -> Lincons1.earray -> 'a t
val of_tcons_array : 'a Manager.t -> Environment.t -> Tcons1.earray -> 'a t
  Abstract a conjunction of constraints

val assign_linexpr :
  'a Manager.t ->
  'a t ->
  Var.t -> Linexpr1.t -> 'a t option -> 'a t
val substitute_linexpr :
  'a Manager.t ->
  'a t ->
  Var.t -> Linexpr1.t -> 'a t option -> 'a t
val assign_texpr :
  'a Manager.t ->
  'a t ->
  Var.t -> Texpr1.t -> 'a t option -> 'a t
val substitute_texpr :
  'a Manager.t ->
  'a t ->
  Var.t -> Texpr1.t -> 'a t option -> 'a t
  Assignement/Substitution of a single dimension by a single expression

val assign_linexpr_with :
  'a Manager.t ->
  'a t -> Var.t -> Linexpr1.t -> 'a t option -> unit
val substitute_linexpr_with :
  'a Manager.t ->
  'a t -> Var.t -> Linexpr1.t -> 'a t option -> unit
val assign_texpr_with :
  'a Manager.t ->
  'a t -> Var.t -> Texpr1.t -> 'a t option -> unit
val substitute_texpr_with :
  'a Manager.t ->
  'a t -> Var.t -> Texpr1.t -> 'a t option -> unit
  Side-effect version of the previous functions

val unify : 'a Manager.t -> 'a t -> 'a t -> 'a t
  Unification of 2 abstract values on their least common environment

val unify_with : 'a Manager.t -> 'a t -> 'a t -> unit
  Side-effect version

```

Chapter 19

Module Parser : APRON Parsing of expressions

19.1 Introduction

This small module implements the parsing of expressions, constraints and generators. The allowed syntax is simple for linear expressions (no parenthesis) but supports interval expressions. The syntax is more flexible for tree expressions.

19.1.1 Syntax

```
lincons ::= linexpr ('>' | '>=' | '=' | '!=+' | '=' | '<=' | '<') linexpr | linexpr = linexpr 'mod'  
scalar  
gen ::= ('V:' | 'R:' | 'L:' | 'RM:' | 'LM:') linexpr  
linexpr ::= linexpr '+' linterm | linexpr '-' linterm | linterm  
linterm ::= coeff ['*'] identifier | coeff | ['-'] identifier  
tcons ::= texpr ('>' | '>=' | '=' | '!=+' | '=' | '<=' | '<') texpr | texpr = texpr 'mod' scalar  
texpr ::= coeff | identifier | unop texpr | texpr binop texpr | '(' texpr ')' |  
binop ::= ('+' | '-' | '*' | '/' | '%' ) [ '_' ('i' | 'f' | 'd' | 'l' | 'q') ] [ ',' ('n' | '0' | '+oo' | '-oo') ]  
unop ::= ('cast' | 'sqrt') [ '_' ('i' | 'f' | 'd' | 'l' | 'q') ] [ ',' ('n' | '0' | '+oo' | '-oo') ]  
coeff ::= scalar | ['-'] '[' scalar ';' scalar ']'  
scalar ::= ['-'] (integer | rational | floating_point_number)
```

For tree expressions `texpr`, by default the operations have an exact arithmetic semantics in the real numbers (even if involved variables are of integer). The type qualifiers modify this default semantics. Their meaning is as follows:

- `i` integer semantics
- `f` IEEE754 32 bits floating-point semantics
- `d` IEEE754 64 bits floating-point semantics
- `l` IEEE754 80 bits floating-point semantics
- `q` IEEE754 129 bits floating-point semantics

By default, the rounding mode is "any" (this applies only in non-real semantics), which allows to emulate all the following rounding modes:

- `n` nearest

- 0 towards zero
- +oo towards infinity
- -oo towards minus infinity
- ? any

19.1.2 Examples

```
let (linexpr:Linexpr1.t) = Parser.linexpr1_of_string env "z+0.4x+2y"
let (tab:Lincons1.earray) = Parser.lincons1_of_lstring env ["1/2x+2/3y=1"; "[1;2]<=z+2w"; "z+2w<=4"; "0"
let (generator:Generator1.t) = Parser.generator1_of_string env "R:x+2y"
let (texpr:Texpr1.t) = Parser.texpr1_of_string env "a %_i,? b +_f,0 c"
```

19.1.3 Remarks

There is the possibility to parse directly from a lexing buffer, or from a string (from which one can generate a buffer with the function `Lexing.from_string`.

This module uses the underlying modules `Apron_lexer` and `Apron_parser`.

19.2 Introduction

This small module implements the parsing of expressions, constraints and generators. The allowed syntax is simple for linear expressions (no parenthesis) but supports interval expressions. The syntax is more flexible for tree expressions.

19.2.1 Syntax

```
lincons ::= linexpr ('>' | '>=' | '=' | '!=+' | '!' | '<=' | '<') linexpr | linexpr = linexpr 'mod'
scalar
gen ::= ('V:' | 'R:' | 'L:' | 'RM:' | 'LM:') linexpr
linexpr ::= linexpr '+' linterm | linexpr '-' linterm | linterm
linterm ::= coeff ['*'] identifier | coeff | ['-'] identifier
tcons ::= texpr ('>' | '>=' | '=' | '!=+' | '!' | '<=' | '<') texpr | texpr = texpr 'mod' scalar
texpr ::= coeff | identifier | unop texpr | texpr binop texpr | '(' texpr ')'
binop ::= ('+' | '-' | '*' | '/' | '%') ['_']('i' | 'f' | 'd' | 'l' | 'q') [','('n' | '0' | '+oo' | '-oo')]
unop ::= ('cast' | 'sqrt') ['_']('i' | 'f' | 'd' | 'l' | 'q') [','('n' | '0' | '+oo' | '-oo')]
coeff ::= scalar | ['-'] '['scalar ';' scalar ']'
scalar ::= ['-'] (integer | rational | floating_point_number)
```

For tree expressions `texpr`, by default the operations have an exact arithmetic semantics in the real numbers (even if involved variables are of integer). The type qualifiers modify this default semantics. Their meaning is as follows:

- i integer semantics
- f IEEE754 32 bits floating-point semantics
- d IEEE754 64 bits floating-point semantics
- l IEEE754 80 bits floating-point semantics
- q IEEE754 129 bits floating-point semantics

By default, the rounding mode is "any" (this applies only in non-real semantics), which allows to emulate all the following rounding modes:

- n nearest
- 0 towards zero
- +oo towards infinity
- -oo towards minus infinity
- ? any

19.2.2 Examples

```
let (linexpr:Linexpr1.t) = Parser.linexpr1_of_string env "z+0.4x+2y"
let (tab:Lincons1.earray) = Parser.lincons1_of_lstring env "[1/2x+2/3y=1";"[1;2]<=z+2w";"z+2w<=4";"0"
let (generator:Generator1.t) = Parser.generator1_of_string env "R:x+2y"
let (texpr:Texpr1.t) = Parser.texpr1_of_string env "a %_i,? b +_f,0 c"
```

19.2.3 Remarks

There is the possibility to parse directly from a lexing buffer, or from a string (from which one can generate a buffer with the function `Lexing.from_string`.

This module uses the underlying modules `Apron_lexer` and `Apron_parser`.

19.3 Interface

```
exception Error of string
```

Raised by conversion functions

```
val linexpr1_of_lexbuf : Environment.t -> Lexing.lexbuf -> Linexpr1.t
val lincons1_of_lexbuf : Environment.t -> Lexing.lexbuf -> Lincons1.t
val generator1_of_lexbuf : Environment.t -> Lexing.lexbuf -> Generator1.t
```

Conversion from lexing buffers to resp. linear expressions, linear constraints and generators, defined on the given environment.

```
val texpr1expr_of_lexbuf : Lexing.lexbuf -> Texpr1.expr
val texpr1_of_lexbuf : Environment.t -> Lexing.lexbuf -> Texpr1.t
val tcons1_of_lexbuf : Environment.t -> Lexing.lexbuf -> Tcons1.t
```

Conversion from lexing buffers to resp. tree expressions and constraints, defined on the given environment.

```
val linexpr1_of_string : Environment.t -> string -> Linexpr1.t
val lincons1_of_string : Environment.t -> string -> Lincons1.t
val generator1_of_string : Environment.t -> string -> Generator1.t
```

Conversion from strings to resp. linear expressions, linear constraints and generators, defined on the given environment.

```
val texpr1expr_of_string : string -> Texpr1.expr
val texpr1_of_string : Environment.t -> string -> Texpr1.t
val tcons1_of_string : Environment.t -> string -> Tcons1.t
```

CHAPTER 19. Module Parser : APRON Parsing of expressions

Conversion from lexing buffers to resp. tree expressions and constraints, defined on the given environment.

```
val lincons1_of_lstring : Environment.t -> string list -> Lincons1.earray
```

```
val generator1_of_lstring : Environment.t -> string list -> Generator1.earray
```

Conversion from lists of strings to array of resp. linear constraints and generators, defined on the given environment.

```
val tcons1_of_lstring : Environment.t -> string list -> Tcons1.earray
```

Conversion from lists of strings to array of tree constraints.

```
val of_lstring :  
'a Manager.t -> Environment.t -> string list -> 'a Abstract1.t
```

Abstraction of lists of strings representing constraints to abstract values, on the abstract domain defined by the given manager.

Part IV

Level 0 of the interface

Chapter 20

Module Dim : APRON Dimensions and related types

```
type t = int
type change = {
    dim : int array ;
    intdim : int ;
    realdim : int ;
}
type change2 = {
    add : change option ;
    remove : change option ;
}
type perm = int array
type dimension = {
    intd : int ;
    reald : int ;
}
```

APRON Dimensions and related types
APRON Dimensions and related types

- `t=int` is the type of dimensions.
- The semantics of an object (`change:change`) is the following one:
 - `change.intdim` and `change.realdim` indicate the number of integer and real dimensions to add or to remove
 - In case of the addition of dimensions,
`change.dim[i]=k` means: add one dimension at dimension k and shift the already existing dimensions greater than or equal to k one step on the right (or increment them).
if k is equal to the size of the vector, then it means: add a dimension at the end.
Repetition are allowed, and means that one inserts more than one dimensions.
Example: `add_dimensions [i0 i1 r0 r1] { dim=[0 1 2 2 4]; intdim=3; realdim=1 }`
returns `0 i0 0 i1 0 0 r0 r1 0`, considered as a vector with 6 integer dimensions and 3 real dimensions.
 - In case of the removal of dimensions,
`dimchange.dim[i]=k` means: remove the dimension k and shift the dimensions greater than k one step on the left (or decrement them).

Repetitions are meaningless (and are not correct specification)

Example: `remove_dimensions [i0 i1 i2 r0 r1 r2] { dim=[0 2 4]; intdim=2; realdim=1 }` returns `i1 r0 r2`, considered as a vector with 1 integer dimensions and 2 real dimensions.

- The semantics of an object (`change2:change2`) is the combination of the two following transformations:
 - `change2.add` indicates an optional addition of dimensions.
 - `change2.remove` indicates an optional removal of dimensions.
- `perm` defines a permutation.
- `dimension` defines the dimensionality of an abstract value (number of integer and real dimensions).

`val change_add_invert : change -> unit`

Assuming a transformation for `add_dimensions`, invert it in-place to obtain the inverse transformation using `remove_dimensions`

`val perm_compose : perm -> perm -> perm`

`perm_compose perm1 perm2` composes the 2 permutations `perm1` and `perm2` (in this order). The sizes of permutations are supposed to be equal.

`val perm_invert : perm -> perm`

Invert a permutation

Chapter 21

Module Linexpr0 : APRON Linear expressions of level 0

```
type t
APRON Linear expressions of level 0

val make : int option -> t
  Create a linear expression. Its representation is sparse if None is provided, dense of size size if Some size is provided.

val of_list : int option -> (Coeff.t * Dim.t) list -> Coeff.t option -> t
  Combines Linexpr0.make[21] and Linexpr0.set_list[21] (see below)

val of_array : int option -> (Coeff.t * Dim.t) array -> Coeff.t option -> t
  Combines Linexpr0.make[21] and Linexpr0.set_array[21] (see below)

val minimize : t -> unit
  In case of sparse representation, remove zero coefficients

val copy : t -> t
  Copy

val compare : t -> t -> int
  Comparison with lexicographic ordering using Coeff.cmp, terminating by constant

val hash : t -> int
  Hashing function

val get_size : t -> int
  Get the size of the linear expression (which may be sparse or dense)

val get_cst : t -> Coeff.t
  Get the constant

val get_coeff : t -> int -> Coeff.t
  Get the coefficient corresponding to the dimension

val set_list : t -> (Coeff.t * Dim.t) list -> Coeff.t option -> unit
```

CHAPTER 21. Module Linexpr0 : APRON Linear expressions of level 0

Set simultaneously a number of coefficients.

`set_list expr [(c1,1); (c2,2)] (Some cst)` assigns coefficients `c1` to dimension 1, coefficient `c2` to dimension 2, and coefficient `cst` to the constant. If `(Some cst)` is replaced by `None`, the constant coefficient is not assigned.

`val set_array : t -> (Coeff.t * Dim.t) array -> Coeff.t option -> unit`

Set simultaneously a number of coefficients, as `set_list`.

`val set_cst : t -> Coeff.t -> unit`

Set the constant

`val set_coeff : t -> int -> Coeff.t -> unit`

Set the coefficient corresponding to the dimension

Iter the function on the pairs coefficient/dimension of the linear expression

`val iter : (Coeff.t -> Dim.t -> unit) -> t -> unit`

`val print : (Dim.t -> string) -> Format.formatter -> t -> unit`

Print a linear expression, using a function converting from dimensions to names

Chapter 22

Module Lincons0 : APRON Linear constraints of level 0

```
type t = {
  mutable linexpr0 : Linexpr0.t ;
  mutable typ : typ ;
}

type typ =
| EQ
| SUPEQ
| SUP
| DISEQ
| EQMOD of Scalar.t

APRON Linear constraints of level 0

val make : Linexpr0.t -> typ -> t
  Make a linear constraint. Modifying later the linear expression modifies correspondingly the linear constraint and conversely

val copy : t -> t
  Copy a linear constraint (deep copy)

val string_of_typ : typ -> string
  Convert a constraint type to a string (=,>=, or >)

val print : (Dim.t -> string) -> Format.formatter -> t -> unit
  Print a constraint
```

Chapter 23

Module Generator0 : APRON Generators of level 0

```
type typ =
| LINE
| RAY
| VERTEX
| LINEMOD
| RAYMOD

type t = {
  mutable linexpr0 : Linexpr0.t ;
  mutable typ : typ ;
}
```

APRON Generators of level 0

val make : Linexpr0.t -> typ -> t

Making a generator. The constant coefficient of the linear expression is ignored. Modifying later the linear expression modifies correspondingly the generator and conversely.

val copy : t -> t

Copy a generator (deep copy)

val string_of_typ : typ -> string

Convert a generator type to a string (LIN,RAY, or VTX)

val print : (Dim.t -> string) -> Format.formatter -> t -> unit

Print a generator

Chapter 24

Module Texpr0

```
type t
type unop =
  | Neg
  | Cast
  | Sqrt
```

Unary operators

```
type binop =
  | Add
  | Sub
  | Mul
  | Div
  | Mod
  | Pow
```

Binary operators

```
type typ =
  | Real
  | Int
  | Single
  | Double
  | Extended
  | Quad
```

Destination type for rounding

```
type round =
  | Near
  | Zero
  | Up
  | Down
  | Rnd
```

Rounding direction

APRON tree expressions of level 0

```
type expr =
| Cst of Coeff.t
| Dim of Dim.t
| Unop of unop * expr * typ * round
| Binop of binop * expr * expr * typ * round
```

User type for tree expressions

24.1 Constructors and Destructor

```
val of_expr : expr -> t
```

General constructor (actually the most efficient)

```
val copy : t -> t
```

Copy

```
val of_linexpr : Linexpr0.t -> t
```

Conversion

```
val to_expr : t -> expr
```

General destructor

24.1.1 Incremental constructors

```
val cst : Coeff.t -> t
```

```
val dim : Dim.t -> t
```

```
val unop : unop -> t -> typ -> round -> t
```

```
val binop : binop ->
    typ -> round -> t -> t -> t
```

24.2 Tests

```
val is_interval_cst : t -> bool
```

```
val is_interval_linear : t -> bool
```

```
val is_interval_polynomial : t -> bool
```

```
val is_interval_polyfrac : t -> bool
```

```
val is_scalar : t -> bool
```

24.3 Printing

```
val string_of_unop : unop -> string
```

```
val string_of_binop : binop -> string
```

```
val string_of_typ : typ -> string
```

```
val string_of_round : round -> string
```

```
val print_unop : Format.formatter -> unop -> unit
```

CHAPTER 24. Module Texpr0

```
val print_binop : Format.formatter -> binop -> unit
val print_typ : Format.formatter -> typ -> unit
val print_round : Format.formatter -> round -> unit
val print_expr : (Dim.t -> string) -> Format.formatter -> expr -> unit
    Print a tree expression, using a function converting from dimensions to names

val print : (Dim.t -> string) -> Format.formatter -> t -> unit
    Print an abstract tree expression, using a function converting from dimensions to names
```

24.4 Internal usage for level 1

```
val print_sprint_unop : unop -> typ -> round -> string
val print_sprint_binop : binop -> typ -> round -> string
val print_precedence_of_unop : unop -> int
val print_precedence_of_binop : binop -> int
```

Chapter 25

Module Tcons0 : APRON tree expressions constraints of level 0

```
type t = {  
  mutable texpr0 : Texpr0.t ;  
  mutable typ : Lincons0.typ ;  
}
```

APRON tree expressions constraints of level 0

```
type typ = Lincons0.typ =  
| EQ  
| SUPEQ  
| SUP  
| DISEQ  
| EQMOD of Scalar.t
```

```
val make : Texpr0.t -> typ -> t
```

Make a tree expression constraint. Modifying later the tree expression expression modifies correspondingly the tree expression constraint and conversely

```
val copy : t -> t
```

Copy a tree expression constraint (deep copy)

```
val string_of_typ : typ -> string
```

Convert a constraint type to a string (=,>=, or >)

```
val print : (Dim.t -> string) -> Format.formatter -> t -> unit
```

Print a constraint

Chapter 26

Module Abstract0 : APRON Abstract value of level 0

```
type 'a t
APRON Abstract value of level 0
The type parameter 'a allows to distinguish abstract values with different underlying abstract domains.
val set_gc : int -> unit
    TO BE DOCUMENTED
```

26.1 General management

26.1.1 Memory

```
val copy : 'a Manager.t -> 'a t -> 'a t
    Copy a value
val size : 'a Manager.t -> 'a t -> int
    Return the abstract size of a value
```

26.1.2 Control of internal representation

```
val minimize : 'a Manager.t -> 'a t -> unit
    Minimize the size of the representation of the value. This may result in a later recomputation of
    internal information.
val canonicalize : 'a Manager.t -> 'a t -> unit
    Put the abstract value in canonical form. (not yet clear definition)
val hash : 'a Manager.t -> 'a t -> int
val approximate : 'a Manager.t -> 'a t -> int -> unit
    approximate man abs alg perform some transformation on the abstract value, guided by the
    argument alg. The transformation may lose information. The argument alg overrides the field
    algorithm of the structure of type Manager.funopt associated to ap_abstract0_approximate
    (commodity feature).
```

26.1.3 Printing

```
val fdump : 'a Manager.t -> 'a t -> unit
          Dump on the stdout C stream the internal representation of an abstract value, for debugging purposes

val print : (int -> string) -> Format.formatter -> 'a t -> unit
          Print as a set of constraints
```

26.1.4 Serialization

26.2 Constructor, accessors, tests and property extraction

26.2.1 Basic constructors

```
val bottom : 'a Manager.t -> int -> int -> 'a t
          Create a bottom (empty) value with the given number of integer and real variables

val top : 'a Manager.t -> int -> int -> 'a t
          Create a top (universe) value with the given number of integer and real variables

val of_box : 'a Manager.t -> int -> int -> Interval.t array -> 'a t
          Abstract an hypercube.
          of_box man intdim realdim array abstracts an hypercube defined by the array of intervals of size intdim+realdim
```

26.2.2 Accessors

```
val dimension : 'a Manager.t -> 'a t -> Dim.dimension
val manager : 'a t -> 'a Manager.t
```

26.2.3 Tests

```
val is_bottom : 'a Manager.t -> 'a t -> bool
          Emptiness test

val is_top : 'a Manager.t -> 'a t -> bool
          Universality test

val is_leq : 'a Manager.t -> 'a t -> 'a t -> bool
          Inclusion test. The 2 abstract values should be compatible.

val is_eq : 'a Manager.t -> 'a t -> 'a t -> bool
          Equality test. The 2 abstract values should be compatible.

val sat_lincons : 'a Manager.t -> 'a t -> Lincons0.t -> bool
          Does the abstract value satisfy the linear constraint ?

val sat_tcons : 'a Manager.t -> 'a t -> Tcons0.t -> bool
          Does the abstract value satisfy the tree expression constraint ?
```

CHAPTER 26. Module Abstract0 : APRON Abstract value of level 0

```
val sat_interval : 'a Manager.t -> 'a t -> Dim.t -> Interval.t -> bool
```

Does the abstract value satisfy the constraint dim in interval ?

```
val is_dimension_unconstrained : 'a Manager.t -> 'a t -> Dim.t -> bool
```

Is the dimension unconstrained in the abstract value ? If yes, this means that the existential quantification of the dimension does not change the value.

26.2.4 Extraction of properties

```
val bound_dimension : 'a Manager.t -> 'a t -> Dim.t -> Interval.t
```

Return the interval of variation of the dimension in the abstract value.

```
val bound_linexpr : 'a Manager.t -> 'a t -> Linexpr0.t -> Interval.t
```

Return the interval of variation of the linear expression in the abstract value.

Implement a form of linear programming, where the argument linear expression is the one to optimize under the constraints induced by the abstract value.

```
val bound_texpr : 'a Manager.t -> 'a t -> Texpr0.t -> Interval.t
```

Return the interval of variation of the tree expression in the abstract value.

```
val to_box : 'a Manager.t -> 'a t -> Interval.t array
```

Convert the abstract value to an hypercube

```
val to_lincons_array : 'a Manager.t -> 'a t -> Lincons0.t array
```

Convert the abstract value to a conjunction of linear constraints.

```
val to_tcons_array : 'a Manager.t -> 'a t -> Tcons0.t array
```

Convert the abstract value to a conjunction of tree expression constraints.

```
val to_generator_array : 'a Manager.t -> 'a t -> Generator0.t array
```

Convert the abstract value to a set of generators that defines it.

26.3 Operations

26.3.1 Meet and Join

```
val meet : 'a Manager.t -> 'a t -> 'a t -> 'a t
```

Meet of 2 abstract values.

```
val meet_array : 'a Manager.t -> 'a t array -> 'a t
```

Meet of a non empty array of abstract values.

```
val meet_lincons_array : 'a Manager.t -> 'a t -> Lincons0.t array -> 'a t
```

Meet of an abstract value with an array of linear constraints.

```
val meet_tcons_array : 'a Manager.t -> 'a t -> Tcons0.t array -> 'a t
```

Meet of an abstract value with an array of tree expression constraints.

```
val join : 'a Manager.t -> 'a t -> 'a t -> 'a t
```

Join of 2 abstract values.

```
val join_array : 'a Manager.t -> 'a t array -> 'a t
  Join of a non empty array of abstract values.

val add_ray_array : 'a Manager.t -> 'a t -> Generator0.t array -> 'a t
  Add the array of generators to the abstract value (time elapse operator).
  The generators should either lines or rays, not vertices.
```

26.3.1.0.1 Side-effect versions of the previous functions

```
val meet_with : 'a Manager.t -> 'a t -> 'a t -> unit
val meet_lincons_array_with :
  'a Manager.t -> 'a t -> Lincons0.t array -> unit
val meet_tcons_array_with : 'a Manager.t -> 'a t -> Tcons0.t array -> unit
val join_with : 'a Manager.t -> 'a t -> 'a t -> unit
val add_ray_array_with : 'a Manager.t -> 'a t -> Generator0.t array -> unit
```

26.3.2 Assignements and Substitutions

```
val assign_linexpr_array :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Linexpr0.t array -> 'a t option -> 'a t
  Parallel assignement of an array of dimensions by an array of same size of linear expressions
```

```
val substitute_linexpr_array :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Linexpr0.t array -> 'a t option -> 'a t
  Parallel substitution of an array of dimensions by an array of same size of linear expressions
```

```
val assign_texpr_array :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Texpr0.t array -> 'a t option -> 'a t
  Parallel assignement of an array of dimensions by an array of same size of tree expressions
```

```
val substitute_texpr_array :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Texpr0.t array -> 'a t option -> 'a t
  Parallel substitution of an array of dimensions by an array of same size of tree expressions
```

26.3.2.0.1 Side-effect versions of the previous functions

```
val assign_linexpr_array_with :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Linexpr0.t array -> 'a t option -> unit
val substitute_linexpr_array_with :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Linexpr0.t array -> 'a t option -> unit
```

```
val assign_texpr_array_with :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Texpr0.t array -> 'a t option -> unit
val substitute_texpr_array_with :
  'a Manager.t ->
  'a t ->
  Dim.t array -> Texpr0.t array -> 'a t option -> unit
```

26.3.3 Projections

These functions implements forgetting (existential quantification) of (array of) dimensions. Both functional and side-effect versions are provided. The Boolean, if true, adds a projection onto 0-plane.

```
val forget_array : 'a Manager.t -> 'a t -> Dim.t array -> bool -> 'a t
val forget_array_with : 'a Manager.t -> 'a t -> Dim.t array -> bool -> unit
```

26.3.4 Change and permutation of dimensions

```
val add_dimensions : 'a Manager.t -> 'a t -> Dim.change -> bool -> 'a t
val remove_dimensions : 'a Manager.t -> 'a t -> Dim.change -> 'a t
val apply_dimchange2 : 'a Manager.t -> 'a t -> Dim.change2 -> bool -> 'a t
val permute_dimensions : 'a Manager.t -> 'a t -> Dim.perm -> 'a t
```

26.3.4.0.1 Side-effect versions of the previous functions

```
val add_dimensions_with : 'a Manager.t -> 'a t -> Dim.change -> bool -> unit
val remove_dimensions_with : 'a Manager.t -> 'a t -> Dim.change -> unit
val apply_dimchange2_with :
  'a Manager.t -> 'a t -> Dim.change2 -> bool -> unit
val permute_dimensions_with : 'a Manager.t -> 'a t -> Dim.perm option -> unit
```

26.3.5 Expansion and folding of dimensions

26.3.6 Expansion and folding of dimensions

These functions allows to expand one dimension into several ones having the same properties with respect to the other dimensions, and to fold several dimensions into one. Formally,

- expand $P(x,y,z)$ $z w = P(x,y,z) \text{ inter } P(x,y,w)$ if z is expanded in z and w
- fold $Q(x,y,z,w)$ $z w = \exists w:Q(x,y,z,w) \cup (\exists z:Q(x,y,z,w))(z \leftarrow w)$ if z and w are folded onto z

```
val expand : 'a Manager.t -> 'a t -> Dim.t -> int -> 'a t
```

Expansion: `expand a dim n` expands the dimension `dim` into itself + `n` additional dimensions. It results in $(n+1)$ unrelated dimensions having same relations with other dimensions. The $(n+1)$ dimensions are put as follows:

- original dimension `dim`
- if the dimension is integer, the `n` additional dimensions are put at the end of integer dimensions; if it is real, at the end of the real dimensions.

```
val fold : 'a Manager.t -> 'a t -> Dim.t array -> 'a t
```

Folding: fold a tdim fold the dimensions in the array tdim of size $n \geq 1$ and put the result in the first dimension of the array. The other dimensions of the array are then removed (using ap_abstract0_permit_remove_dimensions).

```
val expand_with : 'a Manager.t -> 'a t -> Dim.t -> int -> unit
val fold_with : 'a Manager.t -> 'a t -> Dim.t array -> unit
```

26.3.7 Widening

```
val widening : 'a Manager.t -> 'a t -> 'a t -> 'a t
```

Widening. Assumes that the first abstract value is included in the second one.

```
val widening_threshold :
  'a Manager.t ->
  'a t -> 'a t -> Lincons0.t array -> 'a t
```

26.3.8 Closure operation

```
val closure : 'a Manager.t -> 'a t -> 'a t
```

Closure: transform strict constraints into non-strict ones.

```
val closure_with : 'a Manager.t -> 'a t -> unit
```

Side-effect version

26.4 Additional operations

```
val of_lincons_array : 'a Manager.t -> int -> int -> Lincons0.t array -> 'a t
val of_tcons_array : 'a Manager.t -> int -> int -> Tcons0.t array -> 'a t
```

Abstract a conjunction of constraints

```
val assign_linexpr :
  'a Manager.t ->
  'a t ->
  Dim.t -> Linexpr0.t -> 'a t option -> 'a t
```

```
val substitute_linexpr :
  'a Manager.t ->
  'a t ->
  Dim.t -> Linexpr0.t -> 'a t option -> 'a t
```

```
val assign_texpr :
  'a Manager.t ->
  'a t ->
  Dim.t -> Texpr0.t -> 'a t option -> 'a t
```

```
val substitute_texpr :
  'a Manager.t ->
  'a t ->
  Dim.t -> Texpr0.t -> 'a t option -> 'a t
```

Assignment/Substitution of a single dimension by a single expression

```
val assign_linexpr_with :
  'a Manager.t ->
  'a t -> Dim.t -> Linexpr0.t -> 'a t option -> unit
```

CHAPTER 26. Module Abstract0 : APRON Abstract value of level 0

```
val substitute_linexpr_with :
  'a Manager.t ->
  'a t -> Dim.t -> Linexpr0.t -> 'a t option -> unit

val assign_texpr_with :
  'a Manager.t ->
  'a t -> Dim.t -> Texpr0.t -> 'a t option -> unit

val substitute_texpr_with :
  'a Manager.t ->
  'a t -> Dim.t -> Texpr0.t -> 'a t option -> unit

Side-effect version of the previous functions

val print_array :
  ?first:(unit, Format.formatter, unit) Pervasives.format ->
  ?sep:(unit, Format.formatter, unit) Pervasives.format ->
  ?last:(unit, Format.formatter, unit) Pervasives.format ->
  (Format.formatter -> 'a -> unit) -> Format.formatter -> 'a array -> unit

General use
```

Part V

MLGmpIDL modules

Chapter 27

Module Mpz : GMP multi-precision integers

```
type 'a tt
GMP multi-precision integers

type m
    Mutable tag

type f
    Functional (immutable) tag

type t = m tt
    Mutable multi-precision integer
```

The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`.

These functions are as efficient as their C counterpart: they do not imply additional memory allocation, unlike the corresponding functions in the module `Mpzf`[32].

The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`.

These functions are as efficient as their C counterpart: they do not imply additional memory allocation, unlike the corresponding functions in the module `Mpzf`[32].

27.1 Pretty printing

```
val print : Format.formatter -> 'a tt -> unit
```

27.2 Initialization Functions

C documentation[<http://gmplib.org/manual/Initializing-Integers.html#Initializing-Integers>]

```
val init : unit -> 'a tt
val init2 : int -> 'a tt
val realloc2 : t -> int -> unit
```

27.3 Assignment Functions

C documentation[<http://gmplib.org/manual/Assigning-Integers.html#Assigning-Integers>]

27.4 Assignment Functions

C documentation[<http://gmplib.org/manual/Assigning-Integers.html#Assigning-Integers>]

The first parameter holds the result.

```
val set : t -> 'a tt -> unit
val set_si : t -> int -> unit
val set_d : t -> float -> unit
For set_q: t -> Mpq.t -> unit, see Mpq.get_z[28.5]
val _set_str : t -> string -> int -> unit
val set_str : t -> string -> base:int -> unit
val swap : t -> t -> unit
```

27.5 Combined Initialization and Assignment Functions

C documentation[http://gmplib.org/manual/Simultaneous-Integer-Init-_0026-Assign.html#Simultaneous-Init]

```
val init_set : 'a tt -> 'b tt
val init_set_si : int -> 'a tt
val init_set_d : float -> 'a tt
val _init_set_str : string -> int -> 'a tt
val init_set_str : string -> base:int -> t
```

27.6 Conversion Functions

C documentation[<http://gmplib.org/manual/Converting-Integers.html#Converting-Integers>]

```
val get_si : 'a tt -> nativeint
val get_int : 'a tt -> int
val get_d : 'a tt -> float
val get_d_2exp : 'a tt -> float * int
val _get_str : int -> 'a tt -> string
val get_str : base:int -> 'a tt -> string
```

27.7 User Conversions

27.8 User Conversions

These functions are additions to or renaming of functions offered by the C library.

```
val to_string : 'a tt -> string
val to_float : 'a tt -> float
val of_string : string -> 'a tt
val of_float : float -> 'a tt
val of_int : int -> 'a tt
```

27.9 Arithmetic Functions

C documentation[<http://gmplib.org/manual/Integer-Arithmetic.html#Integer-Arithmetic>]

27.10 Arithmetic Functions

C documentation[<http://gmplib.org/manual/Integer-Arithmetic.html#Integer-Arithmetic>]

The first parameter holds the result.

```
val add : t -> 'a tt -> 'b tt -> unit
val add_ui : t -> 'a tt -> int -> unit
val sub : t -> 'a tt -> 'b tt -> unit
val sub_ui : t -> 'a tt -> int -> unit
val ui_sub : t -> int -> 'a tt -> unit
val mul : t -> 'a tt -> 'b tt -> unit
val mul_si : t -> 'a tt -> int -> unit
val addmul : t -> 'a tt -> 'b tt -> unit
val addmul_ui : t -> 'a tt -> int -> unit
val submul : t -> 'a tt -> 'b tt -> unit
val submul_ui : t -> 'a tt -> int -> unit
val mul_2exp : t -> 'a tt -> int -> unit
val neg : t -> 'a tt -> unit
val abs : t -> 'a tt -> unit
```

27.11 Division Functions

C documentation[<http://gmplib.org/manual/Integer-Division.html#Integer-Division>]

27.12 Division Functions

C documentation[<http://gmplib.org/manual/Integer-Division.html#Integer-Division>]

27.13 Division Functions

C documentation[<http://gmplib.org/manual/Integer-Division.html#Integer-Division>]

c stands for ceiling, f for floor, and t for truncate (rounds toward 0).

27.13.1 Ceiling division

```
val cdiv_q : t -> 'a tt -> 'b tt -> unit
```

The first parameter holds the quotient.

```
val cdiv_r : t -> 'a tt -> 'b tt -> unit
```

The first parameter holds the remainder.

```
val cdiv_qr : t -> t -> 'a tt -> 'b tt -> unit
```

The two first parameters hold resp. the quotient and the remainder).

```
val cdiv_q_ui : t -> 'a tt -> int -> int
```

The first parameter holds the quotient.

```
val cdiv_r_ui : t -> 'a tt -> int -> int
```

The first parameter holds the remainder.

```
val cdiv_qr_ui : t -> t -> 'a tt -> int -> int
```

The two first parameters hold resp. the quotient and the remainder).

```
val cdiv_ui : 'a tt -> int -> int
```

```
val cdiv_q_2exp : t -> 'a tt -> int -> unit
```

The first parameter holds the quotient.

```
val cdiv_r_2exp : t -> 'a tt -> int -> unit
```

The first parameter holds the remainder.

27.13.2 Floor division

```
val fdiv_q : t -> 'a tt -> 'b tt -> unit
```

```
val fdiv_r : t -> 'a tt -> 'b tt -> unit
```

```
val fdiv_qr : t -> t -> 'a tt -> 'b tt -> unit
```

```
val fdiv_q_ui : t -> 'a tt -> int -> int
```

```
val fdiv_r_ui : t -> 'a tt -> int -> int
```

```
val fdiv_qr_ui : t -> t -> 'a tt -> int -> int
```

```
val fdiv_ui : 'a tt -> int -> int
```

```
val fdiv_q_2exp : t -> 'a tt -> int -> unit
```

```
val fdiv_r_2exp : t -> 'a tt -> int -> unit
```

27.13.3 Truncate division

```
val tdiv_q : t -> 'a tt -> 'b tt -> unit
```

```
val tdiv_r : t -> 'a tt -> 'b tt -> unit
```

```
val tdiv_qr : t -> t -> 'a tt -> 'b tt -> unit
```

```
val tdiv_q_ui : t -> 'a tt -> int -> int
```

```
val tdiv_r_ui : t -> 'a tt -> int -> int
```

```
val tdiv_qr_ui : t -> t -> 'a tt -> int -> int
```

```
val tdiv_ui : 'a tt -> int -> int
```

```
val tdiv_q_2exp : t -> 'a tt -> int -> unit
```

```
val tdiv_r_2exp : t -> 'a tt -> int -> unit
```

27.13.4 Other division-related functions

```
val gmod : t -> 'a tt -> 'b tt -> unit
```

```
val gmod_ui : t -> 'a tt -> int -> int
```

```
val divexact : t -> 'a tt -> 'b tt -> unit
```

```
val divexact_ui : t -> 'a tt -> int -> unit
```

```
val divisible_p : 'a tt -> 'b tt -> bool
```

```
val divisible_ui_p : 'a tt -> int -> bool
```

```
val divisible_2exp_p : 'a tt -> int -> bool
```

```
val congruent_p : 'a tt -> 'b tt -> 'c tt -> bool
```

```
val congruent_ui_p : 'a tt -> int -> int -> bool
```

```
val congruent_2exp_p : 'a tt -> 'b tt -> int -> bool
```

27.14 Exponentiation Functions

C documentation[<http://gmplib.org/manual/Integer-Exponentiation.html#Integer-Exponentiation>]

```
val _powm : t -> 'a tt -> 'b tt -> 'c tt -> unit
val _powm_ui : t -> 'a tt -> int -> 'b tt -> unit
val powm : t -> 'a tt -> 'b tt -> modulo:'c tt -> unit
val powm_ui : t -> 'a tt -> int -> modulo:'b tt -> unit
val pow_ui : t -> 'a tt -> int -> unit
val ui_pow_ui : t -> int -> int -> unit
```

27.15 Root Extraction Functions

C documentation[<http://gmplib.org/manual/Integer-Roots.html#Integer-Roots>]

```
val root : t -> 'a tt -> int -> bool
val sqrt : t -> 'a tt -> unit
val _sqrtrrem : t -> t -> 'a tt -> unit
val sqrtrrem : t -> remainder:t -> 'a tt -> unit
val perfect_power_p : 'a tt -> bool
val perfect_square_p : 'a tt -> bool
```

27.16 Number Theoretic Functions

C documentation[<http://gmplib.org/manual/Number-Theoretic-Functions.html#Number-Theoretic-Functions>]

```
val probab_prime_p : 'a tt -> int -> int
val nextprime : t -> 'a tt -> unit
val gcd : t -> 'a tt -> 'b tt -> unit
val gcd_ui : t option -> 'a tt -> int -> int
val _gcdext : t -> t -> t -> 'a tt -> 'b tt -> unit
val gcdext : gcd:t -> alpha:t -> beta:t -> 'a tt -> 'b tt -> unit
val lcm : t -> 'a tt -> 'b tt -> unit
val lcm_ui : t -> 'a tt -> int -> unit
val invert : t -> 'a tt -> 'b tt -> bool
val jacobi : 'a tt -> 'b tt -> int
val legendre : 'a tt -> 'b tt -> int
val kronecker : 'a tt -> 'b tt -> int
val kronecker_si : 'a tt -> int -> int
val si_kronecker : int -> 'a tt -> int
val remove : t -> 'a tt -> 'b tt -> int
val fac_ui : t -> int -> unit
val bin_ui : t -> 'a tt -> int -> unit
val bin_uui : t -> int -> int -> unit
val fib_ui : t -> int -> unit
val fib2_ui : t -> t -> int -> unit
val lucnum_ui : t -> int -> unit
val lucnum2_ui : t -> t -> int -> unit
```

27.17 Comparison Functions

C documentation[<http://gmplib.org/manual/Integer-Comparisons.html#Integer-Comparisons>]

```
val cmp : 'a tt -> 'b tt -> int
val cmp_d : 'a tt -> float -> int
val cmp_si : 'a tt -> int -> int
val cmpabs : 'a tt -> 'b tt -> int
val cmpabs_d : 'a tt -> float -> int
val cmpabs_ui : 'a tt -> int -> int
val sgn : 'a tt -> int
```

27.18 Logical and Bit Manipulation Functions

C documentation[<http://gmplib.org/manual/Integer-Logic-and-Bit-Fiddling.html#Integer-Logic-and-Bit-Fiddling>]

```
val gand : t -> 'a tt -> 'b tt -> unit
val ior : t -> 'a tt -> 'b tt -> unit
val xor : t -> 'a tt -> 'b tt -> unit
val com : t -> 'a tt -> unit
val popcount : 'a tt -> int
val hamdist : 'a tt -> 'b tt -> int
val scan0 : 'a tt -> int -> int
val scan1 : 'a tt -> int -> int
val setbit : t -> int -> unit
val clrbit : t -> int -> unit
val tstbit : 'a tt -> int -> bool
```

27.19 Input and Output Functions: not interfaced

27.20 Input and Output Functions: not interfaced

27.21 Random Number Functions: see Gmp_random[31] module

27.22 Input and Output Functions: not interfaced

27.23 Random Number Functions: see Gmp_random[31] module

27.24 Input and Output Functions: not interfaced

27.25 Random Number Functions: see Gmp_random[31] module

27.26 Integer Import and Export Functions

C documentation[<http://gmplib.org/manual/Integer-Import-and-Export.html#Integer-Import-and-Export>]

```
val _import :
  t ->
  (int, Bigarray.int32_elt, Bigarray.c_layout) Bigarray.Array1.t ->
```

```
int -> int -> unit
val _export :
  'a tt ->
  int -> int -> (int, Bigarray.int32_elt, Bigarray.c_layout) Bigarray.Array1.t
val import :
  dest:t ->
  (int, Bigarray.int32_elt, Bigarray.c_layout) Bigarray.Array1.t ->
  order:int -> endian:int -> unit
val export :
  'a tt ->
  order:int ->
  endian:int -> (int, Bigarray.int32_elt, Bigarray.c_layout) Bigarray.Array1.t
```

27.27 Miscellaneous Functions

C documentation[<http://gmplib.org/manual/Miscellaneous-Integer-Functions.html#Miscellaneous-Integer-Functions>]

```
val fits_int_p : 'a tt -> bool
val odd_p : 'a tt -> bool
val even_p : 'a tt -> bool
val size : 'a tt -> int
val sizeinbase : 'a tt -> int -> int
val fits_ulong_p : 'a tt -> bool
val fits_slong_p : 'a tt -> bool
val fits_uint_p : 'a tt -> bool
val fits_sint_p : 'a tt -> bool
val fits_ushort_p : 'a tt -> bool
val fits_sshort_p : 'a tt -> bool
```

Chapter 28

Module Mpq : GMP multi-precision rationals

```
type 'a tt
GMP multi-precision rationals
type m
    Mutable tag
type f
    Functional (immutable) tag
type t = m tt
    Mutable multi-precision rationals
```

The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`. These functions are as efficient as their C counterpart: they do not imply additional memory allocation, unlike the corresponding functions in the module `Mpqf`[33].

```
val canonicalize : 'a tt -> unit
```

28.1 Pretty printing

```
val print : Format.formatter -> 'a tt -> unit
```

28.2 Initialization and Assignment Functions

C documentation[<http://gmplib.org/manual/Initializing-Rationals.html#Initializing-Rationals>]

```
val init : unit -> 'a tt
val set : t -> 'a tt -> unit
val set_z : t -> 'a Mpz.tt -> unit
val set_si : t -> int -> int -> unit
val _set_str : t -> string -> int -> unit
val set_str : t -> string -> base:int -> unit
val swap : t -> t -> unit
```

28.3 Additional Initialization and Assignements functions

28.4 Additional Initialization and Assignements functions

These functions are additions to or renaming of functions offered by the C library.

```
val init_set : 'a tt -> 'b tt
val init_set_z : 'a Mpz.tt -> 'b tt
val init_set_si : int -> int -> 'a tt
val init_set_str : string -> base:int -> 'a tt
val init_set_d : float -> 'a tt
```

28.5 Conversion Functions

C documentation[<http://gmplib.org/manual/Rational-Conversions.html#Rational-Conversions>]

```
val get_d : 'a tt -> float
val set_d : t -> float -> unit
val get_z : Mpz.t -> 'a tt -> unit
val _get_str : int -> 'a tt -> string
val get_str : base:int -> t -> string
```

28.6 User Conversions

28.7 User Conversions

These functionss are additions to or renaming of functions offeered by the C library.

```
val to_string : 'a tt -> string
val to_float : 'a tt -> float
val of_string : string -> 'a tt
val of_float : float -> 'a tt
val of_int : int -> 'a tt
val of_frac : int -> int -> 'a tt
val of_mpz : 'a Mpz.tt -> 'b tt
val of_mpz2 : 'a Mpz.tt -> 'b Mpz.tt -> 'c tt
```

28.8 Arithmetic Functions

C documentation[<http://gmplib.org/manual/Rational-Arithmetic.html#Rational-Arithmetic>]

```
val add : t -> 'a tt -> 'b tt -> unit
val sub : t -> 'a tt -> 'b tt -> unit
val mul : t -> 'a tt -> 'b tt -> unit
val mul_2exp : t -> 'a tt -> int -> unit
val div : t -> 'a tt -> 'b tt -> unit
val div_2exp : t -> 'a tt -> int -> unit
val neg : t -> 'a tt -> unit
val abs : t -> 'a tt -> unit
val inv : t -> 'a tt -> unit
```

28.9 Comparison Functions

C documentation[<http://gmplib.org/manual/Comparing-Rationals.html#Comparing-Rationals>]

```
val cmp : 'a tt -> 'b tt -> int
val cmp_si : 'a tt -> int -> int -> int
val sgn : 'a tt -> int
val equal : 'a tt -> 'b tt -> bool
```

28.10 Applying Integer Functions to Rationals

C documentation[<http://gmplib.org/manual/Applying-Integer-Functions.html#Applying-Integer-Functions>]

```
val get_num : Mpz.t -> 'a tt -> unit
val get_den : Mpz.t -> 'a tt -> unit
val set_num : t -> 'a Mpz.tt -> unit
val set_den : t -> 'a Mpz.tt -> unit
```

28.11 Input and Output Functions: not interfaced

Chapter 29

Module Mpfa : GMP multi-precision floating-point numbers

```
type 'a tt
GMP multi-precision floating-point numbers

type m
    Mutable tag

type f
    Functional (immutable) tag

type t = m tt
    Mutable multi-precision floating-point numbers
```

The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`.

These functions are as efficient as their C counterpart: they do not imply additional memory allocation. The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`.

These functions are as efficient as their C counterpart: they do not imply additional memory allocation.

29.1 Pretty printing

```
val print : Format.formatter -> 'a tt -> unit
```

29.2 Initialization Functions

C documentation[<http://gmplib.org/manual/Initializing-Floats.html#Initializing-Floats>]

```
val set_default_prec : int -> unit
val get_default_prec : unit -> int
val init : unit -> 'a tt
val init2 : int -> 'a tt
val get_prec : 'a tt -> int
```

```
val set_prec : t -> int -> unit
val set_prec_raw : t -> int -> unit
```

29.3 Assignment Functions

C documentation[<http://gmplib.org/manual/Assigning-Floats.html#Assigning-Floats>]

```
val set : t -> 'a tt -> unit
val set_si : t -> int -> unit
val set_d : t -> float -> unit
val set_z : t -> 'a Mpz.tt -> unit
val set_q : t -> 'a Mpq.tt -> unit
val _set_str : t -> string -> int -> unit
val set_str : t -> string -> base:int -> unit
val swap : t -> t -> unit
```

29.4 Combined Initialization and Assignment Functions

C documentation[http://gmplib.org/manual/Simultaneous-Float-Init-_0026-Assign.html#Simultaneous-Float]

```
val init_set : 'a tt -> 'b tt
val init_set_si : int -> 'a tt
val init_set_d : float -> 'a tt
val _init_set_str : string -> int -> 'a tt
val init_set_str : string -> base:int -> 'a tt
```

29.5 Conversion Functions

C documentation[<http://gmplib.org/manual/Converting-Floats.html#Converting-Floats>]

```
val get_d : 'a tt -> float
val get_d_2exp : 'a tt -> float * int
val get_si : 'a tt -> nativeint
val get_int : 'a tt -> int
val get_z : Mpz.t -> 'a tt -> unit
val get_q : Mpq.t -> 'a tt -> unit
val _get_str : int -> int -> 'a tt -> string * int
val get_str : base:int -> digits:int -> 'a tt -> string * int
```

29.6 User Conversions

29.7 User Conversions

These functionss are additions to or renaming of functions offered by the C library.

```
val to_string : 'a tt -> string
val to_float : 'a tt -> float
val of_string : string -> 'a tt
val of_float : float -> 'a tt
```

```
val of_int : int -> 'a tt  
val of_mpz : 'a Mpz.tt -> 'b tt  
val of_mpq : 'a Mpq.tt -> 'b tt  
val is_integer : 'a tt -> bool
```

29.8 Arithmetic Functions

C documentation[<http://gmplib.org/manual/Float-Arithmetic.html#Float-Arithmetic>]

```
val add : t -> 'a tt -> 'b tt -> unit  
val add_ui : t -> 'a tt -> int -> unit  
val sub : t -> 'a tt -> 'b tt -> unit  
val ui_sub : t -> int -> 'a tt -> unit  
val sub_ui : t -> 'a tt -> int -> unit  
val mul : t -> 'a tt -> 'b tt -> unit  
val mul_ui : t -> 'a tt -> int -> unit  
val mul_2exp : t -> 'a tt -> int -> unit  
val div : t -> 'a tt -> 'b tt -> unit  
val ui_div : t -> int -> 'a tt -> unit  
val div_ui : t -> 'a tt -> int -> unit  
val div_2exp : t -> 'a tt -> int -> unit  
val sqrt : t -> 'a tt -> unit  
val pow_ui : t -> 'a tt -> int -> unit  
val neg : t -> 'a tt -> unit  
val abs : t -> 'a tt -> unit
```

29.9 Comparison Functions

C documentation[<http://gmplib.org/manual/Float-Comparison.html#Float-Comparison>]

```
val cmp : 'a tt -> 'b tt -> int  
val cmp_d : 'a tt -> float -> int  
val cmp_si : 'a tt -> int -> int  
val sgn : 'a tt -> int  
val _equal : 'a tt -> 'b tt -> int -> bool  
val equal : 'a tt -> 'a tt -> bits:int -> bool  
val reldiff : t -> 'a tt -> 'b tt -> unit
```

29.10 Input and Output Functions: not interfaced**29.11 Input and Output Functions: not interfaced****29.12 Random Number Functions: see Gmp_random[31] module****29.13 Input and Output Functions: not interfaced****29.14 Random Number Functions: see Gmp_random[31] module****29.15 Input and Output Functions: not interfaced****29.16 Random Number Functions: see Gmp_random[31] module****29.17 Miscellaneous Float Functions**C documentation [<http://gmplib.org/manual/Miscellaneous-Float-Functions.html#Miscellaneous-Float-Functions>]

```

val ceil : t -> 'a tt -> unit
val floor : t -> 'a tt -> unit
val trunc : t -> 'a tt -> unit
val integer_p : 'a tt -> bool
val fits_int_p : 'a tt -> bool
val fits_ulong_p : 'a tt -> bool
val fits_slong_p : 'a tt -> bool
val fits_uint_p : 'a tt -> bool
val fits_sint_p : 'a tt -> bool
val fits_ushort_p : 'a tt -> bool
val fits_short_p : 'a tt -> bool

```

Chapter 30

Module Mpfr : MPFR multi-precision floating-point numbers

```
type 'a tt
type round =
  | Near
  | Zero
  | Up
  | Down
  | Away
  | Faith
  | NearAway
MPFR multi-precision floating-point numbers
type m
  Mutable tag
type f
  Functional (immutable) tag
type t = m tt
  Mutable multi-precision floating-point numbers
```

The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`.

These functions are as efficient as their C counterpart: they do not imply additional memory allocation. The following operations are mapped as much as possible to their C counterpart. In case of imperative functions (like `set`, `add`, ...) the first parameter of type `t` is an out-parameter and holds the result when the function returns. For instance, `add x y z` adds the values of `y` and `z` and stores the result in `x`.

These functions are as efficient as their C counterpart: they do not imply additional memory allocation.

30.1 Pretty printing

```
val print : Format.formatter -> 'a tt -> unit
```

```
val print_round : Format.formatter -> round -> unit
val string_of_round : round -> string
```

30.2 Rounding Modes

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Rounding-Related-Functions>]

```
val set_default_rounding_mode : round -> unit
val get_default_rounding_mode : unit -> round
val round_prec : t -> round -> int -> int
```

30.3 Exceptions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Exception-Related-Functions>]

```
val get_emin : unit -> int
val get_emax : unit -> int
val set_emin : int -> unit
val set_emax : int -> unit
val check_range : t -> int -> round -> int
val clear_underflow : unit -> unit
val clear_overflow : unit -> unit
val clear_nanflag : unit -> unit
val clear_inexflag : unit -> unit
val clear_flags : unit -> unit
val underflow_p : unit -> bool
val overflow_p : unit -> bool
val nanflag_p : unit -> bool
val inexflag_p : unit -> bool
```

30.4 Initialization Functions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Initialization-Functions>]

```
val set_default_prec : int -> unit
val get_default_prec : unit -> int
val init : unit -> 'a tt
val init2 : int -> 'a tt
val get_prec : 'a tt -> int
val set_prec : t -> int -> unit
val set_prec_raw : t -> int -> unit
```

30.5 Assignment Functions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Assignment-Functions>]

```
val set : t -> 'a tt -> round -> int
val set_si : t -> int -> round -> int
val set_d : t -> float -> round -> int
```

```
val set_z : t -> 'a Mpz.tt -> round -> int
val set_q : t -> 'a Mpq.tt -> round -> int
val _set_str : t -> string -> int -> round -> unit
val set_str : t -> string -> base:int -> round -> unit
val _strtofr : t -> string -> int -> round -> int * int
val strtofr : t -> string -> base:int -> round -> int * int
```

As MPFR's strtofr, but returns a pair (r,i) where r is the usual\n ternary result, and i is the index in the string of the first not-read character. Thus, i=0 when no number could be read at all, and is equal to the length of the string if everything was read.

```
val set_f : t -> 'a Mpfr.tt -> round -> int
val set_si_2exp : t -> int -> int -> round -> int
val set_inf : t -> int -> unit
val set_nan : t -> unit
val swap : t -> t -> unit
```

30.6 Combined Initialization and Assignment Functions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Combined-Initialization-and-Assignment-Functions>]

```
val init_set : 'a tt -> round -> int * 'b tt
val init_set_si : int -> round -> int * 'a tt
val init_set_d : float -> round -> int * 'a tt
val init_set_f : 'a Mpfr.tt -> round -> int * 'b tt
val init_set_z : 'a Mpz.tt -> round -> int * 'b tt
val init_set_q : 'a Mpq.tt -> round -> int * 'b tt
val _init_set_str : string -> int -> round -> 'a tt
val init_set_str : string -> base:int -> round -> 'a tt
```

30.7 Conversion Functions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Conversion-Functions>]

```
val get_d : 'a tt -> round -> float
val get_d1 : 'a tt -> float
val get_z_exp : Mpz.t -> 'a tt -> int
val get_z : Mpz.t -> 'a tt -> round -> unit
val _get_str : int -> int -> 'a tt -> round -> string * int
val get_str : base:int -> digits:int -> t -> round -> string * int
```

30.8 User Conversions

30.9 User Conversions

These functionss are additions to or renaming of functions offered by the C library.

```
val to_string : 'a tt -> string
val to_float : ?round:round -> 'a tt -> float
val to_mpq : 'a tt -> 'b Mpq.tt
```

```
val of_string : string -> round -> 'a tt
val of_float : float -> round -> 'a tt
val of_int : int -> round -> 'a tt
val of_frac : int -> int -> round -> 'a tt
val of_mpz : 'a Mpz.tt -> round -> 'b tt
val of_mpz2 : 'a Mpz.tt -> 'b Mpz.tt -> round -> 'c tt
val of_mpq : 'a Mpq.tt -> round -> 'b tt
```

30.10 Basic Arithmetic Functions

C documentation [<http://www.mpfr.org/mpfr-current/mpfr.html#Basic-Arithmetic-Functions>]

```
val add : t -> 'a tt -> 'b tt -> round -> int
val add_ui : t -> 'a tt -> int -> round -> int
val add_z : t -> 'a tt -> 'a Mpz.tt -> round -> int
val add_q : t -> 'a tt -> 'a Mpq.tt -> round -> int
val sub : t -> 'a tt -> 'b tt -> round -> int
val ui_sub : t -> int -> 'a tt -> round -> int
val sub_ui : t -> 'a tt -> int -> round -> int
val sub_z : t -> 'a tt -> 'a Mpz.tt -> round -> int
val sub_q : t -> 'a tt -> 'a Mpq.tt -> round -> int
val mul : t -> 'a tt -> 'b tt -> round -> int
val mul_ui : t -> 'a tt -> int -> round -> int
val mul_z : t -> 'a tt -> 'a Mpz.tt -> round -> int
val mul_q : t -> 'a tt -> 'a Mpq.tt -> round -> int
val mul_2ui : t -> 'a tt -> int -> round -> int
val mul_2si : t -> 'a tt -> int -> round -> int
val mul_2exp : t -> 'a tt -> int -> round -> int
val div : t -> 'a tt -> 'b tt -> round -> int
val ui_div : t -> int -> 'a tt -> round -> int
val div_ui : t -> 'a tt -> int -> round -> int
val div_z : t -> 'a tt -> 'a Mpz.tt -> round -> int
val div_q : t -> 'a tt -> 'a Mpq.tt -> round -> int
val div_2ui : t -> 'a tt -> int -> round -> int
val div_2si : t -> 'a tt -> int -> round -> int
val div_2exp : t -> t -> int -> round -> int
val sqrt : t -> 'a tt -> round -> bool
val sqrt_ui : t -> int -> round -> bool
val pow_ui : t -> 'a tt -> int -> round -> bool
val pow_si : t -> 'a tt -> int -> round -> bool
val ui_pow_ui : t -> int -> int -> round -> bool
val ui_pow : t -> int -> 'a tt -> round -> bool
val pow : t -> 'a tt -> 'b tt -> round -> bool
val neg : t -> 'a tt -> round -> int
val abs : t -> 'a tt -> round -> int
```

30.11 Comparison Functions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Comparison-Functions>]

```
val cmp : 'a tt -> 'b tt -> int
val cmp_si : 'a tt -> int -> int
val cmp_si_2exp : 'a tt -> int -> int -> int
val sgn : 'a tt -> int
val _equal : 'a tt -> 'b tt -> int -> bool
val equal : 'a tt -> 'b tt -> bits:int -> bool
val nan_p : 'a tt -> bool
val inf_p : 'a tt -> bool
val number_p : 'a tt -> bool
val reldiff : t -> 'a tt -> 'b tt -> round -> unit
```

30.12 Special Functions

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Special-Functions>]

```
val log : t -> 'a tt -> round -> int
val log2 : t -> 'a tt -> round -> int
val log10 : t -> 'a tt -> round -> int
val exp : t -> 'a tt -> round -> int
val exp2 : t -> 'a tt -> round -> int
val exp10 : t -> 'a tt -> round -> int
val cos : 'a tt -> 'b tt -> round -> int
val sin : 'a tt -> 'b tt -> round -> int
val tan : 'a tt -> 'b tt -> round -> int
val sec : 'a tt -> 'b tt -> round -> int
val csc : 'a tt -> 'b tt -> round -> int
val cot : 'a tt -> 'b tt -> round -> int
val sin_cos : 'a tt -> 'b tt -> 'c tt -> round -> bool
val acos : t -> 'a tt -> round -> int
val asin : t -> 'a tt -> round -> int
val atan : t -> 'a tt -> round -> int
val atan2 : t -> 'a tt -> 'b tt -> round -> int
val cosh : 'a tt -> 'b tt -> round -> int
val sinh : 'a tt -> 'b tt -> round -> int
val tanh : 'a tt -> 'b tt -> round -> int
val sech : 'a tt -> 'b tt -> round -> int
val csch : 'a tt -> 'b tt -> round -> int
val coth : 'a tt -> 'b tt -> round -> int
val acosh : t -> 'a tt -> round -> int
val asinh : t -> 'a tt -> round -> int
val atanh : t -> 'a tt -> round -> int
val fac_ui : t -> int -> round -> int
val log1p : t -> 'a tt -> round -> int
```

```
val expm1 : t -> 'a tt -> round -> int
val eint : t -> 'a tt -> round -> int
val gamma : t -> 'a tt -> round -> int
val lngamma : t -> 'a tt -> round -> int
val zeta : t -> 'a tt -> round -> int
val erf : t -> 'a tt -> round -> int
val erfc : t -> 'a tt -> round -> int
val j0 : t -> 'a tt -> round -> int
val j1 : t -> 'a tt -> round -> int
val jn : t -> int -> 'a tt -> round -> int
val y0 : t -> 'a tt -> round -> int
val y1 : t -> 'a tt -> round -> int
val yn : t -> int -> 'a tt -> round -> int
val fma : t -> 'a tt -> 'b tt -> 'c tt -> round -> int
val fms : t -> 'a tt -> 'b tt -> 'c tt -> round -> int
val agm : t -> 'a tt -> 'b tt -> round -> int
val hypot : t -> 'a tt -> 'b tt -> round -> int
val const_log2 : t -> round -> int
val const_pi : t -> round -> int
val const_euler : t -> round -> int
val const_catalan : t -> round -> int
```

30.13 Input and Output Functions: not interfaced

30.14 Input and Output Functions: not interfaced

30.15 Input and Output Functions: not interfaced

30.16 Miscellaneous Float Functions

C documentation [<http://www.mpfr.org/mpfr-current/mpfr.html#Rounding-Related-Functions>]

```
val rint : t -> 'a tt -> round -> int
val ceil : t -> 'a tt -> int
val floor : t -> 'a tt -> int
val round : t -> 'a tt -> int
val trunc : t -> 'a tt -> int
val frac : t -> 'a tt -> round -> int
val modf : t -> t -> 'a tt -> round -> int
val fmod : t -> 'a tt -> 'b tt -> round -> int
val remainder : t -> 'a tt -> 'b tt -> round -> int
val integer_p : 'a tt -> bool
val nexttoward : t -> 'a tt -> unit
val nextabove : t -> unit
val nextbelow : t -> unit
val min : t -> 'a tt -> 'b tt -> round -> int
```

```
val max : t -> 'a tt -> 'b tt -> round -> int
val get_exp : 'a tt -> int
val set_exp : t -> int -> int
```

Chapter 31

Module Gmp_random : GMP random generation functions

```
type state
GMP random generation functions
GMP random generation functions
GMP random generation functions
```

31.1 Random State Initialization

C documentation[<http://gmplib.org/manual/Random-State-Initialization.html#Random-State-Initialization>]

```
val init_default : unit -> state
val init_lc_2exp : 'a Mpz.t -> int -> int -> state
val init_lc_2exp_size : int -> state
```

31.2 Random State Seeding

C documentation[<http://gmplib.org/manual/Random-State-Seeding.html#Random-State-Seeding>]

```
val seed : state -> 'a Mpz.t -> unit
val seed_ui : state -> int -> unit
```

31.3 Random Number Functions

31.4 Random Number Functions

31.5 Random Number Functions

31.5.1 Integers (Mpz[27])

C documentation[<http://gmplib.org/manual/Integer-Random-Numbers.html#Integer-Random-Numbers>]

```
module Mpz :
sig
  val urandomb : Mpz.t -> Gmp_random.state -> int -> unit
```

CHAPTER 31. Module Gmp_random : GMP random generation functions

```
val urandomm : Mpz.t -> Gmp_random.state -> 'a Mpz.tt -> unit
val rrandomb : Mpz.t -> Gmp_random.state -> int -> unit
end
```

31.5.2 Floating-point (Mpf[29])

C documentation[<http://gmplib.org/manual/Miscellaneous-Float-Functions.html#Miscellaneous-Float-Functions>]

```
module Mpf :
sig
  val urandomb : Mpf.t -> Gmp_random.state -> int -> unit
end
```

31.5.3 Floating-point (Mpfr[30])

C documentation[<http://www.mpfr.org/mpfr-current/mpfr.html#Miscellaneous-Functions>]

```
module Mpfr :
sig
  val urandomb : Mpfr.t -> Gmp_random.state -> unit
  val urandom : 'a Mpfr.tt -> Gmp_random.state -> Mpfr.round -> unit
end
```

Chapter 32

Module Mpzf : GMP multi-precision integers, functional version

Functions in this module has a functional semantics, unlike the corresponding functions in Mpz[27]. These functions are less efficient, due to the additional memory allocation needed for the result.

This module could be extended to offer more functions with a functional semantics, if asked for.

```
type 'a tt = 'a Mpz.tt
```

```
type t = Mpz.f tt
```

multi-precision integer

```
val _mpz : t -> Mpz.t
```

```
val _mpzf : Mpz.t -> t
```

```
val to_mpz : t -> 'a Mpz.tt
```

```
val of_mpz : 'a Mpz.tt -> t
```

Safe conversion from and to Mpz.t.

There is no sharing between the argument and the result.

32.1 Pretty-printing

```
val print : Format.formatter -> 'a tt -> unit
```

32.2 Constructors

```
val of_string : string -> t
```

```
val of_float : float -> t
```

```
val of_int : int -> t
```

32.3 Conversions

```
val to_string : 'a tt -> string
```

```
val to_float : 'a tt -> float
```

32.4 Arithmetic Functions

```

val add : 'a tt -> 'b tt -> t
val add_int : 'a tt -> int -> t
val sub : 'a tt -> 'b tt -> t
val sub_int : 'a tt -> int -> t
val mul : 'a tt -> 'b tt -> t
val mul_int : 'a tt -> int -> t
val cdiv_q : 'a tt -> 'b tt -> t
val cdiv_r : 'a tt -> 'b tt -> t
val cdiv_qr : 'a tt -> 'b tt -> t * t
val fdiv_q : 'a tt -> 'b tt -> t
val fdiv_r : 'a tt -> 'b tt -> t
val fdiv_qr : 'a tt -> 'b tt -> t * t
val tdiv_q : 'a tt -> 'b tt -> t
val tdiv_r : 'a tt -> 'b tt -> t
val tdiv_qr : 'a tt -> 'b tt -> t * t
val divexact : 'a tt -> 'b tt -> t
val gmod : 'a tt -> 'b tt -> t
val gcd : 'a tt -> 'b tt -> t
val lcm : 'a tt -> 'b tt -> t
val neg : 'a tt -> t
val abs : 'a tt -> t

```

32.5 Comparison Functions

```

val cmp : 'a tt -> 'b tt -> int
val cmp_int : 'a tt -> int -> int
val sgn : 'a tt -> int

```

Chapter 33

Module Mpqf : GMP multi-precision rationals, functional version

Functions in this module has a functional semantics, unlike the corresponding functions in Mpq[28]. These functions are less efficient, due to the additional memory allocation needed for the result.

```
type 'a tt = 'a Mpq.tt
type t = Mpq.f tt
multi-precision rationals

val to_mpq : t -> 'a Mpq.tt
val of_mpq : 'a Mpq.tt -> t
```

Safe conversion from and to Mpq.t.

There is no sharing between the argument and the result.

```
val _mpq : t -> Mpq.t
val _mpqf : Mpq.t -> t
Unsafe conversion from and to Mpq.t.

Sharing between the argument and the result.
```

33.1 Pretty-printing

```
val print : Format.formatter -> 'a tt -> unit
```

33.2 Constructors

```
val of_string : string -> t
val of_float : float -> t
val of_int : int -> t
val of_frac : int -> int -> t
val of_mpz : 'a Mpz.tt -> t
val of_mpz2 : 'a Mpz.tt -> 'b Mpz.tt -> t
```

33.3 Conversions

```
val to_string : 'a tt -> string
val to_float : 'a tt -> float
val to_mpzf2 : 'a tt -> Mpzf.t * Mpzf.t
```

33.4 Arithmetic Functions

```
val add : 'a tt -> 'b tt -> t
val sub : 'a tt -> 'b tt -> t
val mul : 'a tt -> 'b tt -> t
val div : 'a tt -> 'b tt -> t
val neg : 'a tt -> t
val abs : 'a tt -> t
val inv : 'a tt -> t
val equal : 'a tt -> 'b tt -> bool
```

33.5 Comparison Functions

```
val cmp : 'a tt -> 'b tt -> int
val cmp_int : 'a tt -> int -> int
val cmp_frac : 'a tt -> int -> int -> int
val sgn : 'a tt -> int
```

33.6 Extraction Functions

```
val get_num : t -> Mpzf.t
val get_den : t -> Mpzf.t
```

Chapter 34

Module Mpfrf : MPFR multi-precision floating-point version, functional version

Functions in this module has a functional semantics, unlike the corresponding functions in Mpfr[30]. These functions do not return the rounding information and are less efficient, due to the additional memory allocation needed for the result.

type 'a tt = 'a Mpfr.tt

type t = Mpfr.f tt

multi-precision floating-point numbers

val to_mpfr : t -> 'a Mpfr.tt

val of_mpfr : 'a Mpfr.tt -> t

Safe conversion from and to Mpfr.t.

There is no sharing between the argument and the result.

val _mpfr : t -> Mpfr.t

val _mpfrf : Mpfr.t -> t

Unsafe conversion from and to Mpfr.t.

The argument and the result actually share the same number: be cautious !

Conversion from and to Mpz.t, Mpq.t and Mpfr.t There is no sharing between the argument and the result.

Conversion from and to Mpz.t, Mpq.t and Mpfr.t There is no sharing between the argument and the result.

34.1 Pretty-printing

val print : Format.formatter -> t -> unit

34.2 Constructors

val of_string : string -> Mpfr.round -> t

val of_float : float -> Mpfr.round -> t

```
val of_int : int -> Mpfr.round -> t
val of_frac : int -> int -> Mpfr.round -> t
val of_mpz : 'a Mpz.tt -> Mpfr.round -> t
val of_mpz2 : 'a Mpz.tt -> 'b Mpz.tt -> Mpfr.round -> t
val of_mpq : 'a Mpq.tt -> Mpfr.round -> t
```

34.3 Conversions

```
val to_string : t -> string
val to_float : ?round:Mpfr.round -> t -> float
val to_mpqf : t -> Mpqf.t
```

34.4 Arithmetic Functions

```
val add : 'a tt -> 'b tt -> Mpfr.round -> t
val add_int : 'a tt -> int -> Mpfr.round -> t
val sub : 'a tt -> 'b tt -> Mpfr.round -> t
val sub_int : 'a tt -> int -> Mpfr.round -> t
val mul : 'a tt -> 'b tt -> Mpfr.round -> t
val mul_ui : 'a tt -> int -> Mpfr.round -> t
val ui_div : int -> 'b tt -> Mpfr.round -> t
val div : 'a tt -> 'b tt -> Mpfr.round -> t
val div_ui : 'a tt -> int -> Mpfr.round -> t
val sqrt : 'a tt -> Mpfr.round -> t
val ui_pow : int -> 'b tt -> Mpfr.round -> t
val pow : 'a tt -> 'b tt -> Mpfr.round -> t
val pow_int : 'a tt -> int -> Mpfr.round -> t
val neg : 'a tt -> Mpfr.round -> t
val abs : 'a tt -> Mpfr.round -> t
```

34.5 Comparison Functions

```
val equal : 'a tt -> 'b tt -> bits:int -> bool
val cmp : 'a tt -> 'b tt -> int
val cmp_int : 'a tt -> int -> int
val sgn : 'a tt -> int
val nan_p : 'a tt -> bool
val inf_p : 'a tt -> bool
val number_p : 'a tt -> bool
```

Index

_equal, 119, 125
_export, 113
_gcdext, 111
_get_str, 108, 115, 118, 123
_import, 113
_init_set_str, 108, 118, 123
_mpfr, 134
_mpfrf, 134
_mpq, 132
_mpqf, 132
_mpz, 130
_mpzf, 130
_powm, 111
_powm_ui, 111
_set_str, 108, 114, 118, 123
_sqrtrem, 111
_strtofr, 123

abs, 109, 115, 119, 124, 131, 133, 135
Abstract0, 43, 47, 50, 54, 58, 99
abstract0, 78
Abstract1, 44, 47, 51, 55, 58, 77
acos, 125
acosh, 125
add, 62, 109, 115, 119, 124, 131, 133, 135
add_dimensions, 103
add_dimensions_with, 103
add_epsilon, 46
add_epsilon_bin, 47
add_int, 131, 135
add_q, 124
add_ray_array, 80, 102
add_ray_array_with, 80, 102
add_ui, 109, 119, 124
add_z, 124
addmul, 109
addmul_ui, 109
agm, 126
apply_dimchange2, 103
apply_dimchange2_with, 103
approximate, 77, 99
array_extend_environment, 68, 70, 76
array_extend_environment_with, 68, 70, 76
array_get, 68, 70, 76
array_get_env, 68, 76
array_length, 68, 70, 76
array_make, 68, 70, 76

array_print, 68, 70, 76
array_set, 68, 70, 76
asin, 125
asinh, 125
assign_linexpr, 83, 104
assign_linexpr_array, 80, 102
assign_linexpr_array_with, 81, 102
assign_linexpr_with, 83, 104
assign_texpr, 83, 104
assign_texpr_array, 80, 102
assign_texpr_array_with, 81, 103
assign_texpr_with, 83, 105
atan, 125
atan2, 125
atanh, 125

bin_ui, 111
bin_uui, 111
binop, 72, 73, 95, 96
bottom, 36, 78, 100
bound_dimension, 101
bound_linexpr, 79, 101
bound_texpr, 79, 101
bound_variable, 79
Box, 43
box1, 77

canonicalize, 77, 99, 114
cdiv_q, 109, 131
cdiv_q_2exp, 110
cdiv_q_ui, 109
cdiv_qr, 109, 131
cdiv_qr_ui, 110
cdiv_r, 109, 131
cdiv_r_2exp, 110
cdiv_r_ui, 110
cdiv_ui, 110
ceil, 120, 126
change, 89
change_add_invert, 90
change_environment, 81
change_environment_with, 82
change2, 89
check_range, 122
clear_flags, 122
clear_inexflag, 122
clear_nanflag, 122

clear_overflow, 122
 clear_underflow, 122
 closure, 82, 104
 closure_with, 82, 104
 clrbit, 112
 cmp, 34, 36, 38, 112, 116, 119, 125, 131, 133, 135
 cmp_d, 112, 119
 cmp_frac, 133
 cmp_int, 34, 131, 133, 135
 cmp_si, 112, 116, 119, 125
 cmp_si_2exp, 125
 cmpabs, 112
 cmpabs_d, 112
 cmpabs_ui, 112
 Coeff, 37
 com, 112
 compare, 61, 63, 91
 compose, 57
 congruent_2exp_p, 110
 congruent_p, 110
 congruent_ui_p, 110
 const_catalan, 126
 const_euler, 126
 const_log2, 126
 const_pi, 126
 copy, 64, 66, 69, 73, 75, 77, 91, 93, 94, 96, 98, 99
 cos, 125
 cosh, 125
 cot, 125
 coth, 125
 csc, 125
 csch, 125
 cst, 73, 96

 decompose, 57
 Dim, 89
 dim, 96
 dim_of_var, 63
 dimchange, 63
 dimchange2, 63
 dimension, 63, 89, 100
 div, 115, 119, 124, 133, 135
 div_2exp, 115, 119, 124
 div_2si, 124
 div_2ui, 124
 div_q, 124
 div_ui, 119, 124, 135
 div_z, 124
 divexact, 110, 131
 divexact_ui, 110
 divisible_2exp_p, 110
 divisible_p, 110
 divisible_ui_p, 110

 earray, 66, 69, 75
 eint, 126

 env, 78
 Environment, 62
 equal, 34, 36, 38, 63, 116, 119, 125, 133, 135
 equal_int, 34, 36, 38
 equalities, 49
 erf, 126
 erfc, 126
 Error, 42, 86
 even_p, 113
 exc, 41
 exclog, 41
 exp, 125
 exp10, 125
 exp2, 125
 expand, 82, 103
 expand_with, 82, 104
 expm1, 126
 export, 113
 expr, 73, 96
 extend_environment, 65, 67, 70, 73, 76
 extend_environment_with, 65, 67, 70, 73, 76

 f, 107, 114, 117, 121
 fac_ui, 111, 125
 fdiv_q, 110, 131
 fdiv_q_2exp, 110
 fdiv_q_ui, 110
 fdiv_qr, 110, 131
 fdiv_qr_ui, 110
 fdiv_r, 110, 131
 fdiv_r_2exp, 110
 fdiv_r_ui, 110
 fdiv_ui, 110
 fdump, 78, 100
 fib_ui, 111
 fib2_ui, 111
 fits_int_p, 113, 120
 fits_sint_p, 113, 120
 fits_slong_p, 113, 120
 fits_sshort_p, 113, 120
 fits_uint_p, 113, 120
 fits_ulong_p, 113, 120
 fits_ushort_p, 113, 120
 floor, 120, 126
 fma, 126
 fmod, 126
 fms, 126
 fold, 82, 103
 fold_with, 82, 104
 forget_array, 81, 103
 forget_array_with, 81, 103
 frac, 126
 funid, 41
 funopt, 41
 funopt_make, 42

gamma, 126
 gand, 112
 gcd, 111, 131
 gcd_ui, 111
 gcdext, 111
 Generator0, 94
 Generator1, 69
 generator1_of_lexbuf, 86
 generator1_of_lstring, 87
 generator1_of_string, 86
 get_approximate_max_coeff_size, 50
 get_coeff, 65, 67, 70, 91
 get_cst, 64, 67, 91
 get_d, 108, 115, 118, 123
 get_d_2exp, 108, 118
 get_d1, 123
 get_default_prec, 117, 122
 get_default_rounding_mode, 122
 get_den, 116, 133
 get_deserialize, 42
 get_emax, 122
 get_emin, 122
 get_env, 65, 67, 71, 74, 76
 get_exp, 127
 get_flag_best, 42
 get_flag_exact, 42
 get_funopt, 42
 get_generator0, 71
 get_int, 108, 118
 get_library, 41
 get_lincons0, 67
 get_linexpr0, 65
 get_linexpr1, 67, 71
 get_max_coeff_size, 50
 get_num, 116, 133
 get_prec, 117, 122
 get_q, 118
 get_si, 108, 118
 get_size, 91
 get_str, 108, 115, 118, 123
 get_tcons0, 76
 get_texpr0, 73
 get_texpr1, 76
 get_typ, 66, 69, 75
 get_version, 41
 get_z, 115, 118, 123
 get_z_exp, 123
 gmod, 110, 131
 gmod_ui, 110
 Gmp_random, 128
 grid, 53

 hamdist, 112
 hash, 61, 63, 77, 91, 99
 hypot, 126

i_of_float, 37
 i_of_frac, 37
 i_of_int, 37
 i_of_mpfr, 37
 i_of_mpq, 37
 i_of_mpqf, 37
 i_of_scalar, 37
 import, 113
 inexflag_p, 122
 inf_p, 125, 135
 init, 107, 114, 117, 122
 init_default, 128
 init_lc_2exp, 128
 init_lc_2exp_size, 128
 init_set, 108, 115, 118, 123
 init_set_d, 108, 115, 118, 123
 init_set_f, 123
 init_set_q, 123
 init_set_si, 108, 115, 118, 123
 init_set_str, 108, 115, 118, 123
 init_set_z, 115, 123
 init2, 107, 117, 122
 integer_p, 120, 126
 internal, 46, 49
 Interval, 35
 Introduction, 5
 inv, 115, 133
 invert, 111
 ior, 112
 is_bottom, 35, 79, 100
 is_box, 43, 44
 is_dimension_unconstrained, 101
 is_eq, 79, 100
 is_infty, 33
 is_integer, 65, 119
 is_interval, 38
 is_interval_cst, 73, 96
 is_interval_linear, 73, 96
 is_interval_polyfrac, 73, 96
 is_interval_polynomial, 73, 96
 is_leq, 35, 79, 100
 is_oct, 47
 is_polka, 50, 51
 is_polka_equalities, 50, 51
 is_polka_loose, 50, 51
 is_polka_strict, 50, 51
 is_polkagrid, 58
 is_ppl, 54, 55
 is_ppl_grid, 54, 55
 is_ppl_loose, 54, 55
 is_ppl_strict, 54, 55
 is_real, 65
 is_scalar, 38, 73, 96
 is_top, 35, 79, 100
 is_unsat, 67
 is_variable_unconstrained, 79

is_zero, 36, 38
 iter, 64, 66, 69, 92
 j0, 126
 j1, 126
 jacobi, 111
 jn, 126
 join, 80, 101
 join_array, 80, 102
 join_with, 80, 102
 kronecker, 111
 kronecker_si, 111
 lce, 62
 lce_change, 62
 lcm, 111, 131
 lcm_ui, 111
 legendre, 111
 Lincons0, 93
 Lincons1, 66
 lincons1_of_lexbuf, 86
 lincons1_of_lstring, 87
 lincons1_of_string, 86
 Linexpr0, 91
 Linexpr1, 64
 linexpr1_of_lexbuf, 86
 linexpr1_of_string, 86
 {lngamma, 126
 log, 125
 log10, 125
 log1p, 125
 log2, 125
 loose, 49, 53
 lucnum_ui, 111
 lucnum2_ui, 111
 m, 107, 114, 117, 121
 make, 62, 64, 66, 69, 75, 91, 93, 94, 98
 make_unsat, 67
 Manager, 40
 manager, 78, 100
 manager_alloc, 43, 46, 57
 manager_alloc_equalities, 50
 manager_alloc_grid, 53
 manager_alloc_loose, 49, 53
 manager_alloc_strict, 49, 53
 manager_decompose, 57
 manager_get_internal, 46, 50
 manager_is_box, 43
 manager_is_oct, 47
 manager_is_polka, 50
 manager_is_polka_equalities, 50
 manager_is_polka_loose, 50
 manager_is_polka_strict, 50
 manager_is_polkagrid, 57

manager_is_ppl, 54
 manager_is_ppl_grid, 54
 manager_is_ppl_loose, 54
 manager_is_ppl_strict, 54
 manager_of_box, 43
 manager_of_oct, 47
 manager_of_polka, 50
 manager_of_polka_equalities, 50
 manager_of_polka_loose, 50
 manager_of_polka_strict, 50
 manager_of_polkagrid, 57
 manager_of_ppl, 54
 manager_of_ppl_grid, 54
 manager_of_ppl_loose, 54
 manager_of_ppl_strict, 54
 manager_to_box, 43
 manager_to_oct, 47
 manager_to_polka, 50
 manager_to_polka_equalities, 50
 manager_to_polka_loose, 50
 manager_to_polka_strict, 50
 manager_to_polkagrid, 58
 manager_to_ppl, 54
 manager_to_ppl_grid, 54
 manager_to_ppl_loose, 54
 manager_to_ppl_strict, 54
 max, 127
 meet, 80, 101
 meet_array, 80, 101
 meet_lincons_array, 80, 101
 meet_lincons_array_with, 80, 102
 meet_tcons_array, 80, 101
 meet_tcons_array_with, 80, 102
 meet_with, 80, 102
 mem_var, 63
 min, 126
 minimize, 64, 77, 91, 99
 minimize_environment, 81
 minimize_environment_with, 82
 modf, 126
 Mpfr, 117, 129
 Mpfrf, 121, 129
 Mpq, 114
 Mpqf, 132
 Mpz, 107, 128
 Mpzf, 130
 mul, 109, 115, 119, 124, 131, 133, 135
 mul_2exp, 109, 115, 119, 124
 mul_2si, 124
 mul_2ui, 124
 mul_int, 131
 mul_q, 124
 mul_si, 109
 mul_ui, 119, 124, 135
 mul_z, 124

| | |
|---|--|
| nan_p, 125, 135 | Polka, 49 |
| nanflag_p, 122 | PolkaGrid, 57 |
| narrowing, 46 | popcount, 112 |
| neg, 34, 36, 38, 109, 115, 119, 124, 131, 133, 135 | pow, 124, 135 |
| nextabove, 126 | pow_int, 135 |
| nextbelow, 126 | pow_si, 124 |
| nextprime, 111 | pow_ui, 111, 119, 124 |
| nexttoward, 126 | powm, 111 |
| number_p, 125, 135 | powm_ui, 111 |
| Oct, 46 | Ppl, 53 |
| odd_p, 113 | pre_widening, 47 |
| of_array, 91 | print, 34, 36, 38, 44, 61, 63, 64, 66, 69, 74, 75, |
| of_box, 43, 44, 78, 100 | 78, 92–94, 97, 98, 100, 107, 114, 117, 121, |
| of_expr, 73, 96 | 130, 132, 134 |
| of_float, 33, 35, 108, 115, 118, 124, 130, 132, 134 | print_array, 105 |
| of_frac, 33, 35, 115, 124, 132, 135 | print_binop, 74, 97 |
| of_generator_array, 46 | print_exc, 42 |
| of_infsup, 35 | print_exclog, 42 |
| of_infty, 33 | print_expr, 74, 97 |
| of_int, 33, 35, 108, 115, 119, 124, 130, 132, 135 | print_funid, 42 |
| of_lincons_array, 83, 104 | print_funopt, 42 |
| of_linexpr, 73, 96 | print_precedence_of_binop, 97 |
| of_list, 91 | print_precedence_of_unop, 97 |
| of_lstring, 87 | print_round, 74, 97, 122 |
| of_mpfr, 33, 35, 134 | print_sprint_binop, 97 |
| of_mpfrf, 33 | print_sprint_unop, 97 |
| of_mpq, 33, 35, 119, 124, 132, 135 | print_typ, 74, 97 |
| of_mpqf, 33, 35 | print_unop, 74, 96 |
| of_mpz, 115, 119, 124, 130, 132, 135 | print0, 44 |
| of_mpz2, 115, 124, 132, 135 | print1, 44 |
| of_oct, 47 | probab_prime_p, 111 |
| of_polka, 50, 51 | realloc2, 107 |
| of_polka_equalities, 50, 51 | reduce, 38 |
| of_polka_loose, 50, 51 | reldiff, 119, 125 |
| of_polka_strict, 50, 51 | remainder, 126 |
| of_polkagrid, 58 | remove, 62, 111 |
| of_ppl, 54, 55 | remove_dimensions, 103 |
| of_ppl_grid, 54, 55 | remove_dimensions_with, 103 |
| of_ppl_loose, 54, 55 | rename, 62 |
| of_ppl_strict, 54, 55 | rename_array, 81 |
| of_scalar, 35 | rename_array_with, 82 |
| of_string, 61, 108, 115, 118, 124, 130, 132, 134 | rename_perm, 62 |
| of_tcons_array, 83, 104 | rint, 126 |
| overflow_p, 122 | root, 111 |
| Parser, 84 | round, 72, 96, 121, 126 |
| perfect_power_p, 111 | round_prec, 122 |
| perfect_square_p, 111 | rrandomb, 129 |
| perm, 89 | s_of_float, 37 |
| perm_compose, 90 | s_of_frac, 37 |
| perm_invert, 90 | s_of_int, 37 |
| permute_dimensions, 103 | s_of_mpfr, 37 |
| permute_dimensions_with, 103 | s_of_mpq, 37 |
| Policy, 44 | s_of_mpqf, 37 |
| policy_manager_alloc, 44 | sat_interval, 79, 101 |

sat_lincons, 79, 100
 sat_tcons, 79, 100
 Scalar, 33
 scan0, 112
 scan1, 112
 sec, 125
 sech, 125
 seed, 128
 seed_ui, 128
 set, 108, 114, 118, 122
 set_approximate_max_coeff_size, 50
 set_array, 64, 67, 70, 92
 set_bottom, 36
 set_coeff, 65, 67, 70, 92
 set_cst, 64, 67, 92
 set_d, 108, 115, 118, 122
 set_default_prec, 117, 122
 set_default_rounding_mode, 122
 set_den, 116
 set_deserialize, 42
 set_emax, 122
 set_emin, 122
 set_exp, 127
 set_f, 123
 set_funopt, 42
 set_gc, 99
 set_inf, 123
 set_infsup, 36
 set_list, 64, 67, 70, 91
 set_max_coeff_size, 50
 set_nan, 123
 set_num, 116
 set_prec, 118, 122
 set_prec_raw, 118, 122
 set_q, 118, 123
 set_si, 108, 114, 118, 122
 set_si_2exp, 123
 set_str, 108, 114, 118, 123
 set_top, 36
 set_typ, 67, 69, 75
 set_var_operations, 61
 set_z, 114, 118, 123
 setbit, 112
 sgn, 34, 112, 116, 119, 125, 131, 133, 135
 si_kronecker, 111
 sin, 125
 sin_cos, 125
 sinh, 125
 size, 63, 77, 99, 113
 sizeinbase, 113
 sqrt, 111, 119, 124, 135
 sqrt_ui, 124
 sqrtrem, 111
 state, 128
 strict, 49, 53
 string_of_binop, 74, 96

string_of_exc, 42
 string_of_funid, 42
 string_of_round, 74, 96, 122
 string_of_typ, 66, 74, 75, 93, 94, 96, 98
 string_of_unop, 74, 96
 strtofr, 123
 sub, 109, 115, 119, 124, 131, 133, 135
 sub_int, 131, 135
 sub_q, 124
 sub_ui, 109, 119, 124
 sub_z, 124
 submul, 109
 submul_ui, 109
 substitute_linexpr, 83, 104
 substitute_linexpr_array, 80, 102
 substitute_linexpr_array_with, 81, 102
 substitute_linexpr_with, 83, 105
 substitute_texpr, 83, 104
 substitute_texpr_array, 81, 102
 substitute_texpr_array_with, 81, 103
 substitute_texpr_with, 83, 105
 swap, 108, 114, 118, 123

 t, 33, 35, 37, 41, 43, 46, 49, 53, 57, 61, 62, 64, 66,
 69, 72, 75, 77, 89, 91, 93–95, 98, 99, 107,
 114, 117, 121, 130, 132, 134

 tan, 125
 tanh, 125
 Tcons0, 98
 Tcons1, 75
 tcons1_of_lexbuf, 86
 tcons1_of_lstring, 87
 tcons1_of_string, 86
 tdiv_q, 110, 131
 tdiv_q_2exp, 110
 tdiv_q_ui, 110
 tdiv_qr, 110, 131
 tdiv_qr_ui, 110
 tdiv_r, 110, 131
 tdiv_r_2exp, 110
 tdiv_r_ui, 110
 tdiv_ui, 110
 Texpr0, 95
 Texpr1, 72
 texpr1_of_lexbuf, 86
 texpr1_of_string, 86
 texpr1expr_of_lexbuf, 86
 texpr1expr_of_string, 86
 to_box, 43, 44, 79, 101
 to_expr, 73, 96
 to_float, 108, 115, 118, 123, 130, 133, 135
 to_generator_array, 79, 101
 to_lincons_array, 79, 101
 to_mpfr, 134
 to_mpq, 123, 132
 to_mpqf, 135

`to_mpz`, 130
`to_mpzf2`, 133
`to_oct`, 47
`to_polka`, 51
`to_polka_equalities`, 51
`to_polka_loose`, 51
`to_polka_strict`, 51
`to_polkagrid`, 58
`to_ppl`, 54, 55
`to_ppl_grid`, 54, 55
`to_ppl_loose`, 54, 55
`to_ppl_strict`, 54, 55
`to_string`, 34, 61, 108, 115, 118, 123, 130, 133, 135
`to_tcons_array`, 79, 101
`top`, 36, 78, 100
`trunc`, 120, 126
`tstbit`, 112
`tt`, 107, 114, 117, 121, 130, 132, 134
`typ`, 66, 69, 72, 75, 93–95, 98
`typ_of_var`, 63
`typvar`, 62

`ui_div`, 119, 124, 135
`ui_pow`, 124, 135
`ui_pow_ui`, 111, 124
`ui_sub`, 109, 119, 124
`underflow_p`, 122
`unify`, 83
`unify_with`, 83
`union_5`, 37
`unop`, 72, 73, 95, 96
`urandom`, 129
`urandomb`, 128, 129
`urandomm`, 129

`Var`, 61
`var`, 73
`var_of_dim`, 63
`vars`, 63

`widening`, 82, 104
`widening_threshold`, 82, 104
`widening_thresholds`, 46

`xor`, 112

`y0`, 126
`y1`, 126
`yn`, 126

`zeta`, 126