

Graphics drivers for L^AT_EX 2_ε*

Sebastian Rahtz and David Carlisle

2015/12/30

This file is maintained by the L^AT_EX Project team.
Bug reports can be opened (category **graphics**) at
<http://latex-project.org/bugs.html>.

1 Driver files

This file implements some of the currently supported drivers. If the driver you use is not in this list then a ‘.def’ file may be distributed with This graphics bundle, or may be distributed with your driver.

If not, send us some details of the driver’s `\special` syntax, and we will try to produce a suitable file.

Note that some of these files are for drivers to which we have no access, so they are untested. Please send any corrections to the latexbugs address.

2 Colour

Most of the drivers that support colour use one of three methods.

- color1: ‘dvips’ style colour specials.
- color2: ‘textures’ style colour specials.
- color3: Colour implemented via literal PostScript specials.
- color4: Colour implemented by specials that only support RGB, i.e., Red Green Blue specified as integers in the range 0–255. Other models converted to this within T_EX.

Some drivers do not use any of these modules and have their own code. Note that drivers using the ‘color3’ code can not fully support the L^AT_EX colour commands.

```
1 (*color1 | color2 | color3 | color4)
2 \def\color@arg#1{%
3   \dimen@#1\p@
4   \ifdim\dimen@<\z@\dimen@\maxdimen\fi
5   \ifdim\dimen@>\p@
6     \PackageError{color}{Argument ‘#1’ not in range [0,1]}\@ehd
7   \fi}
```

*Version v3.0k, revised 2015/12/30

Need to make sure of a trailing .0 for textures. Apparently it is OK to always add a . as 1.3. is accepted by textures. textures gray special is reversed, so just use rgb instead.

```

8 \def\color@gray#1#2{%
9   \c@lor@arg{#2}%
10  \color4 \c@lor@rgb@RGB\@tempa
11  \color1 \edef#1{gray #2}%
12  \color2 \edef#1{rgb #2. #2. #2.}%
13  \color3 \edef#1{#2 setgray}%
14  \color4 \edef#1{\@tempa\@tempa\@tempa}%
15  }
16 \def\color@cmyk#1#2{\c@lor@@cmyk#2\@@#1}
17 \def\c@lor@@cmyk#1,#2,#3,#4\@@#5{%
18   \c@lor@arg{#4}%
19  \color4 \dimen@ii#4\p@
20   \c@lor@arg{#1}%
21  \color4 \c@lor@cmyk@RGB\@tempa
22   \c@lor@arg{#2}%
23  \color4 \c@lor@cmyk@RGB\@tempb
24   \c@lor@arg{#3}%
25  \color4 \c@lor@cmyk@RGB\@tempc
26  \color1 \edef#5{cmyk #1 #2 #3 #4}%
27  \color2 \edef#5{cmyk #1. #2. #3. #4.}%
28  \color3 \edef#5{#1 #2 #3 #4 setcmykcolor}%
29  \color4 \edef#5{\@tempa\@tempb\@tempc}%
30  }

```

A 0–1 range value will have been left in \dimen@ by \c@lor@arg. The black value (0–1) will be stored in \dimen@ii. Covert to 0–255 integer, and leave in #1.

```

31 (*color4)
32 \def\c@lor@cmyk@RGB#1{%
33   \advance\dimen@-\p@
34   \advance\dimen@\dimen@ii
35   \dimen@-\@cc1v\dimen@
36   \divide\dimen@\p@
37   \count@\ifdim\dimen@<\z@\z@\else\dimen@\fi
38   \edef#1{\the\count@\space}}
39 \color4
40 \def\color@rgb#1#2{\c@lor@@rgb#2\@@#1}
41 \def\c@lor@@rgb#1,#2,#3\@@#4{%
42   \c@lor@arg{#1}%
43  \color4 \c@lor@rgb@RGB\@tempa
44   \c@lor@arg{#2}%
45  \color4 \c@lor@rgb@RGB\@tempb
46   \c@lor@arg{#3}%
47  \color4 \c@lor@rgb@RGB\@tempc
48  \color1 \edef#4{rgb #1 #2 #3}%
49  \color2 \edef#4{rgb #1. #2. #3.}%
50  \color3 \edef#4{#1 #2 #3 setrgbcolor}%
51  \color4 \edef#4{\@tempa\@tempb\@tempc}%
52  }

```

A 0–1 range value will have been left in \dimen@ by \c@lor@arg. Convert to 0–255 integer, and leave in #1.

```

53 <*color4>
54 \def\color@rgb@RGB#1{%
55   \dimen@ \@cclv\dimen@
56   \count@ \dimen@
57   \divide\count@ \p@
58   \edef#1{\the\count@\space}}
59 </color4>
60 \def\color@RGB#1#2{\color@@RGB#2\@@#1}
61 \def\color@@RGB#1,#2,#3\@@#4{%
62 <!color4> \color@RGB@rgb{#1}\@tempa
63 <!color4> \color@RGB@rgb{#2}\@tempb
64 <!color4> \color@RGB@rgb{#3}\@tempc
65 <!color4> \color@rgb\@tempa,\@tempb,\@tempc\@@#4%
66 <color4> \edef#4{#1 #2 #3}%
67   }

```

Convert 0–255 integer, #1, to 0–1 real, and leave in #2.

```

68 <!*color4>
69 \def\color@RGB@rgb#1#2{%
70   \dimen@#1\p@
71   \divide\dimen@\@cclv
72   \edef#2{\strip@pt\dimen@}}
73 </!color4>
74 <*color1 | color3>
75 \def\color@hsb#1#2{\color@@hsb#2\@@#1}
76 \def\color@@hsb#1,#2,#3\@@#4{%
77   \color@arg{#1}%
78   \color@arg{#2}%
79   \color@arg{#3}%
80 <color1> \edef#4{hsb #1 #2 #3}%
81 <color3> \edef#4{#1 #2 #3 sethsbcolor}%
82   }
83 </color1 | color3>
84 \def\color@named#1#2{\color@@named#2,,\@@#1}
85 \def\color@@named#1,#2,#3\@@#4{%
86   \ifundefined{col@#1}%
87     {\PackageError{color}{Undefined color ‘#1’}\@ehd}%
88 <color1&!dvipsone> {\edef#4{ #1}}%
89 <color2> {\edef#4{ #1 \if!#2!\else #2.\fi}}%
90 <color3 | dvipsone | color4> {\edef#4{\csname col@#1\endcsname}}%
91   }

```

Conversion from \special syntax to PostScript (for PSTricks).

```

92 <*color1 | color2>
93 \def\color@to@ps#1 #2\@@{\csname c@lor@ps@#1\endcsname#2 \@@}
94 </color1 | color2>
95 <*color3>
96 \def\color@to@ps#1\@@{#1}
97 </color3>
98 <*color4>
99 \def\color@to@ps#1#2 #3 #4\@@{%
100   #1#2 255 div #3 255 div #4 255 div setrgbcolor}
101 </color4>

```

```

102 <*color1>
103 \def\color@ps@#1 #2\@{\TeXDict begin #1 end}
104 \def\color@ps@rgb#1\@{\#1 setrgbcolor}
105 \def\color@ps@hsb#1\@{\#1 sethsbcolor}
106 \def\color@ps@cmymk#1\@{\#1 setcmymkcolor}
107 \def\color@ps@gray#1\@{\#1 setgray}
108 </color1>
109 <*color2>
110 \def\color@to@ps@#1 #2\@{\csname color@ps@#1\endcsname#2 \@}
111 \def\color@ps@#1 #2\@{\%
112   \expandafter\expandafter\expandafter
113     \color@to@ps@\csname col@#1\endcsname\space#2. \@{\#1}}
114 \def\color@ps@rgb#1. #2. #3. #4\@{\#1 #2 #3 setrgbcolor}
115 \def\color@ps@rgb@#1. #2. #3. #4. #5\@{\#1 #2 #3 setrgbcolor}
116 \def\color@ps@cmymk#1. #2. #3. #4. #5. #6\@{\#1 #2 #3 #4 setcmymkcolor}
117 \def\color@ps@cmymk@#1. #2. #3. #4. #5. #6\@{\#1 #2 #3 #4 setcmymkcolor}
118   #1 #2 #3 #4 (#7) findcustomcmymkcolor
119   \if!\@firstofone#5!1 \else#5 \fi setcustomcolor}
120 </color2>

121 <color1&!dvipsone>\def\current@color{ Black}
122 <color1 & dvipsone>\def\current@color{gray 0}
123 <color2>\def\current@color{rgb 0. 0. 0.}
124 <color3>\def\current@color{0 setgray}
125 <color4>\def\current@color{0 0 0}

126 <*color1>
127 \def\set@color{\%
128 (!dvipsone&!dvipdf) \special{color push \current@color
129 (dvipsone) \special{color push}\special{color \current@color
130 (dvipdf) \special{pdf: /C \current@color\space<<
131 } \aftergroup\reset@color}
132 \def\reset@color{\special{\%
133 (!dvipdf) color pop}}
134 (dvipdf) pdf: /C >> }}
135 \def\set@page@color{\special{\%
136 (!dvipdf) background \current@color}}
137 (dvipdf) pdf: /BG \current@color}}
138 \def\define@color@named#1#2{\%
139 (!dvipsone) \expandafter\let\csname col@#1\endcsname\@nnil}
140 (dvipsone) \expandafter\edef\csname col@#1\endcsname{\#2}}
141 (dvips) \def\no@page@color{\special{background \string"newpath clip}}
142 </color1>
143 <*color2>
144 \def\set@color{\%
145 \special{color push}\%
146 \special{color \current@color}\%
147 \aftergroup\reset@color}
148 \def\reset@color{\special{color pop}}
149 \def\set@page@color{\color@special\sixt@@n{background \current@color}}
150 \def\define@color@named#1#2{\%
151 \AtBeginDvi{\special{color define #1 #2}}\%
152 \expandafter\edef\csname col@#1\endcsname{\#2}}
153 </color2>
154 <*color3>

```

```

155 \def\set@color{%
156   \Gin@PS@raw{\current@color}\aftergroup\reset@color}
157 \def\reset@color{\Gin@PS@raw{\current@color}}
158 \color3}
159 \color4}
160 \def\set@color{%
161   \special{textcolor: \current@color}\aftergroup\reset@color}
162 \def\reset@color{\special{textcolor: \current@color}}
163 \color4}
164 \color3 | color4}
165 \def\set@page@color{%
166   \c@lor@special\sixt@@n{background color ignored: \current@color}}
167 \def\define@color@named#1#2{%
168   \expandafter\edef\csname col@#1\endcsname{#2}}
169 \color3 | color4}

170 \color1 | color2 | color3 | color4}

171 \colorfix}
172 \AtBeginDocument{%
173   \let\@ldc@l@r\color
174   \def\color{\if@inlabel\leavevmode\fi\@ldc@l@r}%
175   \let\@lduseb@x\usebox
176   \def\usebox#1{\@lduseb@x{#1}\set@color}}
177 \colorfix}

178 \dvipsnames}
179 \DefineNamedColor{named}{GreenYellow} {cmyk}{0.15,0,0.69,0}
180 \DefineNamedColor{named}{Yellow} {cmyk}{0,0,1,0}
181 \DefineNamedColor{named}{Goldenrod} {cmyk}{0,0.10,0.84,0}
182 \DefineNamedColor{named}{Dandelion} {cmyk}{0,0.29,0.84,0}
183 \DefineNamedColor{named}{Apricot} {cmyk}{0,0.32,0.52,0}
184 \DefineNamedColor{named}{Peach} {cmyk}{0,0.50,0.70,0}
185 \DefineNamedColor{named}{Melon} {cmyk}{0,0.46,0.50,0}
186 \DefineNamedColor{named}{YellowOrange} {cmyk}{0,0.42,1,0}
187 \DefineNamedColor{named}{Orange} {cmyk}{0,0.61,0.87,0}
188 \DefineNamedColor{named}{BurntOrange} {cmyk}{0,0.51,1,0}
189 \DefineNamedColor{named}{Bittersweet} {cmyk}{0,0.75,1,0.24}
190 \DefineNamedColor{named}{RedOrange} {cmyk}{0,0.77,0.87,0}
191 \DefineNamedColor{named}{Mahogany} {cmyk}{0,0.85,0.87,0.35}
192 \DefineNamedColor{named}{Maroon} {cmyk}{0,0.87,0.68,0.32}
193 \DefineNamedColor{named}{BrickRed} {cmyk}{0,0.89,0.94,0.28}
194 \DefineNamedColor{named}{Red} {cmyk}{0,1,1,0}
195 \DefineNamedColor{named}{OrangeRed} {cmyk}{0,1,0.50,0}
196 \DefineNamedColor{named}{RubineRed} {cmyk}{0,1,0.13,0}
197 \DefineNamedColor{named}{WildStrawberry} {cmyk}{0,0.96,0.39,0}
198 \DefineNamedColor{named}{Salmon} {cmyk}{0,0.53,0.38,0}
199 \DefineNamedColor{named}{CarnationPink} {cmyk}{0,0.63,0,0}
200 \DefineNamedColor{named}{Magenta} {cmyk}{0,1,0,0}
201 \DefineNamedColor{named}{VioletRed} {cmyk}{0,0.81,0,0}
202 \DefineNamedColor{named}{Rhodamine} {cmyk}{0,0.82,0,0}
203 \DefineNamedColor{named}{Mulberry} {cmyk}{0.34,0.90,0,0.02}
204 \DefineNamedColor{named}{RedViolet} {cmyk}{0.07,0.90,0,0.34}
205 \DefineNamedColor{named}{Fuchsia} {cmyk}{0.47,0.91,0,0.08}
206 \DefineNamedColor{named}{Lavender} {cmyk}{0,0.48,0,0}
207 \DefineNamedColor{named}{Thistle} {cmyk}{0.12,0.59,0,0}

```

```

208 \DefineNamedColor{named}{Orchid} {cmyk}{0.32,0.64,0,0}
209 \DefineNamedColor{named}{DarkOrchid} {cmyk}{0.40,0.80,0.20,0}
210 \DefineNamedColor{named}{Purple} {cmyk}{0.45,0.86,0,0}
211 \DefineNamedColor{named}{Plum} {cmyk}{0.50,1,0,0}
212 \DefineNamedColor{named}{Violet} {cmyk}{0.79,0.88,0,0}
213 \DefineNamedColor{named}{RoyalPurple} {cmyk}{0.75,0.90,0,0}
214 \DefineNamedColor{named}{BlueViolet} {cmyk}{0.86,0.91,0,0.04}
215 \DefineNamedColor{named}{Periwinkle} {cmyk}{0.57,0.55,0,0}
216 \DefineNamedColor{named}{CadetBlue} {cmyk}{0.62,0.57,0.23,0}
217 \DefineNamedColor{named}{CornflowerBlue} {cmyk}{0.65,0.13,0,0}
218 \DefineNamedColor{named}{MidnightBlue} {cmyk}{0.98,0.13,0,0.43}
219 \DefineNamedColor{named}{NavyBlue} {cmyk}{0.94,0.54,0,0}
220 \DefineNamedColor{named}{RoyalBlue} {cmyk}{1,0.50,0,0}
221 \DefineNamedColor{named}{Blue} {cmyk}{1,1,0,0}
222 \DefineNamedColor{named}{Cerulean} {cmyk}{0.94,0.11,0,0}
223 \DefineNamedColor{named}{Cyan} {cmyk}{1,0,0,0}
224 \DefineNamedColor{named}{ProcessBlue} {cmyk}{0.96,0,0,0}
225 \DefineNamedColor{named}{SkyBlue} {cmyk}{0.62,0,0.12,0}
226 \DefineNamedColor{named}{Turquoise} {cmyk}{0.85,0,0.20,0}
227 \DefineNamedColor{named}{TealBlue} {cmyk}{0.86,0,0.34,0.02}
228 \DefineNamedColor{named}{Aquamarine} {cmyk}{0.82,0,0.30,0}
229 \DefineNamedColor{named}{BlueGreen} {cmyk}{0.85,0,0.33,0}
230 \DefineNamedColor{named}{Emerald} {cmyk}{1,0,0.50,0}
231 \DefineNamedColor{named}{JungleGreen} {cmyk}{0.99,0,0.52,0}
232 \DefineNamedColor{named}{SeaGreen} {cmyk}{0.69,0,0.50,0}
233 \DefineNamedColor{named}{Green} {cmyk}{1,0,1,0}
234 \DefineNamedColor{named}{ForestGreen} {cmyk}{0.91,0,0.88,0.12}
235 \DefineNamedColor{named}{PineGreen} {cmyk}{0.92,0,0.59,0.25}
236 \DefineNamedColor{named}{LimeGreen} {cmyk}{0.50,0,1,0}
237 \DefineNamedColor{named}{YellowGreen} {cmyk}{0.44,0,0.74,0}
238 \DefineNamedColor{named}{SpringGreen} {cmyk}{0.26,0,0.76,0}
239 \DefineNamedColor{named}{OliveGreen} {cmyk}{0.64,0,0.95,0.40}
240 \DefineNamedColor{named}{RawSienna} {cmyk}{0,0.72,1,0.45}
241 \DefineNamedColor{named}{Sepia} {cmyk}{0,0.83,1,0.70}
242 \DefineNamedColor{named}{Brown} {cmyk}{0,0.81,1,0.60}
243 \DefineNamedColor{named}{Tan} {cmyk}{0.14,0.42,0.56,0}
244 \DefineNamedColor{named}{Gray} {cmyk}{0,0,0,0.50}
245 \DefineNamedColor{named}{Black} {cmyk}{0,0,0,1}
246 \DefineNamedColor{named}{White} {cmyk}{0,0,0,0}
247 \end{dvipsnames}

```

3 dvips

A L^AT_EX 2_ε graphics driver file for Tom Rokicki's *dvips* driver; tested with version 5.58f.

```
248 (*dvips)
```

3.1 Colour

Uses the generic ‘color1’ code.

3.2 File inclusion

```

\Gininclude@eps #1 input file (or command)
249 \def\Gininclude@eps#1{%
250 \message{<#1>}%
251 \bgroup

dvips likes to work with its own pixel resolution, so mangle the sizes slightly.

252 \def\@tempa{!}%
253 \dimen@\Gin@req@width
254 \dimen@ii.1bp%
255 \divide\dimen@\dimen@ii
256 \@tempdima\Gin@req@height
257 \divide\@tempdima\dimen@ii
258 \special{PSfile="#1"\space
259 llx=\Gin@llx\space
260 lly=\Gin@lly\space
261 urx=\Gin@urx\space
262 ury=\Gin@ury\space
263 \ifx\Gin@scalex\@tempa\else rwi=\number\dimen@\space\fi
264 \ifx\Gin@scaley\@tempa\else rhi=\number\@tempdima\space\fi
265 \ifGin@clip clip\fi}%
266 \egroup}

\Gininclude@bmp #1 input file; if zero size is requested, the graphic will come at ‘natural’ size.
267 \def\Gininclude@bmp#1{%
268 \message{<#1>}%
269 \dimen@\Gin@req@height
270 \advance\dimen@ by-\Gin@lly bp
271 \kern-\Gin@llx bp\raise\Gin@req@height\hbox{%
272 \ifdim\Gin@urx bp=\z@
273 \ifdim\Gin@ury bp=\z@
274 \special{em: graph #1}%
275 \else
276 \special{em: graph #1,\Gin@urx bp}%
277 \fi
278 \else
279 \special{em: graph #1,\Gin@urx bp,\Gin@ury bp}%
280 \fi
281 }%
282 }

\Gininclude@pict PICT/PNTG format from the Mac. Actually only currently supported by the
\Gininclude@pntg version of dvips distributed with OzTEX, and with the built in OzTEX drivers,
\oztex@include but put here anyway as it is not much code and increases portability between the
systems as now [dvips] and [oztex] share the same back end.

283 \def\oztex@include#1#2{%
284 \dimen@1bp%
285 \divide\Gin@req@width\dimen@
286 \divide\Gin@req@height\dimen@
287 \special{#1=#2\space
288 \@width=\number\Gin@req@width \space
289 \@height=\number\Gin@req@height}}

```

```

290 \def\Gininclude@pntg{\oxtex@include{pntg}}
291 \def\Gininclude@pict{\oxtex@include{pict}}

```

3.3 Rotation

```

292 \def\Grot@start{%
293   \special{ps: gsave currentpoint
294     currentpoint translate \Grot@angle\space neg
295     rotate neg exch neg exch translate}}
296 \def\Grot@end{\special{ps: currentpoint grestore moveto}}

```

3.4 Scaling

```

297 \def\Gscale@start{\special{ps: currentpoint currentpoint translate
298   \Gscale@x\space \Gscale@y\space scale neg exch neg exch translate}}
299 \def\Gscale@end{\special{ps: currentpoint currentpoint translate
300   1 \Gscale@x\space div 1 \Gscale@y\space div scale
301   neg exch neg exch translate}}

```

4 Literal Postscript

Raw PostScript code, no save/restore.

```

302 \def\Gin@PS@raw#1{\special{ps: #1}}

```

PostScript code, to be surrounded by save/restore by the driver. Coordinate system standard PostScript, but with origin at current (T_EX) position.

```

303 \def\Gin@PS@restored#1{\special{" #1}}

```

PostScript code to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```

304 \def\Gin@PS@literal@header#1{\AtBeginDvi{\special{! #1}}}

```

Name of external file, the contents of which are to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```

305 \def\Gin@PS@file@header#1{\AtBeginDvi{\special{header=#1}}}

```

```

306 </dvips>

```

5 dvipdf

A L^AT_EX 2_ε graphics driver file for *dvipdf* driver.

```

307 (*dvipdf)

```

5.1 Colour

Uses the generic ‘color1’ code.

5.2 File inclusion

`\Gininclude@eps` #1 input file (or command)

```

308 \def\Gininclude@eps#1{%
309   \message{<#1>}%
310   \bgroup

```

dvips likes to work with its own pixel resolution, so mangle the sizes slightly.

```

311 \def\@tempa{!}%
312 \dimen@\Gin@req@width
313 \dimen@ii.1bp%
314 \divide\dimen@\dimen@ii
315 \@tempdima\Gin@req@height
316 \divide\@tempdima\dimen@ii
317 \special{PSfile="#1"\space
318     llx=\Gin@llx\space
319     lly=\Gin@lly\space
320     urx=\Gin@urx\space
321     ury=\Gin@ury\space
322     \ifx\Gin@scalex\@tempa\else rwi=\number\dimen@\space\fi
323     \ifx\Gin@scaley\@tempa\else rhi=\number\@tempdima\space\fi
324     \ifGin@clip clip\fi}%
325 \egroup}

```

`\Gininclude@bmp` #1 input file; if zero size is requested, the graphic will come at ‘natural’ size.

```

326 \def\Gininclude@bmp#1{%
327     \message{<#1>}%
328     \dimen@\Gin@req@height
329     \advance\dimen@ by-\Gin@lly bp
330     \kern-\Gin@llx bp\raise\Gin@req@height\hbox{%
331         \ifdim\Gin@urx bp=\z@
332             \ifdim\Gin@ury bp=\z@
333                 \special{pdf: /GRAPH #1}%
334             \else
335                 \special{pdf: /GRAPH #1 \number\Gin@req@width sp}%
336             \fi
337         \else
338             \special{pdf: /GRAPH #1 \number\Gin@req@width sp
339                 \number\Gin@req@height sp}%
340     \fi}}

```

5.3 Rotation

```

341 \def\Grot@start{%
342     \special{pdf: /ROT \Grot@angle\space << }}
343 \def\Grot@end{\special{pdf: /ROT >> }}

```

5.4 Scaling

```

344 \def\Gscale@start{\special{pdf: /S \Gscale@x\space \Gscale@y\space << }}
345 \def\Gscale@end{\special{pdf: /S \space >> }}

```

6 Literal Postscript

Raw PostScript code, no save/restore.

```

346 \def\Gin@PS@raw#1{\special{ps: #1}}

```

PostScript code, to be surrounded by save/restore by the driver. Coordinate system standard PostScript, but with origin at current (T_EX) position.

```

347 \def\Gin@PS@restored#1{\special{" #1}}

```

PostScript code to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```
348 \def\Gin@PS@literal@header#1{\AtBeginDvi{\special{! #1}}}
```

Name of external file, the contents of which are to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```
349 \def\Gin@PS@file@header#1{\AtBeginDvi{\special{header=#1}}}
```

6.1 File extensions

```
350 \@namedef{Gin@rule@.msp}#1{{bmp}}{.bb}{#1}}
351 \@namedef{Gin@rule@.jpg}#1{{bmp}}{.bb}{#1}}
352 \@namedef{Gin@rule@.bmp}#1{{bmp}}{.bb}{#1}}
353 </dvipdf>
```

7 OzTeX

A L^AT_EX 2_ε graphics driver file for OzTeX (versions 1.42 and later), by Andrew Trevorrow.

```
354 <{*oztex}>
```

7.1 Graphics inclusion

```
355 \def\Gininclude@eps{\Oztex@Include{epsf}}
356 \def\Gininclude@pntg{\Oztex@Include{pntg}}
357 \def\Gininclude@pict{\Oztex@Include{pict}}
358 \def\Oztex@Include#1#2{%
359   \ifGin@clip
360     \typeout{No clipping support in OzTeX}%
361   \fi
362   \divide\Gin@req@width by 65781% convert sp to bp
363   \divide\Gin@req@height by 65781%
364   \special{#1=#2\space
365     width=\number\Gin@req@width \space
366     height=\number\Gin@req@height
367   }%
368 }
369 </oztex>
```

8 Textures

A L^AT_EX 2_ε graphics driver file for Blue Sky's Textures

WARNING! There is ongoing work to produce a new version of the textures support. Do not rely on anything in this file being in the next version!

```
370 <{*textures}>
```

8.1 Graphics inclusion

```
371 \PackageInfo{graphics/color}
372 {This file uses the advanced color support\MessageBreak
373   available in textures1.7\MessageBreak
```

```

374 If you are using color with an earlier version\MessageBreak
375 of textures, edit graphics.ins where marked,\MessageBreak
376 and re-latex graphics.ins.\MessageBreak\MessageBreak
377 If you are using textures1.7\MessageBreak
378 you may want to delete this warning\MessageBreak
379 from textures.def.\MessageBreak\MessageBreak
380 The code for scaling/rotation and file inclusion\MessageBreak
381 in this file is still rudimentary, and does not\MessageBreak
382 use textures' full capabilities.\MessageBreak\MessageBreak
383 A new textures.def is currently being developed\@gobble}

384 \def\Gininclude@eps{\Textures@Include{illustration}}
385 \def\Gininclude@pict{\Textures@Include{pictfile}}
386 \def\Textures@Include#1#2{%
387   \def\@tempa{!}%
388   \ifx\Gin@scaley\@tempa
389     \let\Gin@scaley\Gin@scalex
390   \else
391     \ifx\Gin@scalex\@tempa\let\Gin@scalex\Gin@scaley\fi
392   \fi
393   \setlength\@tempdima{\Gin@scalex pt}%
394   \setlength\@tempdimb{\Gin@scaley pt}%
395   \ifdim\@tempdima>\@tempdimb
396     \let\Gin@scalex\Gin@scaley
397   \fi
398   \ifGin@clip
399     \typeout{no clipping support in Textures}%
400   \fi
401   \@tempdimb=1000sp%
402   \setlength\@tempdima{\Gin@scalex\@tempdimb}%
403   \special{#1 #2\space scaled \number\@tempdima}%
404 }

```

8.2 Rotation

This code was written when no unprotected postscript code was allowed; it could almost certainly be rewritten now with ‘rawpostscript’.

```

405 \def\Grot@start{\special{postscript
406   0 0 transform
407   grestore
408   matrix currentmatrix
409   3 1 roll
410   itransform
411   dup 3 -1 roll
412   dup 4 1 roll exch
413   translate
414   \Grot@angle\space neg rotate
415   neg exch neg exch translate
416   gsave}}
417 \def\Grot@end{\special{postscript grestore setmatrix gsave}}

```

8.3 Colour

This will only work for versions 1.6 and Version 1.7 uses ‘color2’.

```

418 \color3\def\Gin@PS@raw#1{\special{rawpostscript #1}}
419 \textures

```

9 dvialw

A L^AT_EX 2_ε graphics driver file for dvialw, by Nelson Beebe

```

420 \*dvialw

```

9.1 Rotation

```

421 \def\Gininclude@eps#1{%
422   \def\@tempa{!}%
423   \ifx\Gin@scaley\@tempa
424     \let\Gin@scaley\Gin@scalex
425   \else
426     \ifx\Gin@scalex\@tempa\let\Gin@scalex\Gin@scaley\fi
427   \fi
428   \ifGin@clip
429     \typeout{no clipping support in dvialw}%
430   \fi
431   \special{language "PS",
432     literal "\Gin@scalex\space
433       \Gin@scaley\space scale",
434     position = "bottom left",
435     include "#1\space"}%
436 }
437 \end{dvialw}

```

10 emtex

A L^AT_EX 2_ε graphics driver file for Eberhard Mattes' emTeX

```

438 \*emtex

```

10.1 Graphics file inclusion

```

439 \def\Gininclude@bmp#1{%
440   \raise\Gin@req@height\hbox{\special{em:graph #1}}%
441   \typeout{WARNING: emtex does not permit graphics to be scaled}%
442 }
443 \end{emtex}

```

11 dvilaser/ps

A L^AT_EX 2_ε graphics driver file for Arbortext's dvilaser/ps

```

444 \*dvilaser

```

11.1 Graphic file inclusion

```

445 \def\Gininclude@eps#1{%
446   \ifGin@clip
447     \typeout{no clipping support in dvilaser/ps}%
448   \fi

```

```

449 \special{ps: epsfile #1\space \the\Gin@req@width}%
450 }
451 </dvlaser>

```

12 psprint

A L^AT_EX 2_ε graphics driver file for Trevorrow's psprint

```

452 (*psprint)

```

12.1 Graphic file inclusion

```

453 \def\Gininclude@eps#1{%
454   \def\@tempa{!}%
455   \ifx\Gin@scaley\@tempa
456     \let\Gin@scaley\Gin@scalex
457   \else
458     \ifx\Gin@scalex\@tempa\let\Gin@scalex\Gin@scaley\fi
459   \fi
460   \ifGin@clip
461     \typeout{no clipping support in psprint}%
462   \fi
463   \special{#1\space
464     \Gin@scalex\space \Gin@scaley\space scale
465     \Gin@llx\space neg
466     \Gin@lly \space neg translate
467 }%
468 }
469 </psprint>

```

13 dvipsone

A L^AT_EX 2_ε graphics driver file for Y&Y's dvipsone

```

470 (*dvipsone)

```

13.1 Graphic file inclusion

PostScript Files.

```

471 \def\Gininclude@eps#1{%
472   \message{<#1>}%
473   \bgroup
474   \def\@tempa{!}%
475   \dimen@\Gin@req@width
476   \dimen@ii.1bp%
477   \divide\dimen@\dimen@ii
478   \@tempdima\Gin@req@height
479   \divide\@tempdima\dimen@ii
480   \special{PSfile="#1"\space
481     llx=\Gin@llx\space
482     lly=\Gin@lly\space
483     urx=\Gin@urx\space
484     ury=\Gin@ury\space
485     \ifx\Gin@scalex\@tempa\else rwi=\number\dimen@\space\fi
486     \ifx\Gin@scaley\@tempa\else rhi=\number\@tempdima\space\fi

```

```

487     \ifGin@clip clip\fi}%
488 \egroup}

Tiff files.

489 \def\Gininclude@tiff#1{%
490 \message{<#1>}%
491 \special{insertimage: #1 \number\Gin@req@width\space
492     \number\Gin@req@height}}

Windows Metafiles.

493 \def\Gininclude@wmf#1{%
494 \message{<#1>}%
495 \special{insertmf: #1 0 0 \number\Gin@req@width\space
496     \number\Gin@req@height}}

497 \def\Gin@PS@raw#1{\special{ps: #1}}

```

13.2 Rotation

```

498 \def\Grot@start{%
499 \special{ps: gsave currentpoint
500 currentpoint translate \Grot@angle\space
501 rotate neg exch neg exch translate}}
502 \def\Grot@end{%
503 \special{ps: currentfont currentpoint grestore moveto setfont}}

```

13.3 Scaling

```

504 \def\Gscale@start{\special{ps: currentpoint currentpoint translate
505 \Gscale@x\space \Gscale@y\space scale neg exch neg exch translate}}
506 \def\Gscale@end{\special{ps: currentpoint currentpoint translate
507 1 \Gscale@x\space div 1 \Gscale@y\space div scale
508 neg exch neg exch translate}}

```

13.4 File Extensions

```

509 \@namedef{Gin@rule@.wmf}#1{{wmf}}{#1}}
510 \@namedef{Gin@rule@.clp}#1{{wmf}}{#1}}

```

14 Literal Postscript

Raw PostScript code, no save/restore.

```
511 \def\Gin@PS@raw#1{\special{ps: #1}}
```

PostScript code, to be surrounded by save/restore by the driver. Coordinate system standard PostScript, but with origin at current (TeX) position.

```
512 \def\Gin@PS@restored#1{\special{" #1}}
```

PostScript code to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```
513 \def\Gin@PS@literal@header#1{\AtBeginDvi{\special{headertext=#1}}}
```

Name of external file, the contents of which are to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```
514 \def\Gin@PS@file@header#1{\AtBeginDvi{\special{header=#1}}}
```

```
515 \end{dvipsone}
```

15 dviwindo

A \LaTeX 2 ϵ graphics driver file for Y&Y's dviwindo.

This driver now uses the same file as dvipsone.

16 dvitops

A \LaTeX 2 ϵ graphics driver file for James Clark's dvitops

516 \langle *dvitops \rangle

16.1 Rotation

```
517 \newcount\Grot@count
518 \Grot@count=\@ne
519 \def\Grot@start{\special{dvitops: origin
520   rot\the\@tempdima}%
521 \special{dvitops: begin rot\the\Grot@count}}%
522 \def\Grot@end{\special{dvitops: end}%
523 \special{dvitops: rotate rot\the\Grot@count \space
524   \Grot@angle}%
525 \global\advance\Grot@count by\@ne}%
```

16.2 Graphic file inclusion

```
526 \def\Gininclude@eps#1{%
527 % These cause an arithmetic overflow, so I've commented them
528 % out. Presumably they were there for some reason.
529 % Any dvitops users out there??
530 % \multiply\Gin@req@width by \@m
531 % \multiply\Gin@req@height by \@m
532 \ifGin@clip
533   \typeout{no clipping support in dvitops}%
534 \fi
535 \special{import #1\space \the\Gin@req@width\space
536   \the\Gin@req@height\space fill}}
537  $\langle$ /dvitops $\rangle$ 
```

17 dvi2ps

A \LaTeX 2 ϵ graphics driver file for original dvi2ps

538 \langle *dvi2ps \rangle

17.1 Graphic file inclusion

```
539 \def\Gininclude@eps#1{%
540   \def\@tempa{!}%
541   \ifx\Gin@scaley\@tempa
542     \let\Gin@scaley\Gin@scalex
543   \else
544     \ifx\Gin@scalex\@tempa\let\Gin@scalex\Gin@scaley\fi
545   \fi
546   \ifGin@clip
```

```

547 \typeout{no clipping support in dvi2ps}%
548 \fi
549 \special{psfile=#1\space
550         hscale=\Gin@scalex\space 1000 mul
551         vscale=\Gin@scaley\space 1000 mul}}
552 </dvi2ps>

```

18 pctxps

A L^AT_EX 2_ε graphics driver file for Personal TeX's PTI Laser/PS; from information supplied by Lance Carnes and Tao Wang <pti@crl.com>.

```

553 (*pctxps)

```

18.1 Graphic file inclusion

```

554 \def\Gininclude@eps#1{%
555 \message{<#1>}%
556 \ifGin@clip
557 \typeout{no clipping support in pctxps}%
558 \fi
559 \Gin@req@width.03515\Gin@req@width
560 \Gin@req@height.03515\Gin@req@height
561 \special{ps:#1\space x=\strip@pt\Gin@req@width cm,
562         y=\strip@pt\Gin@req@height cm}}
563 \def\Gininclude@ps#1{%
564 \message{<#1>}%
565 \ifGin@clip
566 \typeout{no clipping support in pctxps}%
567 \fi
568 \hbox{\kern-\Gin@llx bp\raise-\Gin@lly bp\hbox{\special{ps:#1}}}%
569 \typeout{^^J%
570 -----^^J%
571 .ps graphics without bounding box information cannot be^^J%
572 scaled. If the file actually contains the information,^^J%
573 please rename the file to .eps file extension.^^J%
574 -----^^J}}
575 \def\Gin@extensions{.eps,.ps}
576 \@namedef{Gin@rule@.ps}#1{{ps}{.ps}{#1}}
577 \@namedef{Gin@rule@.eps}#1{{eps}{.eps}{#1}}
578 \def\Gin@PS@raw#1{\special{ps::#1}}
579 \def\Grot@start{%
580 \special{ps::gsave currentpoint
581 currentpoint translate \Grot@angle\space
582 rotate neg exch neg exch translate}}
583 \def\Grot@end{\special{ps:: currentpoint grestore moveto}}
584 \def\Gscale@start{\special{ps:: currentpoint currentpoint translate
585 \Gscale@x\space \Gscale@y\space scale neg exch neg exch translate}}
586 \def\Gscale@end{\special{ps:: currentpoint currentpoint translate
587 1 \Gscale@x\space div 1 \Gscale@y\space div scale
588 neg exch neg exch translate}}
589 </pctxps>

```

19 pctx32

A L^AT_EX 2_ε graphics driver file for Personal TeX's PC TeX for 32 bit Windows;
Code supplied by Tao Wang <pti@crl.com>.

19.1 Colour

Uses the generic 'color1' code.

```
590 \pctx32
```

19.2 Graphic file inclusion

```
591 % including PostScript graphics
592 \def\Gininclude@eps#1{%
593   \message{<#1>}%
594   \bgroup
595   \def\@tempa{!}%
596   \dimen@ \Gin@req@width
597   \dimen@ii.1bp%
598   \divide \dimen@ \dimen@ii
599   \@tempdima \Gin@req@height
600   \divide \@tempdima \dimen@ii
601   \special{PSfile="#1"\space
602     llx=\Gin@llx\space
603     lly=\Gin@lly\space
604     urx=\Gin@urx\space
605     ury=\Gin@ury\space
606     \ifx \Gin@scalex \@tempa \else rwi=\number \dimen@ \space \fi
607     \ifx \Gin@scaley \@tempa \else rhi=\number \@tempdima \space \fi
608     \ifGin@clip clip \fi}%
609   \egroup}

    including BMP graphics
610 \def\Gininclude@bmp#1{%
611   \message{<#1>}%
612   \ifGin@clip
613     \typeout{no clipping support for BMP graphics in PCTeX32}%
614   \fi
615   \Gin@req@width.03515 \Gin@req@width
616   \Gin@req@height.03515 \Gin@req@height
617   \special{bmp:#1\space x=\strip@pt \Gin@req@width cm,
618     y=\strip@pt \Gin@req@height cm}}

    including WMF graphics
619 \def\Gininclude@wmf#1{%
620   \message{<#1>}%
621   \ifGin@clip
622     \typeout{no clipping support for WMF graphics in PCTeX32}%
623   \fi
624   \Gin@req@width.03515 \Gin@req@width
625   \Gin@req@height.03515 \Gin@req@height
626   \special{wmf:#1\space x=\strip@pt \Gin@req@width cm,
627     y=\strip@pt \Gin@req@height cm}}
```

19.3 Scaling and Rotating

PostScript rotation and scaling

```
628 \def\Grot@start{%
629   \special{ps:: gsave currentpoint
630   currentpoint translate \Grot@angle\space neg
631   rotate neg exch neg exch translate}}
632 \def\Grot@end{\special{ps:: currentpoint grestore moveto}}
633 \def\Gscale@start{\special{ps:: currentpoint currentpoint translate
634   \Gscale@x\space \Gscale@y\space scale neg exch neg exch translate}}
635 \def\Gscale@end{\special{ps:: currentpoint currentpoint translate
636   1 \Gscale@x\space div 1 \Gscale@y\space div scale
637   neg exch neg exch translate}}

638 \def\Gin@PS@raw#1{\special{ps:: #1}}
639 \def\Gin@PS@restored#1{\special{" #1}}
```

19.4 Default Extensions

```
640 \def\Gin@extensions{.eps,.ps,.wmf,.bmp}
641 \@namedef{Gin@rule@.ps}#1{{eps}{.ps}{#1}}
642 \@namedef{Gin@rule@.eps}#1{{eps}{.eps}{#1}}
643 \@namedef{Gin@rule@.bmp}#1{{bmp}{.}{#1}}
644 \@namedef{Gin@rule@.wmf}#1{{wmf}{.}{#1}}

645 </pctex32>
```

20 pctexwin

A L^AT_EX 2_ε graphics driver file for Personal TeX's PC TeX for Windows; from information supplied by Lance Carnes and Tao Wang <pti@crl.com>.

```
646 <*pctexwin>
```

20.1 Graphic file inclusion

```
647 \def\Gininclude@eps#1{%
648   \message{<#1>}%
649   \ifGin@clip
650     \typeout{no clipping support in pctexwin}%
651   \fi
652   \Gin@req@width.03515\Gin@req@width
653   \Gin@req@height.03515\Gin@req@height
654   \special{eps:#1\space x=\strip@pt\Gin@req@width cm,
655             y=\strip@pt\Gin@req@height cm}}

656 \def\Gininclude@ps#1{%
657   \message{<#1>}%
658   \ifGin@clip
659     \typeout{no clipping support in pctexwin}%
660   \fi
661   \hbox{\kern-\Gin@llx bp\raise-\Gin@lly bp\hbox{\special{ps:#1}}}%
662   \typeout{^^J%
663   -----^^J%
664   .ps graphics without bounding box information cannot be^^J%
665   scaled. If the file actually contains the information,^^J%}
```

```

666 please rename the file to .eps file extension.^^J%
667 -----^^J%
668 }}

669 \def\Gininclude@bmp#1{%
670 \message{<#1>}%
671 \ifGin@clip
672 \typeout{no clipping support in pctxwin}%
673 \fi
674 \Gin@req@width.03515\Gin@req@width
675 \Gin@req@height.03515\Gin@req@height
676 \special{bmp:#1\space x=\strip@pt\Gin@req@width cm,
677 y=\strip@pt\Gin@req@height cm}}

678 \def\Gininclude@wmf#1{%
679 \message{<#1>}%
680 \ifGin@clip
681 \typeout{no clipping support in pctxwin}%
682 \fi
683 \Gin@req@width.03515\Gin@req@width
684 \Gin@req@height.03515\Gin@req@height
685 \special{wmf:#1\space x=\strip@pt\Gin@req@width cm,
686 y=\strip@pt\Gin@req@height cm}}

687 \def\Gin@extensions{.eps,.ps,.wmf,.bmp}
688 \@namedef{Gin@rule@.bmp}#1{{bmp}}{#1}}
689 \@namedef{Gin@rule@.wmf}#1{{wmf}}{#1}}
690 \@namedef{Gin@rule@.ps}#1{{ps}}{.ps}{#1}}
691 \@namedef{Gin@rule@.eps}#1{{eps}}{.eps}{#1}}
692 \end{pctxwin}

```

21 pctxhp

A L^AT_EX 2_ε graphics driver file for Personal TeX's PTI Laser/HP; from information supplied by Lance Carnes and Tao Wang <pti@crl.com>.

```
693 \begin{pctxhp}
```

21.1 Graphic file inclusion

```

694 \def\Gininclude@pcl#1{%
695 \message{<#1>}%
696 \ifGin@clip
697 \typeout{no clipping support in pctxhp}%
698 \fi
699 \hbox{\kern-\Gin@llx bp\raise-\Gin@lly bp\hbox{\special{pcl:#1}}}%
700 \typeout{WARNING: pctxhp does not permit graphics to be scaled}}
701 \@namedef{Gin@rule@.pcl}#1{{pcl}}{#1}}
702 \def\Gin@extensions{.pcl}
703 \end{pctxhp}

```

22 pubps

A L^AT_EX 2_ε graphics driver file for Arbortext's PUBps; information from Peter R Wilson pwilson@rdrc.rpi.edu.

```
704 \begin{pubps}
```

22.1 Rotation

```
705 \def\Grot@start{\special{ps: gsave currentpoint
706         currentpoint translate \Grot@angle\space
707         rotate neg exch neg exch translate}}
708 \def\Grot@end{\special{ps: currentpoint grestore moveto}}
709 \end{pubps}
```

23 dviwin

A L^AT_EX 2_ε graphics driver file for Hippocrates Sendoukas' dviwin

```
710 \def\*dviwin
```

23.1 Graphic file inclusion

Dviwin sorts out the graphics type itself based on extension. They all use the same `\special`, so as far as `graphics.sty` is concerned they are all the same 'type'. Use 'bmp' for the type as that is as good a name as any. Make this the default.

```
711 \namedef{Gin@rule@*}#1{{\special{ps: gsave currentpoint
712         currentpoint translate \Grot@angle\space
713         rotate neg exch neg exch translate}}
714 \special{ps: grestore moveto}}
715 \end{pubps}
```

The only exception is EPS files, as they may be read for BoundingBox

```
716 \namedef{Gin@rule@.ps}#1{{\special{ps: gsave currentpoint
717         currentpoint translate \Grot@angle\space
718         rotate neg exch neg exch translate}}
719 \special{ps: grestore moveto}}
720 \end{pubps}
```

Add a few default extensions so `\includegraphics{a}` will pick up `a.eps` or `a.wmf`. This list can be reset with `\DeclareGraphicsExtensions`. Other extensions not in the list may be used explicitly, eg `\includegraphics{a.gif}` should work as long as dviwin has access to a gif filter. If `.gif` is added using `\DeclareGraphicsExtensions` then `\includegraphics{a}` would also find `a.gif`.

```
719 \def\Gin@extensions{.eps,.ps,.wmf,.tif}
720 \end{pubps}
```

24 ln

A L^AT_EX 2_ε graphics driver file for B Hamilton Kelly's ln03 driver. Untested, but based on the graphics macros distributed with the driver.

```
721 \def\*ln
```

24.1 Graphic file inclusion

```
722 \def\Gin@rule@#1{{\special{ln03:sixel #1}}
723 \end{pubps}
```

25 truetex

A L^AT_EX 2_ε graphics driver file for Kinch 'truetex' driver.

```
724 \def\*truetex
```

25.1 Colour

Uses the ‘color4’ colour code.

25.2 Graphic file inclusion

EPS File inclusion: DVIPS style.

```
725 \def\Gininclude@eps#1{%
726   \message{<#1>}%
727   \bgroup
728   \def\@tempa{!}%
729   \dimen@{\Gin@req@width
730     \dimen@ii.1bp%
731     \divide\dimen@{\dimen@ii
732       \@tempdima\Gin@req@height
733       \divide\@tempdima\dimen@ii
734       \special{PSfile="#1"\space
735         llx=\Gin@llx\space
736         lly=\Gin@lly\space
737         urx=\Gin@urx\space
738         ury=\Gin@ury\space
739         \ifx\Gin@scalex\@tempa\else rwi=\number\dimen@\space\fi
740         \ifx\Gin@scaley\@tempa\else rhi=\number\@tempdima\space\fi
741         \ifGin@clip clip\fi}%
742   \egroup}
```

bmp File Inclusion.

```
743 \def\Gininclude@bmp#1{%
744   \message{<#1>}%
745   \special{bmpfile #1}}
```

tif(f) File inclusion

```
746 \def\Gininclude@tiff#1{%
747   \message{<#1>}%
748   \special{tiff file #1}}
```

25.3 Literal PostScript

This is not supported, so uses ‘nops’ code.

25.4 Default Rules

Support (e)ps, tif and bmp, default to eps.

```
749 \def\Gin@extensions{.eps,.ps}
750 \@namedef{\Gin@rule@.ps}#1{{eps}}{.ps}{#1}}
751 \@namedef{\Gin@rule@.eps}#1{{eps}}{.eps}{#1}}
752 \@namedef{\Gin@rule@.tif}#1{{tiff}}{tiff}{#1}}
753 \@namedef{\Gin@rule@.bmp}#1{{bmp}}{bmp}{#1}}
754 \@namedef{\Gin@rule@*}#1{{eps}}{\Gin@ext}{#1}}
755 </truetex>
```

26 tcidvi

A L^AT_EX 2_ε graphics driver file for Scientific Word/Workplace. Actually for the Kinch truetex driver, augmented with extra `\special` handling with the DLL supplied with SW.

756 `{*tcidvi}`

26.1 Colour

Uses the ‘color4’ colour code.

The above colours are handled by the Kinch-supplied dll The TCI dll adds support for `\colorbox`, but only grey scale The code below accepts any color model, but only the red component is used.

```
757 \AtBeginDocument{\def\color@block#1#2#3{%
758   {\rlap{\ifcolors@
759     \@defaultunits\count@\current@color\@nnil
760     \dimen@\count@\p@
761     \divide\dimen@\@cc@lv
762     \dimen@ii#2%
763     \advance\dimen@ii#3%
764     \lower#3\hbox{%
765       \special{language "Scientific Word";%
766         type "greybox";%
767         greyscale \strip@pt\dimen@;%
768         height \the\dimen@ii;%
769         width \the#1;%
770         depth 0pt;}}%
771     \fi}}}}
```

26.2 Graphic file inclusion

EPS File inclusion.

```
772 \def\Gininclude@eps#1{%
773   \message{<#1>}%
774   \raise\Gin@req@height\hbox{%
```

If the bounding box has been changed by a trim or viewport key then need to calculate the crop ratios based on the original bb coordinates. (This assumes that clip key is also used).

```
775   \ifx\Gin@ollx\@undefined
776   \else
777     \@tempdimb \Gin@ourx bp%
778     \advance\@tempdimb-\Gin@ollx bp%
779     \@tempdima\Gin@llx bp%
780     \advance\@tempdima-\Gin@ollx bp%
781     \Gscale@div\TCI@cropleft\@tempdima\@tempdimb
782     \@tempdima\Gin@urx bp%
783     \advance\@tempdima-\Gin@ollx bp%
784     \Gscale@div\TCI@cropright\@tempdima\@tempdimb
785     \@tempdimb \Gin@oury bp%
786     \advance\@tempdimb-\Gin@olly bp%
787     \@tempdima\Gin@lly bp%
788     \advance\@tempdima-\Gin@olly bp%
```

```

789 \Gscale@div\TCI@cropbottom\@tempdima\@tempdimb
790 \@tempdima\Gin@ury bp%
791 \advance\@tempdima-\Gin@olly bp%
792 \Gscale@div\TCI@croptop\@tempdima\@tempdimb
793 \fi
794 \special{%
795   language \TCI@language;%
796   type \TCI@type;%
797   valid_file \TCI@validfile;%
798   width \the\Gin@req@width;%
799   height \the\Gin@req@height;%
800   depth 0pt;%
801   original-width \the\Gin@nat@width;%
802   original-height \the\Gin@nat@height;%
803   cropleft "\TCI@cropleft";%
804   croptop "\TCI@croptop";%
805   cropright "\TCI@cropright";%
806   cropbottom "\TCI@cropbottom";%
807   filename '#1';%
808   \ifx\TCI@temp\@empty\else tempfilename \TCI@temp;\fi
809   }}

```

Default values so documents produced elsewhere should work

```

810 \def\TCI@language{"Scientific Word"}
811 \def\TCI@type{"GRAPHIC"}
812 \def\TCI@validfile{'F'}
813 \def\TCI@cropleft{0}
814 \def\TCI@croptop{1}
815 \def\TCI@cropright{1}
816 \def\TCI@cropbottom{0}
817 \let\TCI@temp\@empty

```

Non PS Graphic files.

File inclusion macro is always the same. Use a different name though as LaTeX thinks it can read eps files for BoundingBox.

```

818 \let\Gininclude@bmp\Gininclude@eps

```

26.3 Literal PostScript

This is not supported, so uses 'nops' code.

26.4 Default Rules

SW always gives the full name with extension. So leave this list empty.

```

819 \def\Gin@extensions{}

```

.ps .PS .eps .EPS are (E)PS rest are 'bmp' which is a catch all type for anything that the import filter can handle.

```

820 \@namedef{Gin@rule@.ps}#1{{eps}}{.ps}{#1}}
821 \@namedef{Gin@rule@.eps}#1{{eps}}{.eps}{#1}}
822 \@namedef{Gin@rule@.PS}#1{{eps}}{.PS}{#1}}
823 \@namedef{Gin@rule@.EPS}#1{{eps}}{.EPS}{#1}}
824 \@namedef{Gin@rule@*}#1{{bmp}}{\Gin@ext}{#1}}
825 \tcidvi

```

27 Literal Postscript

Most drivers writing to PostScript allow some form of ‘literal’ PostScript `\special` that inserts code into the final PostScript output. However Non-PS drivers can not support this (and some PS one’s can’t either). The code here makes all these commands no ops. Individual driver sections may define the commands to do something useful.

```
826 \*nops
```

Raw PostScript code, no save/restore. Coordinate system unspecified.

```
827 \def\Gin@PS@raw#1{}
```

PostScript code, to be surrounded by save/restore by the driver. Coordinate system standard PostScript, but with origin at current (TeX) position.

```
828 \def\Gin@PS@restored#1{}
```

PostScript code to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```
829 \def\Gin@PS@literal@header#1{}
```

Name of external file, the contents of which are to be inserted in the Header section of the final PostScript. Must be issued on the first page of a document.

```
830 \def\Gin@PS@file@header#1{}
```

```
831 \nops
```

28 Graphics Inclusion Rules

```
832 \*psrules
```

```
833 \def\Gin@extensions{.eps,.ps}
```

```
834 \@namedef{Gin@rule@.ps}#1{{eps}{.ps}{#1}}
```

```
835 \@namedef{Gin@rule@.eps}#1{{eps}{.eps}{#1}}
```

```
836 \@namedef{Gin@rule@*}#1{{eps}{\Gin@ext}{#1}}
```

```
837 \psrules
```

```
838 \*psrulesZ
```

```
839 \def\Gin@extensions{.eps,.ps,.eps.gz,.ps.gz,.eps.Z,.mps}
```

```
840 \@namedef{Gin@rule@.ps}#1{{eps}{.ps}{#1}}
```

```
841 \@namedef{Gin@rule@.eps}#1{{eps}{.eps}{#1}}
```

```
842 \@namedef{Gin@rule@.mps}#1{{eps}{.mps}{#1}}
```

```
843 \@namedef{Gin@rule@.pz}#1{{eps}{.bb}{#1}}
```

```
844 \@namedef{Gin@rule@.eps.Z}#1{{eps}{.eps.bb}{#1}}
```

```
845 \@namedef{Gin@rule@.ps.Z}#1{{eps}{.ps.bb}{#1}}
```

```
846 \@namedef{Gin@rule@.ps.gz}#1{{eps}{.ps.bb}{#1}}
```

```
847 \@namedef{Gin@rule@.eps.gz}#1{{eps}{.eps.bb}{#1}}
```

```
848 \@namedef{Gin@rule@*}#1{{eps}{\Gin@ext}{#1}}
```

```
849 \psrulesZ
```

```
850 \*dosrules
```

```
851 \!psrulesZ\def\Gin@extensions{.eps,.ps,.pcx,.bmp}
```

```
852 \@namedef{Gin@rule@.pcx}#1{{bmp}{}}{#1}}
```

```
853 \@namedef{Gin@rule@.bmp}#1{{bmp}{}}{#1}}
```

```

854 \@namedef{Gin@rule@.msp}#1{{bmp}}{#1}}
855 </dosrules>
856 <*macrules>
857 %\def\Gin@extensions{, .ps, .eps, .pict}
858 %\@namedef{Gin@rule@.ps}#1{{eps}}{.ps}{#1}}
859 %\@namedef{Gin@rule@.eps}#1{{eps}}{.eps}{#1}}
860 \@namedef{Gin@rule@.pict}#1{{pict}}{#1}}
861 \@namedef{Gin@rule@.pntg}#1{{pntg}}{#1}}
862 %\@namedef{Gin@rule@}#1{{pict}}{\relax}{#1}}
863 </macrules>
864 <*tiffrules>
865 \@namedef{Gin@rule@.tif}#1{{tiff}}{#1}}
866 </tiffrules>

```